



ISO 9001 CERTIFIED COMPANY

# Ring Seal Smoke Repair

Part #: 44416

473 mL (16 FL OZ)

## Ring Seal Smoke Repair

Rislone® Ring Seal® Smoke Repair is formulated to help stop blue exhaust smoke, reduce oil burning and prevent plug fouling caused from “blow-by”. Blow-by is usually caused by gaps in internal engine parts resulting from excess wear. Ring Seal contains high-shear polymers which provide a seal for worn pistons and rings to stop blow-by.

High kilometre / mileage formula is specifically designed for older higher kilometre engines. Viscosity improver cushions and coats engine parts helping to reduce wear and quiet noisy engines. All weather formula retains oil flow characteristic in hot and cold weather.

Works on petrol, LPG and diesel engines with conventional, high kilometre and synthetic engine oils. Can be added anytime, top off oil when low or while changing oil.

### Protecting Engines Since 1921

### Stops Blue Exhaust Smoke and Reduces Oil Burning

### Seals Worn Pistons & Rings

### High-Kilometre Formula



### INSTRUCTIONS:

Add entire bottle of Ring Seal Smoke Repair to engine crankcase at or between oil changes. Idle or drive engine for 5 minutes after installation. Add Ring Seal Smoke Repair every 3500 km or with every oil change. If smoke continues, second application may be required or mechanical attention is needed.

### DOSAGE:

One bottle treats 4 to 6 litres of oil for regular 4, 6 and 8 cylinder engines. For larger engines, use one bottle for every 5 litres of capacity. On 4-Stroke ATV, Motorcycle and small engines, including wet clutch applications, use approximately 89 mL per liter of oil capacity.