



ISO 9001 CERTIFIED

RISLONE TECHNICAL BULLETIN

Tech Bulletin #: TB-44471-1

Page 1 of 1

Date 1st Issued: 22 February 2013

Date Revised: 23 July, 2013

Rislone 710 Oil Treatment

Part #: 44471

HIGH-PERFORMANCE OIL TREATMENT

Rislone Oil Treatment is a high-viscosity formula developed for older and higher mileage engines to increase oil film thickness, building a thicker oil cushion and increasing oil pressure in worn engines.

- Cushions and coats engine parts to reduce friction and wear by preventing metal-to-metal contact between moving parts giving your vehicle longer engine life.
- Increased oil pressure equals increased power and a quieter running engine.
- Improved high-performance formula performs better in both hot and cold weather.
- Works with all petrol and diesel engines using conventional, high kilometre and synthetic oil.
- Use on any 4, 6 and 8 cylinder Car, Ute, Truck, Van or SUV

INSTRUCTIONS

Bring engine up to normal operating temperature. Add entire can of Rislone Oil Treatment to engine crankcase.

For badly worn engines, use two cans.

Rislone Oil Treatment may be used anytime, at or between oil changes.

DOSAGE

1 bottle treats 4 to 6 liters of oil. For larger systems use one can for every 5 liters of oil.



TEST	ASTM	TYPICAL PROPERTIES
Specific Gravity @ 15.6°C	D-4052	0.8550
Flash Point	D-92	210°C
Viscosity, cSt. @ 40°C	D-445	4173
Viscosity, cSt. @ 100°C	D-445	415
Viscosity Index	D-445	271
Pour Point °C	D-97	-18

Part Number:	44471
UPC Item:	0 78615 44471 7
UPC Case:	1 00 78615 44471 4
Bottle Size:	443 mL
Bottle Size (cm):	6.9 x 6.9 x 16
Bottle Cube:	762
Case Pack:	12
Case Size (cm):	28.7 x 21.7 x 17.5
Case Cube:	10 899
Case Weight (kg):	5.3
Pallet:	TI 18 HI 9 Total 162
Pallet Height (m):	1.65