

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 15 August 2019

## 1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** Rislone Diesel Additive - Left Side
- **Product code:** 44740
- **Recommended use and restriction on use**
- **Recommended use:** Treatment for diesel fuel.
- **Restrictions on use:** No further relevant information available.

- **Details of the supplier of the Safety Data Sheet**

- **Manufacturer/Supplier:**

Rislone  
P.O. Box 187  
Holly, MI 48442  
USA  
Phone: (810) 603-1321

- **Distributor:**

Smits Group Pty Ltd  
59 Greenmount Dr, East Tamaki, Auckland, New Zealand  
NZ Telephone: +09 274 6871  
AUS Telephone 1800883 888

- **Emergency telephone number:**

ChemTel Inc.  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)  
+1-300-954-583 (Australia)

Emergencies within Australia - 131126 (NSW Poison Control Centre)

Emergencies within New Zealand - 0800 764 766 (National Poison Control Centre)



## 2 Hazards identification

- **Classification (Australia, New Zealand)**

Australia NOHSC – Hazardous Substance (Classified according to Worksafe Australia NOHSC 2018 National Code of Practice)

New Zealand HSNO - Hazardous (Classified according to the Minimum Degrees of Hazard Regulations 2001)

- **Classification of the substance or mixture**

Flam. Liq. 4      H227 Combustible liquid.  
Carc. 2            H351 Suspected of causing cancer. Route of exposure: Inhalation.  
Asp. Tox. 1        H304 May be fatal if swallowed and enters airways.  
Aquatic Acute 3    H402 Harmful to aquatic life.  
Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- **Hazard statements (New Zealand HSNO Classification)**

HSNO 3.1D Flam. Liq. 4 H227 Combustible liquid.  
HSNO 6.7B Carc.. 2 H351 Suspected of causing cancer.  
HSNO 6.1E Asp. Tox 1 H304 May be fatal if swallowed and enters airways  
HSNO 9.1C Aquatic Acute 3 H402 Harmful to aquatic life.  
HSNO 9.1B Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- **Label elements**

(Cont'd. on page 2)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 15 August 2019

Trade name: Rislone Diesel Additive - Left Side

(Cont'd. from page 1)

- **Hazard pictograms**



GHS08 GHS09

- **Signal word** Danger

- **Hazard statements**

H227 Combustible liquid.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H304 May be fatal if swallowed and enters airways.

H402 Harmful to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

- **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from flames and hot surfaces. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P308+P313 If exposed or concerned: Get medical advice/attention.

P370+P378 In case of fire: Use to extinguish: CO2, powder or water spray.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards** There are no other hazards not otherwise classified that have been identified.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**

- **Components:**

CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydro- treated light Asp. Tox. 1, H304 Flam. Liq. 4, H227; Acute Tox. 5, H313	>60%
CAS: 27247-96-7 EINECS: 248-363-6	2-Ethylhexyl Nitrate Aquatic Chronic 2, H411 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332 Flam. Liq. 4, H227	<10%
CAS: 64742-94-5 EINECS: 265-198-5	Solvent naphtha (petroleum), heavy arom. Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	<10%

(Cont'd. on page 3)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 15 August 2019

## Trade name: Rislone Diesel Additive - Left Side

(Cont'd. from page 2)

	Flam. Liq. 4, H227	
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 Acute Tox. 5, H313	<10%
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Acute Tox. 5, H303; Aquatic Acute 2, H401	<10%
CAS: 64742-54-7 EINECS: 265-157-1	Distillates (petroleum), hydrotreated heavy paraffinic ⚠ Asp. Tox. 1, H304	<10%
CAS: 64742-55-8 EINECS: 265-158-7	Distillates (petroleum), hydrotreated light paraffinic ⚠ Asp. Tox. 1, H304	<10%
CAS: 91-20-3 EINECS: 202-049-5	Naphthalene ⚠ Flam. Sol. 2, H228 ⚠ Carc. 2, H351 ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Acute Tox. 4, H302 Acute Tox. 5, H313	<10%

• **Additional information:**

For the listed ingredient(s), the identity and/or exact percentages are being withheld as a trade secret.  
 For the wording of the listed Hazard Statements refer to section 16.

## 4 First aid measures

• **Description of first aid measures**

• **After inhalation:** Supply fresh air; consult doctor in case of complaints.

• **After skin contact:**

Immediately remove any clothing soiled by the product.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation is experienced, consult a doctor.

• **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while lying on their back should be turned onto their side.

• **Most important symptoms and effects, both acute and delayed**

Breathing difficulty

Coughing

• **Hazards:**

Danger of impaired breathing.

May be fatal if swallowed and enters airways.

Suspected of causing cancer. Route of exposure: Inhalation.

(Cont'd. on page 4)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 15 August 2019

**Trade name: Rislone Diesel Additive - Left Side**

(Cont'd. from page 3)

- **Indication of any immediate medical attention and special treatment needed**

If swallowed or in case of vomiting, danger of entering the lungs.  
 Medical supervision for at least 48 hours.  
 If necessary oxygen respiration treatment.  
 Later observation for pneumonia and pulmonary oedema.  
 If medical advice is needed, have product container or label at hand.

## 5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
  - Foam
  - Carbon dioxide
  - Fire-extinguishing powder
  - Gaseous extinguishing agents
  - Water haze or fog
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
  - Wear self-contained respiratory protective device.
  - Wear fully protective suit.
- **Additional information:** Eliminate all ignition sources if safe to do so.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
  - Particular danger of slipping on leaked/spilled product.
  - Wear protective equipment. Keep unprotected persons away.
  - Ensure adequate ventilation
  - Keep away from ignition sources.
  - Protect from heat.
  - For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.
- **Environmental precautions**
  - Do not allow to enter sewers/ surface or ground water.
  - Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
  - Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
  - Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**

(Cont'd. on page 5)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 15 August 2019

**Trade name: Rislone Diesel Additive - Left Side**

(Cont'd. from page 4)

- **Precautions for safe handling**  
Avoid splashes or spray in enclosed areas.  
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Flammable liquid and vapour.
- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**  
Store away from foodstuffs.  
Store away from oxidising agents.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

**95-63-6 1,2,4-trimethylbenzene**

REL (USA)	Long-term value: 125 mg/m <sup>3</sup> , 25 ppm
TLV (USA)	Long-term value: 123 mg/m <sup>3</sup> , 25 ppm

**91-20-3 Naphthalene**

WES (Australia)	Short-term value: 79 mg/m <sup>3</sup> , 15 ppm Long-term value: 52 mg/m <sup>3</sup> , 10 ppm
PEL (USA)	Long-term value: 50 mg/m <sup>3</sup> , 10 ppm
REL (USA)	Short-term value: 75 mg/m <sup>3</sup> , 15 ppm Long-term value: 50 mg/m <sup>3</sup> , 10 ppm
TLV (USA)	Long-term value: 52 mg/m <sup>3</sup> , 10 ppm Skin; BEI
WES (New Zealand)	Short-term value: 79 mg/m <sup>3</sup> , 15 ppm Long-term value: 52 mg/m <sup>3</sup> , 10 ppm suspected carcinogen

- **Exposure controls**
- **General protective and hygienic measures:**  
The usual precautionary measures are to be adhered to when handling chemicals.  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.
- **Respiratory protection:** Suitable respiratory protective device recommended.
- **Protection of hands:**



Protective gloves

(Cont'd. on page 6)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 15 August 2019

**Trade name: Rislone Diesel Additive - Left Side**

(Cont'd. from page 5)

The glove material has to be impermeable and resistant to the product.

· **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment:**

No further relevant information available.

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Appearance**

· <b>Form:</b>	Liquid
· <b>Colour:</b>	Clear to light yellow.
· <b>Odour:</b>	Mineral-oil-like
· <b>Odour threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Melting point/freezing point:** Not determined.

· **Initial boiling point and boiling range:** Not determined.

· **Flash point:** 64 °C (147.2 °F)

· **Flammability (solid, gas):** Flammable.

· **Auto/Self-ignition temperature:** Not determined.

· **Decomposition temperature:** Not determined.

· **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits**

· **Lower:** Not determined.

· **Upper:** Not determined.

· **Oxidising properties:** Non-oxidising.

· **Vapour pressure:** Not determined.

· **Density:**

· **Relative density:** Not determined.

· **Vapour density:** Not determined.

· **Evaporation rate:** Not determined.

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:** Not determined.

· **Viscosity**

· **Dynamic:** Not determined.

(Cont'd. on page 7)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 15 August 2019

Trade name: Rislone Diesel Additive - Left Side

(Cont'd. from page 6)

- |                          |  |
|--------------------------|--|
| <b>Kinematic:</b>        | Not determined.                            |
| <b>Other information</b> | No further relevant information available. |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**  
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**  
Flammable liquid and vapour.  
Used empty containers may contain product gases which form explosive mixtures with air.  
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
- **Conditions to avoid** Keep ignition sources away - Do not smoke.
- **Incompatible materials** Oxidising agents
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:** None.
- **Primary irritant effect**
- **Skin corrosion/irritation:** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation:** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation:** Based on available data, the classification criteria are not met.

<b>IARC (International Agency for Research on Cancer):</b>	
91-20-3   Naphthalene	2B

- **Probable routes of exposure:**  
Ingestion.  
Inhalation.  
Eye contact.  
Skin contact.
- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Suspected of causing cancer. Route of exposure: Inhalation.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:**  
Toxic to aquatic life with long lasting effects.

(Cont'd. on page 8)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 15 August 2019

Trade name: Rislone Diesel Additive - Left Side

(Cont'd. from page 7)

**27247-96-7 2-Ethylhexyl Nitrate**

LC50 | 2 mg/l (zebra fish) (96hr)

**64742-94-5 Solvent naphtha (petroleum), heavy arom.**

LC50 | 3.6 mg/l (Oncorhynchus mykiss)

**91-20-3 Naphthalene**

LC50 | 1-10 mg/l (daphnia)

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation**  
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT</b></li> <li>· <b>ADG, IMDG, IATA</b></li> </ul>   | <p style="margin: 0;">NA1993<br/>UN3082</p>   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>ADG</b></li> </ul> | <p style="margin: 0;">Combustible liquid, n.o.s. (stoddard solvent, propan-2-ol)<br/>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Ethylhexyl Nitrate, 1,2,4-trimethylbenzene)</p> |

(Cont'd. on page 9)



# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 15 August 2019

Trade name: Rislone Diesel Additive - Left Side

(Cont'd. from page 8)

<ul style="list-style-type: none"> <li>· <b>IMDG</b></li> <li>· <b>IATA</b></li> </ul>	<p>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2,4-trimethylbenzene, 2-Ethylhexyl Nitrate)</p> <p>ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2,4-trimethylbenzene, 2-Ethylhexyl Nitrate)</p>
--	---

- **Transport hazard class(es)**

- **DOT**



<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p>3</p> <p>3</p>
--	-------------------

- **ADG**



<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p>9 (M6)</p> <p>9</p>
--	------------------------

- **IMDG, IATA**



<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p>9</p> <p>9</p>
--	-------------------

- **Packing group**

<ul style="list-style-type: none"> <li>· <b>DOT, ADG, IMDG, IATA</b></li> </ul>	<p>III</p>
---	------------

- **Environmental hazards:**

<ul style="list-style-type: none"> <li>· <b>Marine pollutant:</b></li> </ul>	<p>Symbol (fish and tree)</p>
--	-------------------------------

- **Special precautions for user**

Warning: Miscellaneous dangerous substances and articles.

- **Danger code (Kemler):**

90

- **EMS Number:**

F-E,S-E

- **Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

- **Transport/Additional information:**

Not regulated when carried in single or combination packaging containing a net quantity of 5 L or less for liquids or 5 kg or less for solids per the following:  
 DOT: 171.4(c)(2)  
 ADR: SP 375  
 IMDG: 2.10.2.7  
 IATA: special provision A197

(Cont'd. on page 10)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 15 August 2019

**Trade name: Rislone Diesel Additive - Left Side**

(Cont'd. from page 9)

· DOT	Classified as combustible under US DOT regulations. Labeling is only required for single packages 119 US gal / 450 L.
· ADR/RID/ADN	
· Transport category	3
· Tunnel restriction code	-

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

- IARC (International Agency for Research on Cancer)

91-20-3 | Naphthalene

2B

- Australia

- Australian Inventory of Chemical Substances

All ingredients are listed.

- Standard for the Uniform Scheduling of Medicines and Poisons

Hydrocarbon Liquids

S6

- New Zealand HSR002583

- New Zealand Inventory of Chemicals (NZIOC)

All ingredients are listed.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H226 Flammable liquid and vapour.

H227 Combustible liquid.

H228 Flammable solid.

H302 Harmful if swallowed.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H400 Very toxic to aquatic life.

H401 Toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

(Cont'd. on page 11)

# Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 15 August 2019

**Trade name: Rislone Diesel Additive - Left Side**

(Cont'd. from page 10)

H411 Toxic to aquatic life with long lasting effects.

• **Abbreviations and acronyms:**

ADG: Australian Dangerous Goods Code

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

Flam. Sol. 2: Flammable solids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 5: Acute toxicity – Category 5

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

• **Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com