

**Xtreme Clean™ Super Radiator Flush**

Part #: 41201

650 mL (22 fl oz)



ISO 9001 CERTIFIED COMPANY

Rislone® Xtreme Cool Super Radiator Flush will help your cooling system by removing deposits that build up over time causing overheating. Heavy duty formulation is specially designed to clean solder bloom, oily residue, rust and scale. Non-acid formula is safe to use on all cooling system materials including copper, aluminum, plastic and rubber.

- **Use every time changing antifreeze.**
- **Neutralizes acids that cause corrosion and helps prevent formation of future scale deposits.**
- **Heavy Duty Xtreme Clean™ formula cleans entire cooling system.**
- **Clean systems run cooler.**

**Caution:** Never remove radiator cap if engine is hot.

**Note:** Protect from freezing.

**Dosage:** One bottle cleans up to 15 liter systems.

**Disposal:** Observe local laws and regulations. Where permitted, dispose of in a sanitary sewer system. Never pour on the ground or in a storm sewer system.

### Instructions For Use

Step 1. Allow engine to cool Drain system. Close drain.

Step 2. Add entire contents of bottle and refill system with water. For larger cooling systems use, use one bottle of Super Radiator Flush for every 12 litres. Reinstall cap.

Step 3. Start engine. After reaching normal operating temperature, run engine for 10 minutes with heater control on high.

*NOTE: For extremely dirty systems, run an additional 10 minutes.*

Step 4. Allow engine to cool. Flush cooling system and reservoir until water runs clear.

*TIP: Using a flush "T" with garden hose works best for final cleaning.*

Step 5. Close drain. Refill cooling system and reservoir with manufacturer's recommended antifreeze / water mixture. For best results add Rislone Hy-per Cool Super Coolant after flushing the system, as the metal surfaces inside the system are now cleaned and primed for optimal heat transfer performance and corrosion protection.

