

PRODUCT DATA SHEET



Rislone® Hy-per Cool™ Radiator Cleaner & Super Flush will help your cooling system by removing deposits that build up over time causing overheating. Heavy duty formulation is specially designed to clean solder bloom, oily residue, rust and scale. Contains water pump lubricant and corrosion inhibitors, so will not damage the pump like other brands.

- Fast, easy and safe to use on all cooling system materials, including plastic and aluminum. Works with all cooling systems.
- Eliminates damaging cooling deposits, reducing engine operating temperature to prevent overheating.
- Neutralizes acids that cause corrosion and helps prevent formation of future scale deposits.
- Heavy Duty Xtreme Clean™ formula cleans entire cooling system.
- Removes deposits and coolant gel for a complete cleaning in 30 minutes or less.
- Use every time changing coolant for light flushing or heavy duty cleaning.
- Clean systems run cooler.

Caution:

Never remove radiator cap if engine is hot.

Dosage:

One bottle treats up to 15 liter systems.

Directions:

Step 1. With engine off and cool, open radiator drain petcock and drain coolant into container for proper and safe disposal.

Step 2. Close petcock, pour entire contents of bottle and fill cooling system with water. Reinstall cap, start engine, turn heat on high, and run engine for 10 to 15 minutes. Turn off engine and allow to cool.

Step 3. Open radiator petcock and drain. Can be safely flushed to drain with no environmental concerns. Repeat this procedure one more time with straight water.

TIP: Using a flush "T" with garden hose works best for final cleaning. Step 4. Refill cooling system and reservoir with manufacturer's recommended antifreeze/water mixture. Reinstall radiator cap.

For best results add Hy-per Cool Super Coolant after flushing the system, as the metal surfaces inside the system are now cleaned and primed for optimal heat transfer performance and corrosion protection.



RISLONE

RISLONE. 10386 North Holly Road Holly, MI 48442 USA www.rislone.com USA