



ISO 9001 CERTIFIED

RISLONE TECHNICAL BULLETIN

Tech Bulletin #: TB-21211-2

Page 1 of 1

Date 1st Issued: 15, November 2010

Date Revised: 04, June 2018

Rislone 10 Minute Flush

Part #: 21211

RADIATOR 10 MINUTE FLUSH

Rislone Radiator 10-Minute Flush is fast, easy and safe to use. Contains no acid, needs no neutralizing. Compatible with all automotive cooling systems. Safe to use on Aluminum and Plastic Radiators. The best product to use when performing a normal cooling system service, like an antifreeze flush and fill.

- Use every time changing antifreeze.

DANGER: Opening cooling system while engine is hot or running may cause severe burns.

DISPOSAL

Observe local laws and regulations. Where permitted, dispose of in sanitary sewer systems. Never pour onto the ground or storm sewer system.

INSTRUCTIONS

1. Allow engine to cool. Drain system. Close drain.
2. Add entire contents of bottle and refill system with water. Reinstall cap.
3. After engine reaches normal operating temperature, run engine for 10 minutes with heater on and air conditioner off.
4. Allow engine to cool. Flush cooling system and reservoir until water runs clear.
5. Close drain. Refill cooling system and reservoir with manufacturer's recommended antifreeze / water mixture.

DOSAGE

1 bottle cleans a standard passenger car / light truck. For larger systems use one bottle for every 12 liters of capacity.



Part Number:	21211
UPC Item:	0 78615 21211 8
UPC Case:	4 00 78615 21211 6
Bottle Size:	355 ml
Bottle Size (cm):	6,4 x 6,4 x 15,5
Bottle Cube:	635
Case Pack:	6 bottles
Case Size (cm):	19,8 x 13,4 x 16,5
Case Cube:	4410
Case Weight (kg):	2,5
Pallet:	TI 44 HI 7 Total 308
Pallet Height (cm):	130