



ISO 9001 CERTIFIED

RISLONE TECHNICAL BULLETIN

Tech Bulletin #: TB-22012-1

Page 1 of 1

Date 1st Issued: 12, June 2008

Date Revised: 04, June 2018

Rislone Jack Oil With Stop Leak

Part #: 22012

JACK OIL WITH STOP LEAK

Rislone® Jack Oil with Stop Leak is specially designed to stop seal and o-ring leaks caused by normal jack wear and age. If you are having to add oil to your jack, it has a leak. Easy fill cap is great for topping fluid off.

Brings life back to old jacks and prevents leaks & seepage on newer jacks. Premium formulation reconditions seals to stop current and future leaks.

- Mixes All Approved Hydraulic Jack Oils
- Non-Corrosive, Non-Clogging & Non-Foaming
- Works in All Floor and Bottle Jacks
- Also Works With All Snow Plow Fluids



INSTRUCTIONS

Clean area around filler cap. Fill jack to proper level. Do not overfill. Cycle jack by lifting and releasing a few times to release any air caught in system. Leaks usually stop in a few days of normal use. If leak continues, a second application may be required or mechanical attention is needed.

DOSAGE

One bottle treats 2 to 3 litres of oil. For larger systems use one bottle for every 2 litres of oil capacity.

Part Number:	22012
UPC Item:	0 78615 22012 0
UPC Case:	4 00 78615 22012 8
Bottle Size:	370 ml
Bottle Size (mm):	8.6 x 4.6 x 23.6
Bottle Cube:	934
Case Pack:	6 bottles
Case Size (mm):	18 x 15 x 24.6
Case Cube:	6,997
Case Weight (kg):	2.3
Pallet:	TI 35 HI 6 Total 210
Pallet Height (cm):	163