

 ISO 9001 CERTIFIED	RISLONE TECHNICAL BULLETIN	
	Tech Bulletin #: TB-24326-1	Page 1 of 1
	Date 1 st Issued: 13, June 2008	Date Revised: 04, June 2018
	Rislone Smoke Eliminator With Stop Leak	Part #: 24326

RISLONE SMOKE ELIMINATOR WITH STOP LEAK

Rislone Smoke Eliminator with Stop Leak will reduce exhaust smoke and help stop oil burning caused by blow-by. Blow-by is usually caused by gaps in internal engine parts resulting from excess wear. Smoke Eliminator contains viscosity improvers that thicken the oil film filling these gaps. Smoke Eliminator cushions and coats engine parts helping reduce wear and quiet noisy lifters. Smoke Eliminator helps your engine last longer and makes your oil stronger. Rislone Eliminator with Stop Leak is compatible with ALL gasoline and diesel engines using conventional, high kilometre and synthetic engine oil. Use every 3 500 km at / or between oil changes.

3X ACTION FORMULA

- Stops Oil Loss
- Seals Oil Leaks
- Reduces Exhaust Smoke



Rislone Smoke Eliminator with Stop Leak will help relieve smoking caused from oil leaks, oil burning, worn & dry seals and blow-by.

INSTRUCTIONS

Add entire bottle of Rislone Smoke Eliminator with Stop Leak at / or between oil changes. Do not overfill system. If smoke continues, second application may be required or mechanical attention may be needed.

DOSAGE

1 bottle treats 4 to 6 litres of oil.

Part Number:	24326
UPC Item:	0 78615 34326 6
UPC Case:	4 00 78615 34326 4
Bottle Size:	500 mL
Bottle Dimensions:	8,6 x 5,1 x 19,3
Bottle Cube:	846
Case Pack:	6 bottles per case
Case Size:	18,5 x 16,2 x 20,3
Case Cube:	6083
Case Weight:	6.44 pounds 2.9 kg
Pallet:	TI 28 HI 6 Total 228
Pallet Height:	135,6 cm