



ISO 9001 CERTIFIED

RISLONE TECHNICAL BULLETIN

Tech Bulletin #: TB-24416-3

Page 1 of 1

Date 1st Issued: 22, March 2007

Date Revised: 06, June 2018

Rislone Ring Seal Smoke Repair

Part #: 24416

RING SEAL SMOKE REPAIR

Rislone® Ring Seal® is formulated to help stop blue exhaust smoke, reduce oil burning and prevent plug fouling caused by “blow-by”. Blow-by is usually caused by gaps in internal engine parts resulting from excess wear. Ring Seal contains viscosity improvers that thicken the oil film filling these gaps.

- Contains high-shear polymers which provide a seal for worn pistons & rings to stop blow-by.
- Cushions and coats engine parts helping to reduce wear and quiet noisy lifters.
- Stops blue exhaust smoke and reduces oil burning.
- Retains oil flow characteristics in hot and cold weather.
- Works on all 4, 6, and 8 cylinder vehicles.
- Use on any gasoline or diesel engines.
- Works with conventional, high kilometer and synthetic engine oils.
- Add to engine oil anytime.
- Protecting engines since 1921.



TEST	ASTM	TYPICAL PROPERTIES
Specific Gravity @ 15.6°C	D-1298	0.85 to 0.87
API Gravity	D-1298	35
Flash Point PMCC	D-93	180°C
Viscosity, cSt. @ 100°C	D-445	420 - 480
Pour Point °C	D-97	-15°C to -25°C

INSTRUCTIONS:

Add entire bottle of Ring Seal Smoke Repair to engine crankcase at or between oil changes. Idle or drive engine for 5 minutes after installation.

Add Ring Seal Smoke Repair every 4 000 km or with every oil change.

If smoke continues, second application may be required or mechanical attention is needed.

Part Number:	44416
UPC Item:	0 78615 24416 4
UPC Case:	4 00 78615 24416 2
Bottle Size:	473 mL
Bottle Size (cm):	8,6 X 5,1 X 19,3
Bottle Cube:	846
Case Pack:	6 bottles
Case Size (cm):	18,5 x 16,2 x 20,3
Case Cube:	6083
Case Weight (kg):	2,9
Pallet:	TI 38 HI 6 Total 228
Pallet Height (cm):	135.6

DOSAGE:

One bottle treats 4 to 6 liters of oil for regular 4, 6 and 8 cylinder engines. For larger engines, use 1 bottle for every liters of capacity. On 4-Stroke ATV, Motorcycle and small engines, including wet clutch applications, use approximately 100 mL per liter of oil capacity.