

 ISO 9001 CERTIFIED	RISLONE TECHNICAL BULLETIN	
	Tech Bulletin #: TB-24471-1	Page 1 of 1
	Date 1 st Issued: 23 October 2009	Date Revised: 04 June 2018
	Rislone 710 Oil Treatment	Part #: 24471

HIGH-PERFORMANCE OIL TREATMENT

Rislone Oil Treatment is a high-viscosity formula developed for older and higher mileage engines to increase oil film thickness, building a thicker oil cushion and increasing oil pressure in worn engines.

- Cushions and coats engine parts to reduce friction and wear by preventing metal-to-metal contact between moving parts giving your vehicle longer engine life.
- Increased oil pressure equals increased power and a quieter running engine.
- Improved high-performance formula performs better in both hot and cold weather.
- Works with all gasoline and diesel engines using conventional, high kilometer and synthetic oil.
- Use on any 4, 6 and 8 cylinder Car, Truck, Van or SUV

INSTRUCTIONS

Bring engine up to normal operating temperature. Add entire can of Rislone Oil Treatment to engine crankcase.

For badly worn engines, use two cans.

Rislone Oil Treatment may be used anytime, at or between oil changes.

DOSAGE

1 bottle treats 4 to 6 liters of oil. For larger systems use 1 bottle for every 5 liters of capacity.

TEST	ASTM	TYPICAL PROPERTIES
Specific Gravity @ 15.6°C	D-4052	0.8550
Flash Point	D-92	210°C
Viscosity, cSt. @ 40°C	D-445	4173
Viscosity, cSt. @ 100°C	D-445	415
Viscosity Index	D-445	271
Pour Point °C	D-97	-18



Part Number:	24471
UPC Item:	0 78615 24471 3
UPC Case:	4 00 78615 24471 1
Bottle Size:	443 mL
Bottle Size (cm):	6,9 x 6,9 x 16
Bottle Cube:	762
Case Pack:	12 bottles
Medidas caja (cm):	28,7 x 21,7 x 17x5
Volumen caja:	10899
Case Weight (kg):	5,3
Pallet:	TI 18 HI 9 Total 162
Pallet Height (cm):	165