



ISO 9001 CERTIFIED

## RISLONE TECHNICAL BULLETIN

Tech Bulletin #: TB-24629-0

Page 1 of 1

Date 1<sup>st</sup> Issued: 08, February 2013

Date Revised: 04 June 2018

Rislone Power Steering Stop Leak Concentrate

Part 24629

# POWER STEERING STOP LEAK CONCENTRATE

Rislone Power Steering Stop Leak Concentrate is specially designed to stop seal and o-ring leaks caused by normal power steering wear and age. Works on rack & pinion units, gear boxes and pumps. Keeps power steering seals soft and pliable. Non-corrosive, non-clogging and non-foaming.

Works with ALL domestic, import and heavy duty power steering fluid; including petroleum, mineral oil, synthetics and ATF automatic transmission fluid.

- Stops & Seals Steering Fluid Leaks
- Restores O-rings & Seals to Stop & Prevent Steering Leaks



### INSTRUCTIONS:

Add Stop Leak to power steering reservoir to restore fluid level. Do not overfill. Leaks usually stop in 300 km or 3 days of driving. If leak continues, a second application may be required or mechanical attention is needed.

### DOSAGE:

1 bottle treats up to 2,5 liters of fluid. For larger systems, use 1 bottle for every 2 liters of fluid capacity.

Part Number: 24629  
UPC Item: 0 78615 24629 8  
UPC Case: 4 00 78615 24629 6  
Bottle Size: 325 mL  
Bottle Size (cm): 7,6 x 4,6 x 16,5  
Bottle Cube: 577  
Case Pack: 6 bottles  
Case Size: 15,7 x 14 x 17,5  
Case Cube: 3846  
Case Weight (kg): 2,1  
Pallet: T1 48 HI 7 Total 336  
Pallet Height (cm): 163