



ISO 9001 CERTIFIED COMPANY

Smoke Eliminator

Part #: 24326

500 mL (16.9 FL OZ)

Smoke Eliminator with Stop Leak

Rislone® Smoke Eliminator with Stop Leak is formulated to help stop blue exhaust smoke, reduce oil burning, seal oil leaks and prevent plug fouling caused from “blow-by”. Blow-by is usually caused by gaps in internal engine parts resulting from excess wear. Smoke Eliminator contains high-shear polymers which provide a seal for worn pistons and rings to stop blow-by.

Oil treatment viscosity improver cushions and coats engine parts helping to reduce wear and quiet noisy engines. All weather formula retains oil flow characteristic in hot and cold weather. Smoke Eliminator helps your engine last longer and makes your oil stronger

Helps stop leaks caused by drying, hardening or shrinking of engine gaskets and oil seals.

Works on gasoline and diesel engines with conventional, high kilometre and synthetic engine oils.

Protecting Engines Since 1921

Stops Blue Exhaust Smoke and Oil Leaks

Seals Worn Pistons & Rings

3X Action Formula

Rislone Smoke Eliminator with Stop Leak will help relieve smoking caused from oil leaks, oil burning, worn & dry seals and blow-by.

INSTRUCTIONS:

Add entire bottle of Smoke Eliminator with Stop Leak to engine crankcase at or between oil changes. Idle or drive engine for 5 minutes after installation. Add Ring Seal Smoke Repair every 3500 km or with every oil change. If smoke or leaks continue, second application may be required or mechanical attention is needed.

DOSAGE:

One bottle treats 4 to 6 litres of oil for regular 4, 6 and 8 cylinder engines. For larger engines, use one bottle for every 5 litres of capacity. On 4-Stroke ATV, Motorcycle and small engines, including wet clutch applications, use approximately 100 mL per liter of oil capacity.

