



ISO 9001 CERTIFIED

RISLONE TECHNICAL BULLETIN

Tech Bulletin #: TB-4416-4

Page 1 of 1

Date 1st Issued: March 22, 2007

Date Revised: October 15, 2015

Rislone Ring Seal Smoke Repair

Part #: 4416

RING SEAL SMOKE REPAIR

Rislone® Ring Seal® is formulated to help stop blue exhaust smoke, reduce oil burning and prevent plug fouling caused from “blow-by”. Blow-by is usually caused by gaps in internal engine parts resulting from excess wear. Ring Seal contains viscosity improvers that thicken the oil film filling these gaps.

- Contains high-shear polymers which provide a seal for worn pistons & rings to stop blow-by.
- Cushions and coats engine parts helping to reduce wear and quiet noisy lifters.
- Stops blue exhaust smoke and reduces oil burning.
- Retains oil flow characteristics in hot and cold weather.
- Works on all 4, 6, and 8 cylinder vehicles.
- Use on any gasoline or diesel engines.
- Works with conventional, high mileage and synthetic engine oils.
- Add to engine oil anytime.
- Protecting engines since 1921.



TEST	ASTM	TYPICAL PROPERTIES
Specific Gravity @ 15.6°C	D-1298	0.85 to 0.87
API Gravity	D-1298	35
Flash Point PMCC	D-93	180°C / 356°F
Viscosity, cSt. @ 100°C	D-445	420 - 480
Pour Point °C	D-97	-15°C to -25°C

INSTRUCTIONS:

Add entire bottle of Ring Seal Smoke Repair to engine crankcase at or between oil changes. Idle or drive engine for 5 minutes after installation.

Add Ring Seal Smoke Repair every 2,000 miles or with every oil change.

If smoke continues, second application may be required or mechanical attention is needed.

Part Number:	4416
UPC Item:	0 78615 04416 0
UPC Case:	1 00 78615 04416 7
Bottle Size:	16 fl. oz. (472mL)
Bottle Dimensions:	3.4 X 2 X 7.6
Bottle Cube:	51
Case Pack:	6 bottles
Case Size:	7.3 x 6.4 x 8
Case Cube:	373
Case Weight:	6.61 pounds
Pallet:	TI 38 HI 6 Total 228
Pallet Height:	53.3 inches

DOSAGE:

One bottle treats 4 to 6 quarts of oil for regular 4, 6 and 8 cylinder engines. For larger engines, use 1 bottle for every 5 quarts of capacity. On 4-Stroke ATV, Motorcycle and small engines, including wet clutch applications, use approximately 3 ounces per quart of oil capacity.