



ISO 9001 CERTIFIED

RISLONE TECHNICAL BULLETIN

Tech Bulletin #: TB-4471-3

Page 1 of 1

Date 1st Issued: October 23, 2009

Date Revised: June 08, 2018

Rislone 710 Oil Treatment

Part #: 4471

HIGH-PERFORMANCE OIL TREATMENT

Rislone Oil Treatment is a high-viscosity formula developed for older and higher mileage engines to increase oil film thickness, building a thicker oil cushion and increasing oil pressure in worn engines.

- Cushions and coats engine parts to reduce friction and wear by preventing metal-to-metal contact between moving parts giving your vehicle longer engine life.
- Increased oil pressure equals increased power and a quieter running engine.
- Improved high-performance formula performs better in both hot and cold weather.
- Works with all gasoline and diesel engines using conventional, high mileage and synthetic oil.
- Use on any 4, 6 and 8 cylinder Car, Truck, Van or SUV

TEST	ASTM	TYPICAL PROPERTIES
Specific Gravity @ 15.6°C	D-4052	0.8550
Flash Point	D-92	210°C / 410°F
Viscosity, cSt. @ 40°C	D-445	4173
Viscosity, cSt. @ 100°C	D-445	415
Viscosity Index	D-445	271
Pour Point °C	D-97	-18

INSTRUCTIONS

Bring engine up to normal operating temperature. With engine off add entire can of Rislone Oil Treatment to engine crankcase. (where you add oil).

For badly worn engines, use two cans.

Rislone Oil Treatment may be used anytime, at or between oil changes.

DOSAGE:

One bottle treats 4 to 6 quarts of oil for regular 4, 6 and 8 cylinder engines. For larger engines, use 1 bottle for every 5 quarts of capacity. On 4-Stroke ATV, Motorcycle and small engines, including wet clutch applications, use approximately 3 ounces per quart of oil capacity.



Part Number: 4471
 UPC Item: 0 78615 04471 9
 UPC Case: 1 00 78615 04471 6
 Bottle Size: 15 fl. oz. (443 mL)
 Bottle Dimensions: 2.7 x 2.7 x 6.3
 Bottle Cube: 46
 Case Pack: 12 cans per case
 Case Size: 11.3 x 8.5 x 6.9
 Case Cube: 666
 Case Weight: 11.7 pounds
 Pallet: TI 18 HI 9 Total 162
 Pallet Height: 65 inches