

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

1 Identification

- **Product identifier**
- **Trade name: Rislone® Gas Treat Left Side**
- **Article number: 4700**
- **Recommended use and restriction on use**
- **Recommended use:** Treatment for gasoline.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Rislone
P.O. Box 187
Holly, MI 48442 USA
Phone: (810) 603-1321
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)



2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 3 H226 Flammable liquid and vapor.
Skin Irrit. 2 H315 Causes skin irritation.
Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
Repr. 2 H361 Suspected of damaging fertility or the unborn child.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**

GHS02 GHS07 GHS08
- **Signal word: Danger**
- **Hazard statements:**
H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H351 Suspected of causing cancer. Route of exposure: Inhalation.
H361 Suspected of damaging fertility or the unborn child.
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 1)










P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use foam, powder, or carbon dioxide for extinction.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

64742-81-0	Kerosine (petroleum), hydrodesulfurized  Flam. Liq. 3, H226  Asp. Tox. 1, H304	>50%
	Trade Secret  Skin Irrit. 2, H315 Eye Irrit. 2B, H320	<10%
91-20-3	naphthalene  Flam. Sol. 2, H228  Carc. 2, H351  Acute Tox. 4, H302	<5%
1330-20-7	xylene  Flam. Liq. 3, H226  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	<5%
64771-72-8	Paraffins (petroleum), normal C5-20  Asp. Tox. 1, H304 Flam. Liq. 4, H227	<5%

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 2)

100-41-4	ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H332	<1%
108-88-3	toluene ⚠ Flam. Liq. 2, H225 ⚠ Repr. 2, H361; STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 Eye Irrit. 2B, H320	<1%
111-77-3	2-(2-methoxyethoxy)ethanol ⚠ Repr. 2, H361 Flam. Liq. 4, H227	<1%

· **Additional information:** For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.
 Provide oxygen treatment if affected person has difficulty breathing.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.
 Seek medical treatment in case of complaints.

· **After eye contact:**

Remove contact lenses if worn.
 Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.
 Do not induce vomiting; immediately call for medical help.
 A person vomiting while lying on their back should be turned onto their side.

· **Most important symptoms and effects, both acute and delayed:**

Coughing
 Dizziness
 Breathing difficulty
 Gastric or intestinal disorders
 Irritant to skin and mucous membranes.

· **Danger:**

Danger of impaired breathing.
 Danger of convulsion.

· **Indication of any immediate medical attention and special treatment needed:**

If swallowed, gastric irrigation with added, activated carbon.
 If swallowed or in case of vomiting, danger of entering the lungs.
 Medical supervision for at least 48 hours.
 If necessary oxygen respiration treatment.
 Monitor circulation, possible shock treatment.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

Later observation for pneumonia and pulmonary edema.

(Cont'd. of page 3)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Foam
 - Alcohol resistant foam
 - Gaseous extinguishing agents
 - Carbon dioxide
 - Fire-extinguishing powder
 - Water fog / haze
- **For safety reasons unsuitable extinguishing agents:**
 - Water stream.
 - Water spray
- **Special hazards arising from the substance or mixture**
 - In case of fire, the following can be released:
 - Carbon monoxide (CO)
 - Nitrogen oxides (NO_x)
 - Sulphur dioxide (SO₂)
 - In certain fire conditions, traces of other toxic gases cannot be excluded.
- **Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Wear fully protective suit.
- **Additional information:** Cool endangered containers with water fog.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Use respiratory protective device against the effects of fumes/dust/aerosol.
 - Keep away from ignition sources.
 - Wear protective equipment. Keep unprotected persons away.
 - Ensure adequate ventilation.
 - Particular danger of slipping on leaked/spilled product.
- **Environmental precautions**
 - Do not allow to enter sewers/ surface or ground water.
 - Prevent from spreading (e.g. by damming-in or oil barriers).
 - Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
 - Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
 - Remove from the water surface (e.g. skim or suck off).
 - Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

See Section 13 for disposal information.

(Cont'd. of page 4)

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**
 - Keep out of reach of children.
 - Ensure good ventilation/exhaustion at the workplace.
 - Open and handle receptacle with care.
 - Avoid breathing mist, vapors, or spray.
 - Avoid contact with the eyes and skin.
- **Information about protection against explosions and fires:**
 - Keep respiratory protective device available.
 - Keep ignition sources away - Do not smoke.
- **Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:**
 - Avoid storage near extreme heat, ignition sources or open flame.
 - Store in cool, dry conditions in well sealed receptacles.
- **Information about storage in one common storage facility:**
 - Store away from foodstuffs.
 - Store away from oxidizing agents.
- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

64742-81-0 Kerosine (petroleum), hydrodesulfurized

REL (USA)	Long-term value: 100 mg/m ³ Kerosene only
TLV (USA)	Long-term value: 200 mg/m ³ as total hydrocarbon vapor; Skin; P
EV (Canada)	Long-term value: 200(G) mg/m ³ as total hydrocarbon vapour, Skin
LMPE (Mexico)	Long-term value: 200 mg/m ³ A3, PIEL

91-20-3 naphthalene

PEL (USA)	Long-term value: 50 mg/m ³ , 10 ppm
REL (USA)	Short-term value: 75 mg/m ³ , 15 ppm Long-term value: 50 mg/m ³ , 10 ppm

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 5)

TLV (USA)	Long-term value: 52 mg/m ³ , 10 ppm Skin; BEI
EL (Canada)	Short-term value: 15 ppm Long-term value: 10 ppm Skin; IARC 2B
EV (Canada)	Short-term value: 78 mg/m ³ , 15 ppm Long-term value: 52 mg/m ³ , 10 ppm
LMPE (Mexico)	Short-term value: 15 ppm Long-term value: 10 ppm A4, PIEL

1330-20-7 xylene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm
EV (Canada)	Short-term value: 650 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
LMPE (Mexico)	Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE

100-41-4 ethylbenzene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 87 mg/m ³ , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm IARC 2B
EV (Canada)	Short-term value: 540 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
LMPE (Mexico)	Long-term value: 20 ppm

108-88-3 toluene

PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL (USA)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV (USA)	Long-term value: 75 mg/m ³ , 20 ppm BEI

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 6)

EL (Canada)	Long-term value: 20 ppm R
EV (Canada)	Long-term value: 20 ppm
LMPE (Mexico)	Long-term value: 20 ppm A4, IBE

· Ingredients with biological limit values:
1330-20-7 xylene

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

100-41-4 ethylbenzene

BEI (USA)	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
	- Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

108-88-3 toluene

BEI (USA)	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

· Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Pregnant women should strictly avoid inhalation or skin contact.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

· Engineering controls: No relevant information available.

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 7)

- **Breathing equipment:**
Use suitable respiratory protective device in case of insufficient ventilation.
Use suitable respiratory protective device when aerosol or mist is formed.
For spills, respiratory protection may be advisable.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment**
No relevant information available.
- **Risk management measures** No relevant information available.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· Appearance:

Form: Liquid
Color: Orange

· **Odor:** Petroleum-like
· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Melting point/Melting range:** Not determined.

· **Boiling point/Boiling range:** >35°C (>95 °F)

· **Flash point:** 42.2°C (108 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Auto-ignition temperature:** Not determined.

· **Decomposition temperature:** Not determined.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits

Lower: Not determined.
Upper: Not determined.

· **Oxidizing properties:** Non-oxidizing.

· **Vapor pressure:** Not determined.

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 8)

- | | |
|---|-----------------------------------|
| · Density: | |
| Relative density: | 0.82 |
| Vapor density: | Not determined. |
| Evaporation rate: | Not determined. |
| · Solubility in / Miscibility with Water: | |
| Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): Not determined. | |
| · Viscosity | |
| Dynamic: | Not determined. |
| Kinematic at 40°C (104 °F): | 2.27mm ² /s |
| · Other information | |
| No relevant information available. | |

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Flammable liquid and vapor.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Reacts with oxidizing agents.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**
Carbon monoxide and carbon dioxide
Nitrogen oxides
Sulphur trioxide (SO₃) or SO₃-mist

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

91-20-3 naphthalene

Oral	LD50	490 mg/kg (rat)
Dermal	LD50	5000 mg/kg (rat)

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 9)

71-43-2 benzene

Oral	LD50	4894 mg/kg (rat)
Inhalative	LC50/4h	9980 mg/l (mouse)

- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** No sensitizing effects known.

· **Carcinogenic categories**· **IARC (International Agency for Research on Cancer):**

91-20-3	naphthalene	2B
100-41-4	ethylbenzene	2B
71-43-2	benzene	1

· **NTP (National Toxicology Program):**

91-20-3	naphthalene	R
98-82-8	cumene	R
71-43-2	benzene	K

· **OSHA-Ca (Occupational Safety & Health Administration):**

71-43-2	benzene
---------	---------

· **Probable route(s) of exposure:**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Suspected of causing cancer. Route of exposure: Inhalation.
- **Reproductive toxicity:** Suspected of damaging fertility or the unborn child.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

· **Toxicity**· **Aquatic toxicity**

Toxic to aquatic life with long lasting effects.

91-20-3 naphthalene

LC50	1-10 mg/l (daphnia)
------	---------------------

1330-20-7 xylene

LC50	13.4 mg/l (pimephales promelas)
------	---------------------------------

- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **Bioaccumulative potential:** Does not accumulate in organisms
- **Mobility in soil:** No relevant information available.

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 10)

- **Ecotoxicological effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- **Additional ecological information**
- **General notes:**
 Avoid transfer into the environment.
 Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Contact waste processors for recycling information.
 The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · UN-Number · DOT · ADR, IMDG, IATA | <ul style="list-style-type: none"> NA1993 UN1268 |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR, IMDG · IATA | <ul style="list-style-type: none"> Combustible liquid, n.o.s. (kerosene (petroleum), naphthalene) PETROLEUM PRODUCTS, N.O.S. Petroleum products, n.o.s. |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <ul style="list-style-type: none"> |
| <ul style="list-style-type: none"> · Class · Label | <ul style="list-style-type: none"> 3 Combustible liquids 3 |



(Cont'd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 11)

· ADR



· Class 3 (F1) Flammable liquids
 · Label 3

· IMDG, IATA



· Class 3 Flammable liquids
 · Label 3

· Packing group

· DOT, ADR, IMDG, IATA III

· Environmental hazards

Product contains environmentally hazardous substances: naphthalene

· Marine pollutant:



Yes

· Special precautions for user

Warning: Flammable liquids

· Danger code (Kemler):

30

· EMS Number:

F-E,S-E

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· DOT

Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥ 119 US gal / 450 L.
 Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

(Cont'd. on page 13)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 12)

· ADR


Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.1.8.1)

· IMDG


Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· IATA


Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each / 10 L net.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

91-20-3	naphthalene
1330-20-7	xylene

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Present in trace quantities.

· Proposition 65 (California)
· Chemicals known to cause cancer:

91-20-3	naphthalene
100-41-4	ethylbenzene
98-82-8	cumene

(Cont'd. on page 14)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 13)

71-43-2	benzene
842-07-9	C.I. Solvent Yellow 14

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

71-43-2 | benzene

· **Chemicals known to cause developmental toxicity:**

108-88-3 | toluene

67-56-1 | methanol

71-43-2 | benzene

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency):**

91-20-3	naphthalene	C, CBD
1330-20-7	xylene	I
100-41-4	ethylbenzene	D
108-88-3	toluene	II

· **IARC (International Agency for Research on Cancer):**

91-20-3	naphthalene	2B
100-41-4	ethylbenzene	2B
71-43-2	benzene	1

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

71-43-2 | benzene

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** October 20, 2017 / -

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

Flam. Sol. 2: Flammable solids – Category 2

(Cont'd. on page 15)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Left Side

(Cont'd. of page 14)

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
Carc. 2: Carcinogenicity – Category 2
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor_internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com