

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

1 Identification

- **Product identifier**
- **Trade name:** Rislone® Gas Treat Right Side
- **Product code:** 4700
- **Recommended use and restriction on use**
- **Recommended use:** Treatment for gasoline.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Rislone
P.O. Box 187
Holly, MI 48442 USA
Phone: (810) 603-1321
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)



2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 3 H226 Flammable liquid and vapor.
STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**



GHS02 GHS08

- **Signal word:** Danger
- **Hazard statements:**
H226 Flammable liquid and vapor.
H372 Causes damage to the central nervous system through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements:**
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist/vapors/spray.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Right Side

(Cont'd. of page 1)






P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use foam, powder, or carbon dioxide for extinction.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

8052-41-3	Stoddard solvent  Flam. Liq. 3, H226  STOT RE 1, H372; Asp. Tox. 1, H304	>80%
64742-56-9	Distillates (petroleum), solvent-dewaxed light paraffinic  Asp. Tox. 1, H304	5-10%
67-63-0	propan-2-ol  Flam. Liq. 2, H225  Eye Irrit. 2A, H319; STOT SE 3, H336	1-2.5%

· **Additional information:** For the wording of the listed Hazard Statements refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air; consult doctor in case of complaints.
Provide oxygen treatment if affected person has difficulty breathing.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment in case of complaints.

· **After eye contact:**

Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.
Do not induce vomiting; immediately call for medical help.
A person vomiting while lying on their back should be turned onto their side.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Right Side

(Cont'd. of page 2)

- **Most important symptoms and effects, both acute and delayed:**
 - Coughing
 - Dizziness
 - Breathing difficulty
 - Gastric or intestinal disorders
- **Danger:**
 - Danger of impaired breathing.
 - Danger of convulsion.
- **Indication of any immediate medical attention and special treatment needed:**
 - If swallowed, gastric irrigation with added, activated carbon.
 - If swallowed or in case of vomiting, danger of entering the lungs.
 - Medical supervision for at least 48 hours.
 - If necessary oxygen respiration treatment.
 - Monitor circulation, possible shock treatment.
 - Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Foam
 - Alcohol resistant foam
 - Gaseous extinguishing agents
 - Carbon dioxide
 - Fire-extinguishing powder
 - Water fog / haze
- **For safety reasons unsuitable extinguishing agents:**
 - Water stream.
 - Water spray
- **Special hazards arising from the substance or mixture**
 - Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Wear fully protective suit.
- **Additional information:** Cool endangered containers with water fog.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Use respiratory protective device against the effects of fumes/dust/aerosol.
 - Keep away from ignition sources.
 - Wear protective equipment. Keep unprotected persons away.
 - Ensure adequate ventilation.
 - Particular danger of slipping on leaked/spilled product.
- **Environmental precautions**
 - Do not allow to enter sewers/ surface or ground water.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Right Side

(Cont'd. of page 3)

Prevent from spreading (e.g. by damming-in or oil barriers).
Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up**

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
Remove from the water surface (e.g. skim or suck off).
Send for recovery or disposal in suitable receptacles.

- **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling**

- **Precautions for safe handling:**

Keep out of reach of children.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Avoid breathing mist, vapors, or spray.
Avoid contact with the eyes and skin.

- **Information about protection against explosions and fires:**

Keep respiratory protective device available.
Keep ignition sources away - Do not smoke.

- **Conditions for safe storage, including any incompatibilities**

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Avoid storage near extreme heat, ignition sources or open flame.
Store in cool, dry conditions in well sealed receptacles.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.
Store away from oxidizing agents.

- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

8052-41-3 Stoddard solvent

PEL (USA)	Long-term value: 2900 mg/m ³ , 500 ppm
REL (USA)	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV (USA)	Long-term value: 525 mg/m ³ , 100 ppm
EL (Canada)	Short-term value: 580 mg/m ³ Long-term value: 290 mg/m ³

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Right Side

(Cont'd. of page 4)

EV (Canada)	Long-term value: 525 mg/m ³
LMPE (Mexico)	Long-term value: 100 ppm

67-63-0 propan-2-ol

PEL (USA)	Long-term value: 980 mg/m ³ , 400 ppm
REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI
EL (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
EV (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
LMPE (Mexico)	Short-term value: 400 ppm Long-term value: 200 ppm A4, IBE

Ingredients with biological limit values:
67-63-0 propan-2-ol

BEI (USA)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----------	---

Exposure controls
Personal protective equipment:
General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

Engineering controls: No relevant information available.

Breathing equipment:

- Use suitable respiratory protective device in case of insufficient ventilation.
- Use suitable respiratory protective device when aerosol or mist is formed.
- For spills, respiratory protection may be advisable.

Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Eye protection:


Safety glasses

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Right Side

(Cont'd. of page 5)

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment**
No relevant information available.
- **Risk management measures** No relevant information available.

9 Physical and chemical properties

Information on basic physical and chemical properties

- **Appearance:**
 - **Form:** Liquid
 - **Color:** Light yellow
 - **Odor:** Petroleum-like
 - **Odor threshold:** Not determined.
- **pH-value:** Not determined.
- **Melting point/Melting range:** Not determined.
- **Boiling point/Boiling range:** >35°C (>95 °F)
- **Flash point:** 40.6°C (105.1 °F)
- **Flammability (solid, gaseous):** Not applicable.
- **Auto-ignition temperature:** Not determined.
- **Decomposition temperature:** Not determined.
- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
- **Explosion limits**
 - **Lower:** Not determined.
 - **Upper:** Not determined.
- **Oxidizing properties:** Non-oxidizing.
- **Vapor pressure:** Not determined.
- **Density:**
 - **Relative density:** 0.77
 - **Vapor density:** Not determined.
 - **Evaporation rate:** Not determined.
- **Solubility in / Miscibility with Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity**
 - **Dynamic:** Not determined.
 - **Kinematic at 40°C (104 °F):** 1.4mm²/s
- **Other information** No relevant information available.

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Right Side

(Cont'd. of page 6)

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Flammable liquid and vapor.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Reacts with oxidizing agents.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Slight irritant effect on skin and mucous membranes.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** No sensitizing effects known.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

- **Probable route(s) of exposure:**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:**
Causes damage to the central nervous system through prolonged or repeated exposure.

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Right Side

(Cont'd. of page 7)

- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity** No relevant information available.
- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **Bioaccumulative potential:** Does not accumulate in organisms
- **Mobility in soil:** No relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- **Additional ecological information**
- **General notes:** Avoid transfer into the environment.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Contact waste processors for recycling information.
The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|----------------------------------|--|
| · UN-Number | |
| · DOT | NA1993 |
| · ADR, IMDG, IATA | UN1268 |
| · UN proper shipping name | |
| · DOT | Combustible liquid, n.o.s. (stoddard solvent, propan-2-ol) |
| · ADR, IMDG | PETROLEUM PRODUCTS, N.O.S. |
| · IATA | Petroleum products, n.o.s. |

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Right Side

(Cont'd. of page 8)

· Transport hazard class(es)
· DOT


· **Class** 3 Combustible liquids
 · **Label** 3

· ADR


· **Class** 3 (F1) Flammable liquids
 · **Label** 3

· IMDG, IATA


· **Class** 3 Flammable liquids
 · **Label** 3

· Packing group

· **DOT, ADR, IMDG, IATA** III

· Environmental hazards

· **Marine pollutant:** No

· Special precautions for user

Warning: Flammable liquids
 · **Danger code (Kemler):** 30
 · **EMS Number:** F-E,S-E

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· **DOT** Classified as combustible under US DOT regulations. Labeling is only required for single packages ≥ 119 US gal / 450 L.

· ADR


Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Right Side

(Cont'd. of page 9)

· IMDG


Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

· IATA


Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each / 10 L net.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

67-63-0 | propan-2-ol

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· Proposition 65 (California)
· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories
· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29 CFR 1910.1200)

Printing date: October 20, 2017

Revision: October 20, 2017

Trade name: Rislone® Gas Treat Right Side
--

(Cont'd. of page 10)

· NIOSH-Ca (National Institute for Occupational Safety and Health):
--

None of the ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** October 20, 2017 / -

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor_internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com