

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200)


Revision: August 19, 2019

1 Identification

- **Product identifier**
- **Trade name: Rislone® Diesel Additive - Right Side**
- **Product code:** 4740
- **Recommended use and restriction on use**
- **Recommended use:** Treatment for diesel fuel.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Rislone
P.O. Box 187
Holly, MI 48442 USA
Phone: (810) 603-1321
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)



2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 3 H226 Flammable liquid and vapor.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**

 GHS02 GHS07 GHS08
- **Signal word:** Danger
- **Hazard statements:**
H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer. Route of exposure: Inhalation.
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.

(Cont'd. on page 2)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 1)















P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P331	Do NOT induce vomiting.
P321	Specific treatment (see on this label).
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: CO ₂ , powder or water spray.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

64742-47-8	Distillates (petroleum), hydro- treated light  Asp. Tox. 1, H304  Flam. Liq. 4, H227	60-80%
111-76-2	2-butoxyethanol  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319  Flam. Liq. 4, H227	10-<20%
64742-95-6	Hydrocarbons,C9,aromatics  Flam. Liq. 3, H226  Asp. Tox. 1, H304  STOT SE 3, H335-H336	<10%
112-80-1	oleic acid, pure  Eye Irrit. 2B, H320	<3%
64742-94-5	Solvent naphtha (petroleum), heavy arom.  Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336  Flam. Liq. 4, H227	<3%
95-63-6	1,2,4-trimethylbenzene  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	<3%

(Cont'd. on page 3)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 2)

108-67-8	mesitylene ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H335	<3%
1330-20-7	Xylene ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	<1%
98-82-8	Cumene ⚠ Flam. Liq. 3, H226 ⚠ Carc. 2, H351; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H302; STOT SE 3, H335	<1%
91-20-3	Naphthalene ⚠ Flam. Sol. 2, H228 ⚠ Carc. 2, H351 ⚠ Acute Tox. 4, H302	<1%

• **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
 For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

• **Description of first aid measures**

• **After inhalation:**

Supply fresh air.

Provide oxygen treatment if affected person has difficulty breathing.

If experiencing respiratory symptoms: Call a poison center/doctor.

• **After skin contact:**

Immediately remove any clothing soiled by the product.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash with soap and water.

If skin irritation continues, consult a doctor.

• **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

• **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

• **Most important symptoms and effects, both acute and delayed:**

Breathing difficulty

Dizziness

Coughing

Causes eye irritation.

Causes skin irritation.

• **Danger:**

Danger of impaired breathing.

May be fatal if swallowed and enters airways.

May cause cancer. Route of exposure: Inhalation.

(Cont'd. on page 4)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 3)

· **Indication of any immediate medical attention and special treatment needed:**

- If swallowed or in case of vomiting, danger of entering the lungs.
- Medical supervision for at least 48 hours.
- If necessary oxygen respiration treatment.
- Later observation for pneumonia and pulmonary edema.
- If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Foam
 - Carbon dioxide
 - Fire-extinguishing powder
 - Gaseous extinguishing agents
 - Water fog / haze
- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture** Flammable liquid and vapor.
- **Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Wear fully protective suit.
- **Additional information:** Eliminate all ignition sources if safe to do so.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Wear protective equipment. Keep unprotected persons away.
 - Ensure adequate ventilation.
 - Keep away from ignition sources.
 - Protect from heat.
 - For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.
- **Environmental precautions**
 - Do not allow to enter sewers/ surface or ground water.
 - Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
 - Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
 - Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

7 Handling and storage

- **Handling**
- **Precautions for safe handling:**

(Cont'd. on page 5)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 4)

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Flammable liquid and vapor.

- **Conditions for safe storage, including any incompatibilities**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Avoid storage near extreme heat, ignition sources or open flame.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

64742-47-8 Distillates (petroleum), hydro- treated light

EL (Canada)	Long-term value: 200 mg/m ³ Skin
-------------	--

111-76-2 2-butoxyethanol

PEL (USA)	Long-term value: 240 mg/m ³ , 50 ppm Skin
-----------	---

REL (USA)	Long-term value: 24 mg/m ³ , 5 ppm Skin
-----------	---

TLV (USA)	Long-term value: 97 mg/m ³ , 20 ppm BEI
-----------	---

EL (Canada)	Long-term value: 20 ppm
-------------	-------------------------

EV (Canada)	Long-term value: 20 ppm Skin
-------------	---------------------------------

LMPE (Mexico)	Long-term value: 20 ppm A3, IBE
---------------	------------------------------------

95-63-6 1,2,4-trimethylbenzene

REL (USA)	Long-term value: 125 mg/m ³ , 25 ppm
-----------	---

TLV (USA)	Long-term value: 123 mg/m ³ , 25 ppm
-----------	---

108-67-8 mesitylene

REL (USA)	Long-term value: 125 mg/m ³ , 25 ppm
-----------	---

TLV (USA)	Long-term value: 123 mg/m ³ , 25 ppm
-----------	---

1330-20-7 Xylene

PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
-----------	--

REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
-----------	---

(Cont'd. on page 6)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 5)

TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm
EV (Canada)	Short-term value: 650 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
LMPE (Mexico)	Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE

98-82-8 Cumene

PEL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
TLV (USA)	Long-term value: (246) NIC-5 mg/m ³ , (50) NIC-1 ppm NIC-A3
EL (Canada)	Short-term value: 75 ppm Long-term value: 25 ppm IARC 2B
EV (Canada)	Long-term value: 245 mg/m ³ , 50 ppm Skin
LMPE (Mexico)	Long-term value: 50 ppm

91-20-3 Naphthalene

PEL (USA)	Long-term value: 50 mg/m ³ , 10 ppm
REL (USA)	Short-term value: 75 mg/m ³ , 15 ppm Long-term value: 50 mg/m ³ , 10 ppm
TLV (USA)	Long-term value: 52 mg/m ³ , 10 ppm Skin; BEI
EL (Canada)	Long-term value: 10 ppm Skin; IARC 2B
EV (Canada)	Short-term value: 78 mg/m ³ , 15 ppm Long-term value: 52 mg/m ³ , 10 ppm
LMPE (Mexico)	Short-term value: 15 ppm Long-term value: 10 ppm A4, PIEL

· Ingredients with biological limit values:**111-76-2 2-butoxyethanol**

BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----------	--

1330-20-7 Xylene

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift
-----------	---

(Cont'd. on page 7)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 6)

Parameter: Methylhippuric acids

- **Exposure controls**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Engineering controls:** Provide adequate ventilation.
- **Breathing equipment:** Suitable respiratory protective device recommended.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product.

- **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment**
No relevant information available.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **Appearance:**

Form: Liquid
Color: Clear to light yellow.

- **Odor:** Mineral-oil-like
- **Odor threshold:** Not determined.

- **pH-value:** Not determined.
- **Melting point/Melting range:** Not determined.
- **Boiling point/Boiling range:** Not determined.

- **Flash point:** 57 °C (134.6 °F)

- **Auto-ignition temperature:** Not determined.

- **Decomposition temperature:** Not determined.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits**

Lower: Not determined.

(Cont'd. on page 8)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 7)

Upper:	Not determined.
· Oxidizing properties:	Non-oxidizing.
· Vapor pressure:	Not determined.
· Density:	
Relative density:	Not determined.
Vapor density:	Not determined.
Evaporation rate:	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Flammable liquid and vapor.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
- **Conditions to avoid** Keep ignition sources away - Do not smoke.
- **Incompatible materials** Oxidizing agents.
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Causes eye irritation.
- **Sensitization:** Based on available data, the classification criteria are not met.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer):**

98-82-8	Cumene	2B
91-20-3	Naphthalene	2B

(Cont'd. on page 9)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 8)

· **NTP (National Toxicology Program):**

98-82-8	Cumene	R
91-20-3	Naphthalene	R

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Suspected of causing cancer. Route of exposure: Inhalation.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity**

Harmful to aquatic life with long lasting effects.

64742-94-5 Solvent naphtha (petroleum), heavy arom.

LC50 | 3.6 mg/l (Oncorhynchus mykiss)

91-20-3 Naphthalene

LC50 | 1-10 mg/l (daphnia)

- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· **Uncleaned packagings**

- **Recommendation:** Disposal must be made according to official regulations.

(Cont'd. on page 10)

Safety Data Sheet




according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 9)

14 Transport information

· UN-Number	
· DOT	NA1993
· ADR/RID/ADN, IMDG, IATA	UN1268
· UN proper shipping name	
· DOT	Combustible liquid, n.o.s. (Distillates (petroleum), hydro- treated light, 2-butoxyethanol)
· ADR/RID/ADN, IMDG	PETROLEUM DISTILLATES, N.O.S.
· IATA	Petroleum distillates. n.o.s.
· Transport hazard class(es)	
· DOT	
	
· Class	3
· Label	3
· ADR/RID/ADN	
	
· Class	3 (F1)
· Label	3
· IMDG, IATA	
	
· Class	3
· Label	3
· Packing group	
· DOT, ADR/RID/ADN, IMDG, IATA	III
· Environmental hazards	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	30
· EMS Number:	F-E,S-E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	

(Cont'd. on page 11)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 10)

· DOT

Classified as combustible under US DOT regulations. Labeling is only required for single packages 119 US gal / 450 L.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- United States (USA)
- SARA

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

111-76-2 | 2-butoxyethanol

95-63-6 | 1,2,4-trimethylbenzene

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

· Proposition 65 (California)

· Chemicals known to cause cancer:

98-82-8 | Cumene

91-20-3 | Naphthalene

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

111-76-2 | 2-butoxyethanol

NL

95-63-6 | 1,2,4-trimethylbenzene

II

108-67-8 | mesitylene

II

1330-20-7 | Xylene

I

98-82-8 | Cumene

D, CBD

91-20-3 | Naphthalene

C, CBD

· IARC (International Agency for Research on Cancer):

98-82-8 | Cumene

2B

91-20-3 | Naphthalene

2B

(Cont'd. on page 12)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 11)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapor.
 H227 Combustible liquid.
 H228 Flammable solid.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H320 Causes eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer. Route of exposure: Inhalation.

- **Date of preparation / last revision** August 19, 2019 / -

- **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 OSHA: Occupational Safety & Health Administration
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flam. Liq. 3: Flammable liquids – Category 3
 Flam. Liq. 4: Flammable liquids – Category 4
 Flam. Sol. 2: Flammable solids – Category 2
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1

- **Sources**

Website, European Chemicals Agency (echa.europa.eu)
 Website, US EPA Substance Registry Services (ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do)
 Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
 Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.
 Safety Data Sheets, Individual Manufacturers

SDS Prepared by:
 ChemTel Inc.
 1305 North Florida Avenue

(Cont'd. on page 13)

Safety Data Sheet
according to OSHA HCS (29CFR 1910.1200)

Revision: August 19, 2019

Trade name: Rislone® Diesel Additive - Right Side

(Cont'd. of page 12)

Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com