



ISO 9001 CERTIFIED COMPANY

# LIQUID ALUMINUM STOP LEAK

Part #: 21184

375 mL

## Cooling system radiator stop leak

Rislone® Liquid Aluminum™ Cooling System / Radiator & Heater Core Stop Leak is the best radiator stop leak money can buy. Scientifically formulated to permanently seal coolant leaks that are the cause of most overheating problems. Liquid Aluminum is part of the next generation stop leak line which not only seal leaks, but also conditions the system. Contains Xtreme Cool™ which stops overheating and reduces water temperature. Safely and easily seal leaks in plastic, aluminum and metal (copper / steel) radiators, heater cores, gaskets and freeze plugs. It will not harm the cooling system, no draining is required. Use with ALL types of traditional or extended life coolant including yellow, orange, pink, red, blue, purple and green silicate based & non-silicate based (OAT/HOAT) 50-50 mix antifreeze, and/or water. For most vehicles leaks seal instantly.

### Safe to Use and Seals Instantly

### Works with All Types of Antifreeze Coolant or Water

### Use in Cars, Trucks, Vans, SUV's and RV's

**STOP LEAK** - Liquid Aluminum safely seals leaks in plastic, aluminum and metal radiators, heater cores, gaskets and freeze plugs. One of the few products to meet ASTM D6107 requirements for Stop Leak Additives used in Engine Coolants.

**XTREME COOL™** - Xtreme Cool reduces the surface tension of coolant increasing the wetting ability. This improves heat transfer reducing coolant temperature helping to prevent overheating and leaks.

**DANGER:** Opening the cooling system while the engine is hot or running may cause severe burns.

**NOTE:** Cooling systems that are dirty or partially clogged should be flushed before usage.  
**Protect from freezing.**

### DOSAGE:

One bottle treats cooling systems from 6 liters to 11 liters. For larger systems use one bottle for every 10 liters of cooling system capacity. Small engines or other small systems use approximately 40 mL per liter of fluid capacity.





# LIQUID ALUMINUM STOP LEAK

ISO 9001 CERTIFIED COMPANY

## INSTRUCTIONS:

- 1) Allow engine to cool. Make sure engine is cool enough so radiator cap can be safely removed.
- 2) Shake well. Pour Liquid Aluminum directly into radiator. One bottle treats systems up to 11 liters.

**TIP:** If direct access to radiator is not available, install in overflow tank.

- 3) Fill radiator and overflow tank to proper level and reinstall radiator cap.
- 4) Drive/idle engine for 15 to 20 minutes. If leak continues, second application may be required or mechanical attention is needed. For severe leaks, like a blown head gasket, it is recommended to use Rislone Head Gasket Fix.
- 5) Leave Rislone Liquid Aluminum in cooling system for continued protection.

## ASTM D6107 LABORATORY TEST

Standard Specification for Stop-Leak Additive for Engine Coolants Used in Light Duty Service

### Part 1: ASTM D1881 TEST

Standard Test Method for Foaming Tendencies of Engine Coolants

RUN # 1	1	2	3	Average
Foam Volume (mls)	75	80	75	75
Break Time (sec)	1.8	1.8	1.8	1.8

RUN # 2	1	2	3	Average
Foam Volume (mls)	85	85	80	85
Break Time (sec)	1.8	1.8	1.8	1.8

### Part 2: ASTM D3147 TEST

Standard Test Method for Testing Stop-Leak Additives for Engine Coolants.

This test method covers screening procedures for the preliminary evaluation of leak-stopping materials intended for use in engine cooling systems.

Sample Run	Gum		Particles		Screen	Final Round	Final Slot	Fluid Lost
	Before	After	Before	After	mm	mm	mm	ml
1	No	No	No	No	0.76	0.64	0.25	540
2	Yes	No	No	No	0.76	0.64	0.25	600
<b>Average</b>	Yes	No	No	No	0.76	0.64	0.25	570

The results of this test show that a 0.64 mm round hole and a 0.25 mm wide slot can be successfully sealed with this product with a minimal fluid loss.