

# **PRODUCT DATA SHEET**



Rislone® Hy-per Cool™ Xtreme Clean™ Radiator Cleaner will help your cooling system by removing deposits that build up over time causing overheating. Heavy duty formulation is specially designed to clean solder bloom, oily residue, rust and scale. Harmless to all parts of the cooling system, including copper and aluminum. Non-acid formula is safe to use on all cooling system materials.

- Heavy Duty Xtreme Clean<sup>™</sup> formula cleans entire cooling system.
- Use every time changing coolant for light flushing or heavy duty cleaning.

### Caution:

Never remove radiator cap if engine is hot.

## Dosage:

One bottle treats up to 15 liter systems.

#### **Directions:**

- 1. Allow the engine to cool. Drain the system. Close the drain.
- 2. Pour the entire contents of the bottle and refill the system with water. For large cooling systems, use one bottle of Radiator Cleaner for every 12 liters. Replace the cap.
- 3. Start the engine. After reaching the normal operating temperature keep it running for 10 minutes with the heating on at maximum.
- 4. Allow the engine to cool. Drain the cooling system and flush the overflow tank until the water runs completely clear.
- 5. Close the drain. Refill the cooling system and the overflow tank with the manufactures recommended antifreeze coolant / water mixture.

### **Disposal**

Observe local laws and regulations. Where permitted, dispose of in a sanitary sewer system. Never pour on the ground or in a storm sewer system.



RISLONE

10386 North Holly Road
Holly, MI 48442 USA

USA

www.rislone.com

RADIATOR CLEANER