according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 27 January 2022

1 Identification Product identifier · Trade name: Rislone Gas Fuel System Cleaner- Left Side · Product size: 34700 · Recommended use and restriction on use · Recommended use: Treatment for gasoline. · Restrictions on use: No relevant information available. · Details of the supplier of the Safety Data Sheet · Manufacturer/Supplier: Rislone P.O. Box 187 RISLONE Holly, MI 48442 USA Phone: (810) 603-1321 · Emergency telephone number: ChemTel Inc. 255-3924 (North America) (800) (801) 1 (813)248-0585 (International) 2 Hazard(s) identification Classification of the substance or mixture Flam. Lig. 3 H226 Flammable liquid and vapor. Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox, 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2A H319 Causes serious eye irritation. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms: GHS02 GHS07 Signal word: Warning · Hazard statements: Flammable liquid and vapor. H226 H302+H312+H332 Harmful if swallowed, in contact with skin or if inhaled. Causes skin irritation. H315 Causes serious eye irritation. H319 · Precautionary statements: P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P233 Keep container tightly closed. Ground/bond container and receiving equipment. P240 Use explosion-proof electrical/ventilating/lighting/equipment. P241 P242 Use only non-sparking tools. (Cont'd. on page 2)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 27 January 2022

	(Cont'd. of page
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312	If swallowed: Call a poison center/doctor if you feel unwell.
P330	Rinse mouth.
P303+P361+P3	53 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin w water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses present and easy to do. Continue rinsing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/internation regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:	
111-76-2 2-butoxyethanol	>80%
Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
Flam. Liq. 4, H227	
67-63-0 Propan-2-ol	<10%
Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336	
🚸 Eye Irrit. 2A, H319; STOT SE 3, H336	
Additional information:	
For the wording of the listed Hazard Statements, refer to section 16.	
For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade se	cret.

4 First-aid measures

· Description of first aid measures

· After inhalation:

Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing.

· After skin contact:

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

After eye contact:

(Cont'd. on page 3)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 27 January 2022

Trade name: Rislone Gas Fuel System Cleaner - Left Side

(Cont'd. of page 2)

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· Most important symptoms and effects, both acute and delayed:

Coughing Dizziness

Breathing difficulty

Causes serious eye irritation.

Causes skin irritation.

- · Danger: Harmful if swallowed, in contact with skin or if inhaled.
- Indication of any immediate medical attention and special treatment needed:

No relevant information available.

5 Fire-fighting measures

· Extinguishing media

 Suitable extinguishing agents: Foam Alcohol resistant foam Gaseous extinguishing agents Carbon dioxide Fire-extinguishing powder

Water

· For safety reasons unsuitable extinguishing agents: No relevant information available.

· Special hazards arising from the substance or mixture

In case of fire, the following can be released: Carbon monoxide, carbon dioxide.

· Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device. Wear fully protective suit.

· Additional information:

Use large quantities of foam as it is partially destroyed by the product. Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures
 Use respiratory protective device against the effects of fumes/dust/aerosol.
 Keep away from ignition sources.
 Wear protective equipment. Keep unprotected persons away.
 Ensure adequate ventilation.
 Environmental precautions
 Do not allow to enter sewers/ surface or ground water.
 Prevent from spreading (e.g. by damming-in or oil barriers).

(Cont'd. on page 4)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 27 January 2022

Trade name: Rislone Gas Fuel System Cleaner - Left Side

(Cont'd. of page 3)

 Inform respective authorities in case of seepage into water course or sewage system.
 Methods and material for containment and cleaning up Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders). Remove from the water surface (e.g. skim or suck off). Send for recovery or disposal in suitable receptacles.
 Reference to other sections See Section 7 for information on safe handling

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling

Precautions for safe handling: Keep out of reach of children.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Avoid breathing mist, vapors, or spray.
Avoid contact with the eyes and skin.

• Information about protection against explosions and fires: Keep respiratory protective device available. Keep ignition sources away - Do not smoke.

- · Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: Avoid storage near extreme heat, ignition sources or open flame. Store in cool, dry conditions in well sealed receptacles.
- **Information about storage in one common storage facility:** Store away from foodstuffs. Store away from oxidizing agents.
- Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

Components with limit values that require monitoring at the workplace:
111-76-2 2-butoxyethanol

111-70-2 2-Duit		
PEL (USA)	Long-term value: 240 mg/m³, 50 ppm Skin	
REL (USA)	Long-term value: 24 mg/m³, 5 ppm Skin	
TLV (USA)	Long-term value: 97 mg/m³, 20 ppm BEI	
EL (Canada)	Long-term value: 20 ppm	
EV (Canada)	Long-term value: 20 ppm Skin	
LMPE (Mexico)	Long-term value: 20 ppm	
	(Cont'd. on page 5)	

Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 27 January 2022

Trade name: Rislone Gas Fuel System Cleaner - Left Side

	(Cont'd. of page 4)
	A3, IBE
67-63-0 Propar	n-2-ol
PEL (USA)	Long-term value: 980 mg/m ³ , 400 ppm
REL (USA)	Short-term value: 1225 mg/m³, 500 ppm
	Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm
	Long-term value: 492 mg/m ³ , 200 ppm BEI
EL (Canada)	Short-term value: 400 ppm
	Long-term value: 200 ppm
EV (Canada)	Short-term value: 400 ppm
	Long-term value: 200 ppm
LMPE (Mexico)	Short-term value: 400 ppm
	Long-term value: 200 ppm A4, IBE
-	h biological limit values:
111-76-2 2-but	
	mg/g creatinine
	lium: urine
	e: end of shift ameter: Butoxyacetic acid with hydrolysis
67-63-0 Propar	
BEI (USA) 40 r	
	lium: urine
	e: end of shift at end of workweek
Para	ameter: Acetone (background, nonspecific)
· Exposure cor	ntrols
	tive and hygienic measures:
	n foodstuffs, beverages and feed.
	nove all soiled and contaminated clothing. fore breaks and at the end of work.
	ases / fumes / aerosols.
	ith the eyes and skin.
	ontrols: No relevant information available.
 Breathing equi 	
	spiratory protective device in case of insufficient ventilation.
	spiratory protective device when aerosol or mist is formed. atory protection may be advisable.
· Protection of h	
μ.	
Protect	ive gloves
	rial has to be impermeable and resistant to the product/ the substance/ the preparation.
· Eye protection	: (Cont'd. on page 6)

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 27 January 2022

Trade name: Rislone Gas Fuel System Cleaner - Left Side

(Cont'd. of page 5)

Safety glasses

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment No relevant information available.
- · Risk management measures No relevant information available.

9 Physical and chemical properties		
· Information on basic physical an	d chemical properties	
· Appearance:		
Form:	Liquid	
Color:	Light yellow	
· Odor:	Petroleum-like	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Melting point/Melting range:	Not determined.	
· Boiling point/Boiling range:	Not determined.	
· Flash point:	40.2 °C (104.4 °F)	
· Flammability (solid, gaseous):	Not applicable.	
· Auto-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.	
· Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
 Oxidizing properties: 	Non-oxidizing.	
· Vapor pressure:	Not determined.	
· Density:		
Relative density at 25 °C (77 °F):	0.78-0.80	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
 Solubility in / Miscibility with 		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
 Other information 	No relevant information available.	

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 27 January 2022

Trade name: Rislone Gas Fuel System Cleaner - Left Side

(Cont'd. of page 6)

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability:
- Thermal decomposition / conditions to be avoided: Keep away from heat and direct sunlight. Avoid open flame, ignition sources, contact with incompatible substances.
 Possibility of hazardous reactions Flammable liquid and vapor. Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized. Reacts with oxidizing agents.

- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- · Hazardous decomposition products Carbon monoxide and carbon dioxide

Acute to		oxicological effects	
	if swallowe	d.	
	in contact v	vith skin.	
	if inhaled.		
		at are relevant for classification:	
		y Estimate)	
Oral	LD50	1591 mg/kg (rat)	
Dermal	LD50	1076-2151 mg/kg (rat)	
Inhalativ	e LC50/4h	11.5 mg/l	
111-76-2	2 2-butoxye	ethanol	
Oral	LD50	1480 mg/kg (rat)	
Dermal	LD50	1001-2000 mg/kg (rat) (Estimated)	
Inhalativ	e LC50/4h	450 ppm (rat)	
· Primary	irritant eff	ect:	
· Primary · On the s	irritant effeskin: Irritant	ect: t to skin and mucous membranes.	
 Primary On the s On the e 	irritant eff skin: Irritant eye: Causes	ect: t to skin and mucous membranes. s eye irritation.	
 Primary On the s On the e Sensitiz 	irritant eff skin: Irritan eye: Cause ation: No s	ect: t to skin and mucous membranes. s eye irritation. sensitizing effects known.	
 Primary On the s On the e Sensitiz IARC (In 	irritant eff skin: Irritant eye: Causes ation: No s aternationa	ect: t to skin and mucous membranes. s eye irritation. sensitizing effects known. I Agency for Research on Cancer):	
 Primary On the s On the e Sensitiz IARC (In Present 	irritant eff skin: Irritani eye: Cause: ation: No s iternationa in trace qua	ect: t to skin and mucous membranes. s eye irritation. sensitizing effects known. I Agency for Research on Cancer): antities.	21
 Primary On the s On the s Sensitiz IARC (In Present 91-20-3 	irritant eff skin: Irritan eye: Causes ation: No s aternationa in trace qua 3 Naphthale	ect: t to skin and mucous membranes. s eye irritation. sensitizing effects known. I Agency for Research on Cancer): antities. ene	
 Primary On the s On the e Sensitiz IARC (In Present 91-20-3 100-41-4 	irritant eff skin: Irritant eye: Causes ation: No s nternationa in trace qua Naphthale Ethylbenz	ect: t to skin and mucous membranes. s eye irritation. sensitizing effects known. I Agency for Research on Cancer): antities. ene	2E 2E
 Primary On the s On the e Sensitiz IARC (In Present 91-20-3 100-41-4 NTP (Na 	irritant eff skin: Irritant eye: Causes ation: No s nternationa in trace qua Naphthale Ethylbenz	ect: t to skin and mucous membranes. s eye irritation. sensitizing effects known. I Agency for Research on Cancer): antities. ene tene tene icology Program):	

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 27 January 2022

Trade name: Rislone Gas Fuel System Cleaner - Left Side

(Cont'd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

· Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact. Skin contact.

Corm coll m

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Based on available data, the classification criteria are not met.
- · STOT-single exposure: Based on available data, the classification criteria are not met.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: Does not accumulate in organisms
- Mobility in soil: No relevant information available.
- · Additional ecological information
- · General notes:

Avoid transfer into the environment.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· Other adverse effects No relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Contact waste processors for recycling information.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· Uncleaned packagings

· Recommendation: Disposal must be made according to official regulations.

14 Transport information		
· UN-Number		
· DOT	NA1993	
· ADR/RID/ADN, IMDG, IATA	UN1993	
		(Cont'd. on page 9)


Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 27 January 2022

	le name: Rislone Gas Fuel System Cleaner - Left Side	
	(Cont'd. of pag	
· UN proper shipping name · DOT · ADR/RID/ADN, IMDG, IATA	Combustible liquid, n.o.s. (Isopropanol, butoxyethanol) FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL, butoxyethanol)	
· Transport hazard class(es)		
DOT		
Class	3	
	3	
ADR/RID/ADN		
Class	3 (F1)	
Label IMDG, IATA	3	
Class	3	
Label	3	
· Packing group · DOT, ADR/RID/ADN, IMDG, IATA	III	
Environmental hazards Marine pollutant:	No	
Special precautions for user Danger code (Kemler): EMS Number:	Warning: Flammable liquids 30 F-E, <u>S-E</u>	
 Transport in bulk according to Annex I MARPOL73/78 and the IBC Code 	Il of Not applicable.	
· Transport/Additional information:		
DOT	Classified as combustible under US DOT regulation Labeling is only required for single packages 119 gal / 450 L.	
· ADR/RID/ADN	(Cont'd. on	

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 27 January 2022



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 27 January 2022

Trade name: Rislone Gas Fuel System Cleaner - Left Side

(Cont'd. of page 10)

NL

2B

2B

107-21-1 Ethylene glycol

· EPA (Environmental Protection Agency):

111-76-2 2-butoxyethanol

· IARC (International Agency for Research on Cancer):

91-20-3 Naphthalene

100-41-4 Ethylbenzene

· Canadian Domestic Substances List (DSL):

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent OSHA: Occupational Safety & Health Administration Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Flam. Liq. 4: Flammable liquids – Category 4 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com