

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations


Revision: 05.02.2021

1 Identification

- **Product identifier**
- **Trade name: Rislone Diesel Fuel System Treatment - Left Side**
- **Product code:** 34740
- **Recommended use and restriction on use**
- **Recommended use:** Treatment for diesel fuel.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Rislone
P.O. Box 187
Holly, MI 48442 USA
Phone: (810) 603-1321
- **Emergency telephone number:**
ChemTel Inc.
(800) 255-3924 (North America)
(801) 1 (813)248-0585 (International)



2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 4 H227 Combustible liquid.
Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms:**

GHS08
- **Signal word:** Danger
- **Hazard statements:**
H227 Combustible liquid.
H351 Suspected of causing cancer. Route of exposure: Inhalation.
H304 May be fatal if swallowed and enters airways.
- **Precautionary statements:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from flames and hot surfaces. – No smoking.
P280 Wear protective gloves and eye protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.
P331 Do NOT induce vomiting.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
P403+P235 Store in a well-ventilated place. Keep cool.

(Cont'd. on page 2)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 05.02.2021

Trade name: Rislone Diesel Fuel System Treatment - Left Side

(Cont'd. of page 1)

P405 Store locked up.


















P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Components:**

64742-47-8	Distillates (petroleum), hydro- treated light  Asp. Tox. 1, H304  Flam. Liq. 4, H227	60-80%
27247-96-7	2-Ethylhexyl Nitrate  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332  Flam. Liq. 4, H227	<10%
64742-94-5	Solvent naphtha (petroleum), heavy arom.  Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336  Flam. Liq. 4, H227	<10%
64742-95-6	Solvent naphtha (petroleum), light arom.  Flam. Liq. 3, H226  Asp. Tox. 1, H304	<5%
95-63-6	1,2,4-trimethylbenzene  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	<3%
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic  Asp. Tox. 1, H304	<3%
64742-55-8	Distillates (petroleum), hydrotreated light paraffinic  Asp. Tox. 1, H304	<3%
91-20-3	Naphthalene  Flam. Sol. 2, H228  Carc. 2, H351  Acute Tox. 4, H302	<3%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.
 For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately remove any clothing soiled by the product.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation is experienced, consult a doctor.

(Cont'd. on page 3)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 05.02.2021

Trade name: Rislone Diesel Fuel System Treatment - Left Side

(Cont'd. of page 2)

- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; immediately call for medical help.
A person vomiting while lying on their back should be turned onto their side.
- **Most important symptoms and effects, both acute and delayed:**
Breathing difficulty
Coughing
- **Danger:**
Danger of impaired breathing.
May be fatal if swallowed and enters airways.
Suspected of causing cancer. Route of exposure: Inhalation.
- **Indication of any immediate medical attention and special treatment needed:**
If swallowed or in case of vomiting, danger of entering the lungs.
Medical supervision for at least 48 hours.
If necessary oxygen respiration treatment.
Later observation for pneumonia and pulmonary edema.
If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Foam
Carbon dioxide
Fire-extinguishing powder
Gaseous extinguishing agents
Water fog / haze
- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture** No relevant information available.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information:** Eliminate all ignition sources if safe to do so.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Particular danger of slipping on leaked/spilled product.
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation.
Keep away from ignition sources.
Protect from heat.
For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.
- **Environmental precautions**
Do not allow to enter sewers/ surface or ground water.

(Cont'd. on page 4)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 05.02.2021

Trade name: Rislone Diesel Fuel System Treatment - Left Side

(Cont'd. of page 3)

Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up**

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
Send for recovery or disposal in suitable receptacles.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Handling**

- **Precautions for safe handling:**

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

- **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Flammable liquid and vapor.

- **Conditions for safe storage, including any incompatibilities**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Avoid storage near extreme heat, ignition sources or open flame.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

- **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

64742-47-8 Distillates (petroleum), hydro- treated light

EL (Canada)	Long-term value: 200 mg/m ³ Skin
-------------	--

95-63-6 1,2,4-trimethylbenzene

REL (USA)	Long-term value: 125 mg/m ³ , 25 ppm
-----------	---

TLV (USA)	Long-term value: 123 mg/m ³ , 25 ppm
-----------	---

91-20-3 Naphthalene

PEL (USA)	Long-term value: 50 mg/m ³ , 10 ppm
-----------	--

REL (USA)	Short-term value: 75 mg/m ³ , 15 ppm
-----------	---

	Long-term value: 50 mg/m ³ , 10 ppm
--	--

TLV (USA)	Long-term value: 52 mg/m ³ , 10 ppm
-----------	--

Skin; BEI

EL (Canada)	Long-term value: 10 ppm
-------------	-------------------------

Skin; IARC 2B

(Cont'd. on page 5)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 05.02.2021

Trade name: Rislone Diesel Fuel System Treatment - Left Side

(Cont'd. of page 4)

EV (Canada)	Short-term value: 78 mg/m ³ , 15 ppm Long-term value: 52 mg/m ³ , 10 ppm
LMPE (Mexico)	Short-term value: 15 ppm Long-term value: 10 ppm A4, PIEL

- **Exposure controls**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Engineering controls:** Provide adequate ventilation.
- **Breathing equipment:** Suitable respiratory protective device recommended.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product.

- **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment**
No relevant information available.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **Appearance:**

Form: Liquid
Color: Clear to light yellow.

- **Odor:** Mineral-oil-like
- **Odor threshold:** Not determined.

- **pH-value:** Not determined.
- **Melting point/Melting range:** Not determined.
- **Boiling point/Boiling range:** Not determined.

• **Flash point:** 64 °C (147.2 °F)

• **Flammability (solid, gaseous):** Flammable.

• **Auto-ignition temperature:** Not determined.

• **Decomposition temperature:** Not determined.

(Cont'd. on page 6)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 05.02.2021

Trade name: Rislone Diesel Fuel System Treatment - Left Side

(Cont'd. of page 5)

· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
· Oxidizing properties:	Non-oxidizing.
· Vapor pressure:	Not determined.
· Density:	
Relative density:	Not determined.
Vapor density:	Not determined.
Evaporation rate:	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Flammable liquid and vapor.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
- **Conditions to avoid** Keep ignition sources away - Do not smoke.
- **Incompatible materials** Oxidizing agents.
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** Based on available data, the classification criteria are not met.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** Based on available data, the classification criteria are not met.

(Cont'd. on page 7)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 05.02.2021

Trade name: Rislone Diesel Fuel System Treatment - Left Side

(Cont'd. of page 6)

· **IARC (International Agency for Research on Cancer):**

91-20-3	Naphthalene	2B
---------	-------------	----

· **NTP (National Toxicology Program):**

91-20-3	Naphthalene	R
---------	-------------	---

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Suspected of causing cancer. Route of exposure: Inhalation.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity**

Toxic to aquatic life with long lasting effects.

64742-94-5 Solvent naphtha (petroleum), heavy arom.

LC50	3.6 mg/l (Oncorhynchus mykiss)
------	--------------------------------

91-20-3 Naphthalene

LC50	1-10 mg/l (daphnia)
------	---------------------

· **Persistence and degradability** No relevant information available.

· **Bioaccumulative potential:** No relevant information available.

· **Mobility in soil:** No relevant information available.

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **Additional ecological information**

· **General notes:**

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

· **Other adverse effects** No relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and

(Cont'd. on page 8)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 05.02.2021






Trade name: Rislone Diesel Fuel System Treatment - Left Side

(Cont'd. of page 7)

disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT	NA1993
· ADR/RID/ADN, IMDG, IATA	UN3082
· UN proper shipping name	
· DOT	Combustible liquid, n.o.s. (stoddard solvent, propan-2-ol)
· ADR/RID/ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Ethylhexyl Nitrate, 1,2,4-trimethylbenzene)
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2,4-trimethylbenzene, 2-Ethylhexyl Nitrate)
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2,4-trimethylbenzene, 2-Ethylhexyl Nitrate)
· Transport hazard class(es)	
· DOT	
	
· Class	3
· Label	3
· ADR/RID/ADN	
	
	
· Class	9 (M6)
· Label	9
· IMDG, IATA	
	
	
· Class	9
· Label	9
· Packing group	
· DOT, ADR/RID/ADN, IMDG, IATA	III

(Cont'd. on page 9)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 05.02.2021

Trade name: Rislone Diesel Fuel System Treatment - Left Side

(Cont'd. of page 8)

<ul style="list-style-type: none"> · Environmental hazards · Marine pollutant: 	Symbol (fish and tree)
<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: 	Warning: Miscellaneous dangerous substances and articles 90 F-E, <u>S-E</u>
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: 	Not regulated when carried in single or combination packaging containing a net quantity of 5 L or less for liquids or 5 kg or less for solids per the following: DOT: 171.4(c)(2) ADR: SP 375 IMDG: 2.10.2.7 IATA: special provision A197
<ul style="list-style-type: none"> · DOT 	Classified as combustible under US DOT regulations. Labeling is only required for single packages 119 US gal / 450 L.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

95-63-6 | 1,2,4-trimethylbenzene

91-20-3 | Naphthalene

· TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

· Proposition 65 (California)

· Chemicals known to cause cancer:

91-20-3 | Naphthalene

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

(Cont'd. on page 10)

Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: 05.02.2021

Trade name: Rislone Diesel Fuel System Treatment - Left Side

(Cont'd. of page 9)

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

95-63-6	1,2,4-trimethylbenzene	II
91-20-3	Naphthalene	C, CBD

· **IARC (International Agency for Research on Cancer):**

91-20-3	Naphthalene	2B
---------	-------------	----

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 OSHA: Occupational Safety & Health Administration
 Flam. Liq. 3: Flammable liquids – Category 3
 Flam. Liq. 4: Flammable liquids – Category 4
 Flam. Sol. 2: Flammable solids – Category 2
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1

· **Sources**

Website, European Chemicals Agency (echa.europa.eu)
 Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)
 Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
 Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.
 Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com