

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

1 Identification of the substance/mixture and of the company/undertaking

• Product identifier

- **Trade name:** Rislone® Diesel Fuel System Treatment - Right Side
- **Product code:** 44740

• Recommended use and restriction on use

- **Recommended use:** Treatment for diesel fuel.
- **Restrictions on use:** No further relevant information available.

• Details of the supplier of the Safety Data Sheet

• Manufacturer/Supplier:

Rislone
P.O. Box 187
Holly, MI 48442
USA
Phone: (810) 603-1321



• Distributor:

Smits Group Pty Ltd
59 Greenmount Dr, East Tamaki, Auckland, New Zealand NZ
Telephone: +09 274 6871
AUS Telephone 1800883 888

• Emergency telephone number:

ChemTel Inc.
(800) 255-3924 (North America)
(801) 1 (813)248-0585 (International)
(802) 1-300-954-583 (Australia)

Emergencies within Australia - 131126 (NSW Poison Control Centre)

Emergencies within New Zealand - 0800 764 766 (National Poison Control Centre)

2 Hazards identification

• Classification (Australia, New Zealand)

Australia NOHSC – Hazardous Substance (Classified according to Worksafe Australia NOHSC 2018 National Code of Practice)

New Zealand HSNO - Hazardous (Classified according to the Minimum Degrees of Hazard Regulations 2001)

• Classification of the substance or mixture

Flam. Liq. 3 H226 Flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.
Aquatic Acute 3 H402 Harmful to aquatic life.
Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

• Hazard statements (New Zealand HSNO Classification)

HSNO 3.1C Flam. Liq. 3 H226 Flammable liquid and vapour.
HSNO 9.1C Aquatic Acute 3 H402 Harmful to aquatic life.
HSNO 6.3A Skin Irr. 2 H315 Causes skin irritation.
HSNO 6.4A Eye Irrit. 2A H319 Causes serious eye irritation.
HSNO 9.1C Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.
HSNO 6.1E Asp. Tox 1 H304 May be fatal if swallowed and enters airways

(Cont'd. on page 2)

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 1)

- **Label elements**
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger
- **Hazard statements**
 - H226 Flammable liquid and vapour.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H304 May be fatal if swallowed and enters airways.
 - H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P264 Wash thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P331 Do NOT induce vomiting.
- P321 Specific treatment (see on this label).
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use to extinguish: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards** There are no other hazards not otherwise classified that have been identified.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterisation: Mixtures**
- **Components:**
































(Cont'd. on page 3)

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 2)		
CAS: 64742-47-8 EINECS: 265-149-8	Distillates (petroleum), hydro- treated light  Asp. Tox. 1, H304  Flam. Liq. 4, H227; Acute Tox. 5, H313	>60%
CAS: 111-76-2 EINECS: 203-905-0	2-butoxyethanol  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319  Flam. Liq. 4, H227	10-30%
CAS: 64742-95-6 EC number: 918-668-5	Hydrocarbons, C9, aromatics  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  STOT SE 3, H335-H336 Acute Tox. 5, H313; Aquatic Acute 2, H401	<10%
CAS: 112-80-1 EINECS: 204-007-1	oleic acid, pure  Skin Corr. 3, H316; Eye Irrit. 2B, H320	<10%
CAS: 64742-94-5 EINECS: 265-198-5	Solvent naphtha (petroleum), heavy arom.  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Skin Irrit. 2, H315; STOT SE 3, H336  Flam. Liq. 4, H227	<2.5%
CAS: 95-63-6 EINECS: 202-436-9	1,2,4-trimethylbenzene  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Acute Tox. 5, H303; Aquatic Acute 2, H401	<2.5%
CAS: 108-67-8 EINECS: 203-604-4	mesitylene  Flam. Liq. 3, H226  Aquatic Chronic 2, H411  STOT SE 3, H335	<2.5%
CAS: 1330-20-7 EINECS: 215-535-7	Xylene  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Acute Tox. 5, H303; Aquatic Acute 3, H402; Aquatic Chronic 3, H412	<2.5%
CAS: 98-82-8 EINECS: 202-704-5	Cumene  Flam. Liq. 3, H226  Asp. Tox. 1, H304  Aquatic Chronic 2, H411  Acute Tox. 4, H302; STOT SE 3, H335 Acute Tox. 5, H333	<0.25%
CAS: 91-20-3 EINECS: 202-049-5	Naphthalene  Flam. Sol. 2, H228  Carc. 2, H351  Aquatic Acute 1, H400; Aquatic Chronic 1, H410  Acute Tox. 4, H302 Acute Tox. 5, H313	<0.25%
(Cont'd. on page 4)		

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 3)

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentages are being withheld as a trade secret.
For the wording of the listed Hazard Statements refer to section 16.

4 First aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air.

Provide oxygen treatment if affected person has difficulty breathing.

If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

· **After skin contact:**

Immediately remove any clothing soiled by the product.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash with soap and water.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while lying on their back should be turned onto their side.

· **Most important symptoms and effects, both acute and delayed**

Breathing difficulty

Dizziness

Coughing

Causes eye irritation.

Causes skin irritation.

· **Hazards:**

Danger of impaired breathing.

May be fatal if swallowed and enters airways.

· **Indication of any immediate medical attention and special treatment needed**

If swallowed or in case of vomiting, danger of entering the lungs.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary oedema.

If medical advice is needed, have product container or label at hand.

5 Firefighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

Foam

Carbon dioxide

Fire-extinguishing powder

Gaseous extinguishing agents

(Cont'd. on page 5)

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 4)

Water haze or fog

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** Flammable liquid and vapour.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information:** Eliminate all ignition sources if safe to do so.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.
Protect from heat.
For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.
- **Environmental precautions**
Do not allow to enter sewers/ surface or ground water.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Prevent formation of aerosols.
Avoid splashes or spray in enclosed areas.
Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Flammable liquid and vapour.
- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidising agents.
- **Specific end use(s)** No further relevant information available.

(Cont'd. on page 6)

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 5)

8 Exposure controls/personal protection

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

WES (Australia)	Short-term value: 242 mg/m ³ , 50 ppm Long-term value: 96.9 mg/m ³ , 20 ppm Sk
PEL (USA)	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL (USA)	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV (USA)	Long-term value: 97 mg/m ³ , 20 ppm BEI
WES (New Zealand)	Long-term value: 121 mg/m ³ , 25 ppm skin

95-63-6 1,2,4-trimethylbenzene

REL (USA)	Long-term value: 125 mg/m ³ , 25 ppm
TLV (USA)	Long-term value: 123 mg/m ³ , 25 ppm

108-67-8 mesitylene

REL (USA)	Long-term value: 125 mg/m ³ , 25 ppm
TLV (USA)	Long-term value: 123 mg/m ³ , 25 ppm

1330-20-7 Xylene

WES (Australia)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 350 mg/m ³ , 80 ppm
PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
WES (New Zealand)	Long-term value: 217 mg/m ³ , 50 ppm

98-82-8 Cumene

WES (Australia)	Short-term value: 375 mg/m ³ , 75 ppm Long-term value: 125 mg/m ³ , 25 ppm Sk
PEL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
TLV (USA)	Long-term value: (246) NIC-5 mg/m ³ , (50) NIC-1 ppm NIC-A3
WES (New Zealand)	Short-term value: 375 mg/m ³ , 75 ppm Long-term value: 125 mg/m ³ , 25 ppm

(Cont'd. on page 7)

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 6)

	skin
91-20-3 Naphthalene	
WES (Australia)	Short-term value: 79 mg/m ³ , 15 ppm Long-term value: 52 mg/m ³ , 10 ppm
PEL (USA)	Long-term value: 50 mg/m ³ , 10 ppm
REL (USA)	Short-term value: 75 mg/m ³ , 15 ppm Long-term value: 50 mg/m ³ , 10 ppm
TLV (USA)	Long-term value: 52 mg/m ³ , 10 ppm Skin; BEI
WES (New Zealand)	Short-term value: 79 mg/m ³ , 15 ppm Long-term value: 52 mg/m ³ , 10 ppm suspected carcinogen

· Ingredients with biological limit values:
111-76-2 2-butoxyethanol

BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----------	--

1330-20-7 Xylene

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

· Exposure controls
· General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
 Keep away from foodstuffs, beverages and feed.
 Wash hands before breaks and at the end of work.
 Do not inhale gases / fumes / aerosols.
 Avoid contact with the eyes and skin.

· **Respiratory protection:** Suitable respiratory protective device recommended.

· Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product.

· Eye protection:


Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· **Body protection:** Protective work clothing

· **Limitation and supervision of exposure into the environment:**

No further relevant information available.

(Cont'd. on page 8)

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 7)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· Appearance

Form: Liquid
 Colour: Clear to light yellow.

· Odour: Mineral-oil-like
 · Odour threshold: Not determined.

· pH-value: Not determined.
 · Melting point/freezing point: Not determined.
 · Initial boiling point and boiling range: Not determined.

· Flash point: 57 °C (134.6 °F)

· Auto/Self-ignition temperature: Not determined.

· Decomposition temperature: Not determined.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits

Lower: Not determined.
 Upper: Not determined.

· Oxidising properties: Non-oxidising.

· Vapour pressure: Not determined.

· Density:

Relative density: Not determined.
 Vapour density: Not determined.
 Evaporation rate: Not determined.

· Solubility in / Miscibility with water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity

Dynamic: Not determined.
 Kinematic: Not determined.

· Other information: No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:**
 No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Flammable liquid and vapour.

Used empty containers may contain product gases which form explosive mixtures with air.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.

(Cont'd. on page 9)

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 8)

- **Conditions to avoid** Keep ignition sources away - Do not smoke.
- **Incompatible materials** Oxidising agents
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:** None.
- **Primary irritant effect**
- **Skin corrosion/irritation:** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation:** Causes eye irritation.
- **Respiratory or skin sensitisation:** Based on available data, the classification criteria are not met.

- **IARC (International Agency for Research on Cancer):**

111-76-2	2-butoxyethanol	3
1330-20-7	Xylene	3
98-82-8	Cumene	2B
91-20-3	Naphthalene	2B

- **Probable routes of exposure:**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:**
Harmful to aquatic life with long lasting effects.

64742-94-5 Solvent naphtha (petroleum), heavy arom.	
LC50	3.6 mg/l (Oncorhynchus mykiss)
91-20-3 Naphthalene	
LC50	1-10 mg/l (daphnia)

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

(Cont'd. on page 10)

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 9)

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

• **Results of PBT and vPvB assessment**

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

• **Other adverse effects** No further relevant information available.

13 Disposal considerations

• **Waste treatment methods**

• **Recommendation**

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

• **Uncleaned packaging:**

• **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

• **UN-Number**

• **DOT**

NA1993

• **ADG, IMDG, IATA**

UN1268

• **UN proper shipping name**

• **DOT**

Combustible liquid, n.o.s. (Distillates (petroleum), hydro- treated light, 2-butoxyethanol)

• **ADG, IMDG**

PETROLEUM DISTILLATES, N.O.S.

• **IATA**

Petroleum distillates. n.o.s.

• **Transport hazard class(es)**

• **DOT**



• **Class**

3

• **Label**

3

• **ADG**



• **Class**

3 (F1)

• **Label**

3

(Cont'd. on page 11)

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 10)

· IMDG, IATA



- Class 3
- Label 3

- Packing group
- DOT, ADG, IMDG, IATA III

- Environmental hazards: Not applicable.

- Special precautions for user Warning: Flammable liquids.
- Danger code (Kemler): 30
- EMS Number: F-E,S-E

- Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

- DOT Classified as combustible under US DOT regulations. Labeling is only required for single packages 119 US gal / 450 L.

- ADG
- Transport category 3
- Tunnel restriction code D/E

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

· IARC (International Agency for Research on Cancer)

98-82-8	Cumene	2B
91-20-3	Naphthalene	2B

· Australia

· Australian Inventory of Chemical Substances

All ingredients are listed.

· Standard for the Uniform Scheduling of Medicines and Poisons

Hydrocarbon Liquids	S6
---------------------	----

· New Zealand HSR002583

· New Zealand Inventory of Chemicals (NZIOC)

All ingredients are listed.

(Cont'd. on page 12)

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 11)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Relevant phrases

H226 Flammable liquid and vapour.
 H227 Combustible liquid.
 H228 Flammable solid.
 H302 Harmful if swallowed.
 H303 May be harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H313 May be harmful in contact with skin.
 H315 Causes skin irritation.
 H316 Causes mild skin irritation.
 H319 Causes serious eye irritation.
 H320 Causes eye irritation.
 H332 Harmful if inhaled.
 H333 May be harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer. Route of exposure: Inhalation.
 H400 Very toxic to aquatic life.
 H401 Toxic to aquatic life.
 H402 Harmful to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

• Abbreviations and acronyms:

ADG: Australian Dangerous Goods Code
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bio-accumulable, Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Flam. Liq. 4: Flammable liquids – Category 4
 Flam. Sol. 2: Flammable solids – Category 2
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 5: Acute toxicity – Category 5
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Skin Corr. 3: Skin corrosion/irritation – Category 3
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

(Cont'd. on page 13)

Safety Data Sheet

according to Australia WHS and NZ HSNO Regulations

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 12)

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com