

Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

1 Identification of the substance or mixture and of the supplier

· Product identifier

- **Trade name:** Rislone® Gas Fuel System Cleaner – Right Side
- **Product code:** 44700
- **Application of the substance / the mixture:** Treatment for gasoline.

· Details of the supplier of the Safety Data Sheet

· **Manufacturer/Supplier:**

Rislone
P.O. Box 187
Holly, MI 48442
USA
Phone: (810) 603-1321



· **Distributor:**

Keizin Automotive
Unit B6, Glen Murray Ind. Park
PO Box 201728, Durban North, 4016
South Africa

· **Emergency telephone number:**

ChemTel Inc.
(800) 255-3924 (North America)
(801) 1 (813)248-0585 (International)

2 Hazards identification

· **Classification of the substance or mixture**

Flam. Liq. 3	H226 Flammable liquid and vapour.
Acute Tox. 5	H313 May be harmful in contact with skin.
Acute Tox. 5	H333 May be harmful if inhaled.
Skin Corr. 3	H316 Causes mild skin irritation.
Asp. Tox. 1	H304 May be fatal if swallowed and enters airways.
Aquatic Acute 3	H402 Harmful to aquatic life.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

· **Label elements**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Distillates (petroleum), hydrotreated light
1,2,4-trimethylbenzene
Solvent naphtha (petroleum), light arom.
1,2,3-trimethylbenzene
Cumene

(Cont'd. on page 2)

Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

Trade name: Rislone® Gas Fuel System Cleaner – Right Side

(Cont'd. from page 1)

• Hazard statements

- H226 Flammable liquid and vapour.
- H313 May be harmful in contact with skin.
- H333 May be harmful if inhaled.
- H316 Causes mild skin irritation.
- H304 May be fatal if swallowed and enters airways.
- H412 Harmful to aquatic life with long lasting effects.

• Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P331 Do NOT induce vomiting.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P370+P378 In case of fire: Use to extinguish: CO2, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

• **Other hazards** There are no other hazards not otherwise classified that have been identified.







• Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

• Chemical characterisation: Mixtures

• Components:

64742-47-8	Distillates (petroleum), hydrotreated light  Flam. Liq. 3, H226  Asp. Tox. 1, H304 Acute Tox. 5, H313	40-50%
64742-95-6	Solvent naphtha (petroleum), light arom.  Flam. Liq. 3, H226  Asp. Tox. 1, H304  STOT SE 3, H336 Acute Tox. 5, H313	<5%
	Polyolefin alkyl phenol alkyl amine  Skin Irrit. 2, H315	<5%
95-63-6	1,2,4-trimethylbenzene	<2.5%

(Cont'd. on page 3)

Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

Trade name: Rislone® Gas Fuel System Cleaner – Right Side

(Cont'd. from page 2)

	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Acute Tox. 5, H303; Aquatic Acute 2, H401	
108-67-8	mesitylene	<1.1%
	Flam. Liq. 3, H226 Aquatic Chronic 2, H411 STOT SE 3, H335	
526-73-8	1,2,3-trimethylbenzene	<1%
	Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 STOT SE 3, H335-H336	
98-82-8	Cumene	<1%
	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H302; STOT SE 3, H335 Acute Tox. 5, H333	

• **Additional information:** For the wording of the listed Hazard Statements refer to section 16.

4 First aid measures

• Description of first aid measures

• After inhalation:

Supply fresh air; consult doctor in case of complaints.
Provide oxygen treatment if affected person has difficulty breathing.

• After skin contact:

Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment in case of complaints.

• After eye contact:

Remove contact lenses if worn.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing:

Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.
A person vomiting while lying on their back should be turned onto their side.

• Most important symptoms and effects, both acute and delayed

Coughing
Dizziness
Breathing difficulty
Gastric or intestinal disorders.
May be harmful in contact with skin.
May be harmful if inhaled.
Causes mild skin irritation.

• Hazards: Danger of impaired breathing.

• Indication of any immediate medical attention and special treatment needed

If swallowed, gastric irrigation with added, activated carbon.
If swallowed or in case of vomiting, danger of entering the lungs.

(Cont'd. on page 4)

Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

Trade name: Rislone® Rislone® Gas Fuel System Cleaner – Right Side

(Cont'd. from page 3)

Medical supervision for at least 48 hours.
If necessary oxygen respiration treatment.
Later observation for pneumonia and pulmonary oedema.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 - Foam
 - Alcohol resistant foam
 - Gaseous extinguishing agents
 - Carbon dioxide
 - Fire-extinguishing powder
 - Water haze or fog
- **For safety reasons unsuitable extinguishing agents:**
 - Water with full jet
 - Water spray
- **Special hazards arising from the substance or mixture**
 - Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
 - Wear self-contained respiratory protective device.
 - Wear fully protective suit.
- **Additional information:**
 - Cool endangered receptacles with water fog or haze.
 - Use large quantities of foam as it is partially destroyed by the product.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Use respiratory protective device against the effects of fumes/dust/aerosol.
 - Keep away from ignition sources.
 - Wear protective equipment. Keep unprotected persons away.
 - Ensure adequate ventilation
 - Particular danger of slipping on leaked/spilled product.
- **Environmental precautions**
 - Do not allow to enter sewers/ surface or ground water.
 - Prevent from spreading (e.g. by damming-in or oil barriers).
 - Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**
 - Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).
 - Remove from the water surface (e.g. skim or suck off).
 - Send for recovery or disposal in suitable receptacles.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

(Cont'd. on page 5)

Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

Trade name: Rislone® Gas Fuel System Cleaner – Right Side

(Cont'd. from page 4)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep out of reach of children.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Avoid breathing mist/vapours/spray.
Avoid contact with the eyes and skin.
- **Information about fire - and explosion protection:**
Keep respiratory protective device available.
Keep ignition sources away - Do not smoke.
- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**
Avoid storage near extreme heat, ignition sources or open flame.
Store in cool, dry conditions in well sealed receptacles.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidising agents.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

95-63-6 1,2,4-trimethylbenzene

IOELV (EU)	Long-term value: 100 mg/m ³ , 20 ppm
REL (USA)	Long-term value: 125 mg/m ³ , 25 ppm
TLV (USA)	Long-term value: 123 mg/m ³ , 25 ppm

108-67-8 mesitylene

IOELV (EU)	Long-term value: 100 mg/m ³ , 20 ppm
REL (USA)	Long-term value: 125 mg/m ³ , 25 ppm
TLV (USA)	Long-term value: 123 mg/m ³ , 25 ppm

526-73-8 1,2,3-trimethylbenzene

IOELV (EU)	Long-term value: 100 mg/m ³ , 20 ppm
REL (USA)	Long-term value: 125 mg/m ³ , 25 ppm
TLV (USA)	Long-term value: 123 mg/m ³ , 25 ppm

98-82-8 Cumene

OEL (South Africa)	Short-term value: 370 mg/m ³ , 75 ppm Long-term value: 120 mg/m ³ , 25 ppm Sk
IOELV (EU)	Short-term value: 250 mg/m ³ , 50 ppm Long-term value: 100 mg/m ³ , 20 ppm Skin

(Cont'd. on page 6)

Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

Trade name: Rislone® Gas Fuel System Cleaner – Right Side

(Cont'd. from page 5)

PEL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
TLV (USA)	Long-term value: (246) NIC-5 mg/m ³ , (50) NIC-1 ppm NIC-A3

- **Exposure controls**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

- **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.
Use suitable respiratory protective device when aerosol or mist is formed.
For spills, respiratory protection may be advisable.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing

- **Limitation and supervision of exposure into the environment:**

No further relevant information available.

- **Risk management measures:** No further relevant information available.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **Appearance**

Form: Liquid
Colour: Light yellow

- **Odour:** Petroleum-like

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Melting point/freezing point:** Not determined.

- **Initial boiling point and boiling range:** >35 °C

- **Flash point:** 40.6 °C

(Cont'd. on page 7)

Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

Trade name: Rislone® Gas Fuel System Cleaner – Right Side

(Cont'd. from page 6)

· Flammability (solid, gas):	Not applicable.
· Auto/Self-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits Lower: Upper:	Not determined. Not determined.
· Oxidising properties	Non-oxidising.
· Vapour pressure:	Not determined.
· Density: Relative density: Vapour density: Evaporation rate:	0.77 Not determined. Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity Dynamic: Kinematic at 40 °C:	Not determined. 1.4 mm ² /s
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Flammable liquid and vapour.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
Reacts with oxidising agents.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidisers
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:** None.

(Cont'd. on page 8)

Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

Trade name: Rislone® Gas Fuel System Cleaner – Right Side

(Cont'd. from page 7)

- **Primary irritant effect**
- **Skin corrosion/irritation:** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation:** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation:** Based on available data, the classification criteria are not met.
- **IARC (International Agency for Research on Cancer):**

Present in trace quantities: all except 98-82-8.

98-82-8	Cumene	2B
71-43-2	Benzene	1
75-07-0	acetaldehyde	2B
75-56-9	propylene oxide	2B
91-20-3	Naphthalene	2B
100-41-4	Ethylbenzene	2B
100-42-5	styrene	2B

- **Probable routes of exposure:**
Ingestion.
Inhalation.
Eye contact.
Skin contact.
- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

• Toxicity

• Aquatic toxicity:

128-39-2 2,6-di-tert-butylphenol

LC50 0.89 mg/l (Oncorhynchus mykiss)

- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **Bioaccumulative potential** Does not accumulate in organisms.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- **Additional ecological information:**
- **General notes:** Avoid transfer into the environment.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

(Cont'd. on page 9)

Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

Trade name: Rislone® Gas Fuel System Cleaner – Right Side

(Cont'd. from page 8)

- **Waste treatment methods**

- **Recommendation**

Contact waste processors for recycling information.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- **DOT**

NA1993

- **ADR/RID/ADN, IMDG, IATA**

UN1268

- **UN proper shipping name**

- **DOT**

Combustible liquid, n.o.s. (petroleum distillates)

- **ADR/RID/ADN, IMDG**

PETROLEUM PRODUCTS, N.O.S.

- **IATA**

Petroleum products, n.o.s.

- **Transport hazard class(es)**

- **DOT**



- **Class**

3

- **Label**

3

- **ADR/RID/ADN**



- **Class**

3 (F1)

- **Label**

3

- **IMDG, IATA**



- **Class**

3

- **Label**

3

- **Packing group**

- **DOT, ADR/RID/ADN, IMDG, IATA**

III

- **Environmental hazards:**

(Cont'd. on page 10)




Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

Trade name: Rislone® Gas Fuel System Cleaner – Right Side

(Cont'd. from page 9)

· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	30
· EMS Number:	F-E,S-E
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	Classified as combustible under US DOT regulations. Labeling is only required for single packages 119 US gal / 450 L.
· ADR/RID/ADN	
	Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.
· IMDG	
	Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.
· IATA	
	Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each / 10 L net.

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **IARC (International Agency for Research on Cancer)**

Present in trace quantities: all except 98-82-8.

98-82-8	Cumene	2B
71-43-2	Benzene	1
75-07-0	acetaldehyde	2B
75-56-9	propylene oxide	2B
91-20-3	Naphthalene	2B
100-41-4	Ethylbenzene	2B
100-42-5	styrene	2B
110-00-9	furan	2B

(Cont'd. on page 11)

Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

Trade name: Rislone® Gas Fuel System Cleaner – Right Side

(Cont'd. from page 10)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapour.
 H302 Harmful if swallowed.
 H303 May be harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H313 May be harmful in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H333 May be harmful if inhaled.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H401 Toxic to aquatic life.
 H411 Toxic to aquatic life with long lasting effects.

- **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bio-accumulable, Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 5: Acute toxicity – Category 5
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Skin Corr. 3: Skin corrosion/irritation – Category 3
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- **Sources**

Website, European Chemicals Agency (echa.europa.eu)
 Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)
 Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
 Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaassen, Curtis D., ed., ISBN: 978-0-07-176923-5.
 Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

(Cont'd. on page 12)

Safety Data Sheet

in accordance with SANS

Revision: 27 January 2022

Trade name: Rislone® Gas Fuel System Cleaner – Right Side

(Cont'd. from page 11)

ChemTel Inc.
1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com