

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

1 Identification of the substance or mixture and of the supplier

· Product identifier

- **Trade name:** Rislone® Diesel Fuel System Treatment - Right Side
- **Product code:** 44740
- **Application of the substance / the mixture:** Treatment for diesel fuel.
- **Uses advised against:** No further relevant information available.

· Details of the supplier of the Safety Data Sheet

· **Manufacturer/Supplier:**

Rislone
P.O. Box 187
Holly, MI 48442
USA
Phone: (810) 603-1321

· **Distributor:**

Keizin Automotive
Unit B6, Glen Murray Ind. Park
PO Box 201728, Durban North, 4016
South Africa

· **Emergency telephone number:**

ChemTel Inc.
(800) 255-3924 (North America)
(801) 1 (813)248-0585 (International)



2 Hazards identification

· **Classification of the substance or mixture**

Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Acute 3	H402	Harmful to aquatic life.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

· **Label elements**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Distillates (petroleum), hydro- treated light
Hydrocarbons, C9, aromatics
Solvent naphtha (petroleum), heavy arom.
1,2,4-trimethylbenzene
Xylene

(Cont'd. on page 2)

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 1)

· Hazard statements

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H304 May be fatal if swallowed and enters airways.
- H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P264 Wash thoroughly after handling.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
- P331 Do NOT induce vomiting.
- P321 Specific treatment (see on this label).
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P332+P313 If skin irritation occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use to extinguish: CO₂, powder or water spray.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Other hazards** There are no other hazards not otherwise classified that have been identified.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients**· Chemical characterisation: Mixtures****· Components:**

64742-47-8	Distillates (petroleum), hydro- treated light ⚠ Asp. Tox. 1, H304 Flam. Liq. 4, H227; Acute Tox. 5, H313	60-80%
111-76-2	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 Flam. Liq. 4, H227	10-<20%
64742-95-6	Hydrocarbons,C9,aromatics	<10%

(Cont'd. on page 3)

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 2)

	<ul style="list-style-type: none"> ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H335-H336 Acute Tox. 5, H313; Aquatic Acute 2, H401 	
112-80-1	oleic acid, pure Skin Corr. 3, H316; Eye Irrit. 2B, H320	<2.5%
64742-94-5	Solvent naphtha (petroleum), heavy arom. <ul style="list-style-type: none"> ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 Flam. Liq. 4, H227 	<2.5%
95-63-6	1,2,4-trimethylbenzene <ul style="list-style-type: none"> ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Acute Tox. 5, H303; Aquatic Acute 2, H401 	<2.5%
108-67-8	mesitylene <ul style="list-style-type: none"> ⚠ Flam. Liq. 3, H226 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H335 	<2.5%
1330-20-7	Xylene <ul style="list-style-type: none"> ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335 Acute Tox. 5, H303; Aquatic Acute 3, H402; Aquatic Chronic 3, H412 	<1%
98-82-8	Cumene <ul style="list-style-type: none"> ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H302; STOT SE 3, H335 Acute Tox. 5, H333 	<0.25%
91-20-3	Naphthalene <ul style="list-style-type: none"> ⚠ Flam. Sol. 2, H228 ⚠ Carc. 2, H351 ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Acute Tox. 4, H302 Acute Tox. 5, H313 	<0.25%

· **Additional information:**

For the listed ingredient(s), the identity and/or exact percentages are being withheld as a trade secret.

For the wording of the listed Hazard Statements refer to section 16.

4 First aid measures

· **Description of first aid measures**

· **After inhalation:**

(Cont'd. on page 4)

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 3)

Supply fresh air.

Provide oxygen treatment if affected person has difficulty breathing.

If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

• **After skin contact:**

Immediately remove any clothing soiled by the product.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Wash with soap and water.

If skin irritation continues, consult a doctor.

• **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. Then consult a doctor.

• **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

A person vomiting while lying on their back should be turned onto their side.

• **Most important symptoms and effects, both acute and delayed**

Breathing difficulty

Dizziness

Coughing

Causes eye irritation.

Causes skin irritation.

• **Hazards:**

Danger of impaired breathing.

May be fatal if swallowed and enters airways.

• **Indication of any immediate medical attention and special treatment needed**

If swallowed or in case of vomiting, danger of entering the lungs.

Medical supervision for at least 48 hours.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary oedema.

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

• **Extinguishing media**

• **Suitable extinguishing agents:**

Foam

Carbon dioxide

Fire-extinguishing powder

Gaseous extinguishing agents

Water haze or fog

• **For safety reasons unsuitable extinguishing agents:** Water with full jet

• **Special hazards arising from the substance or mixture** Flammable liquid and vapour.

• **Advice for firefighters**

• **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

• **Additional information:** Eliminate all ignition sources if safe to do so.

(Cont'd. on page 5)

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 4)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

- **Environmental precautions**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

- **Methods and material for containment and cleaning up**

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Send for recovery or disposal in suitable receptacles.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Flammable liquid and vapour.

- **Conditions for safe storage, including any incompatibilities**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Avoid storage near extreme heat, ignition sources or open flame.

- **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidising agents.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

111-76-2 2-butoxyethanol

OEL (South Africa)	Long-term value: 120 mg/m ³ , 25 ppm Sk
--------------------	---

IOELV (EU)	Short-term value: 246 mg/m ³ , 50 ppm
------------	--

(Cont'd. on page 6)

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 5)

PEL (USA)	Long-term value: 98 mg/m ³ , 20 ppm Skin
REL (USA)	Long-term value: 240 mg/m ³ , 50 ppm Skin
TLV (USA)	Long-term value: 24 mg/m ³ , 5 ppm Skin
	Long-term value: 97 mg/m ³ , 20 ppm BEI
95-63-6 1,2,4-trimethylbenzene	
IOELV (EU)	Long-term value: 100 mg/m ³ , 20 ppm
REL (USA)	Long-term value: 125 mg/m ³ , 25 ppm
TLV (USA)	Long-term value: 123 mg/m ³ , 25 ppm
108-67-8 mesitylene	
IOELV (EU)	Long-term value: 100 mg/m ³ , 20 ppm
REL (USA)	Long-term value: 125 mg/m ³ , 25 ppm
TLV (USA)	Long-term value: 123 mg/m ³ , 25 ppm
1330-20-7 Xylene	
OEL (South Africa)	Short-term value: 435 mg/m ³ , 100 ppm Long-term value: 218 mg/m ³ , 50 ppm Sk
IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
PEL (USA)	Long-term value: 435 mg/m ³ , 100 ppm
REL (USA)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (USA)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
98-82-8 Cumene	
OEL (South Africa)	Short-term value: 370 mg/m ³ , 75 ppm Long-term value: 120 mg/m ³ , 25 ppm Sk
IOELV (EU)	Short-term value: 250 mg/m ³ , 50 ppm Long-term value: 100 mg/m ³ , 20 ppm Skin
PEL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL (USA)	Long-term value: 245 mg/m ³ , 50 ppm Skin
TLV (USA)	Long-term value: (246) NIC-5 mg/m ³ , (50) NIC-1 ppm NIC-A3
91-20-3 Naphthalene	
OEL (South Africa)	Short-term value: 75 mg/m ³ , 15 ppm Long-term value: 50 mg/m ³ , 10 ppm

(Cont'd. on page 7)

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 6)

IOELV (EU)	Long-term value: 30 mg/m ³ , 10 ppm
PEL (USA)	Long-term value: 50 mg/m ³ , 10 ppm
REL (USA)	Short-term value: 75 mg/m ³ , 15 ppm
	Long-term value: 50 mg/m ³ , 10 ppm
TLV (USA)	Long-term value: 52 mg/m ³ , 10 ppm
	Skin; BEI

· Ingredients with biological limit values:**111-76-2 2-butoxyethanol**

BEI (USA)	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----------	--

1330-20-7 Xylene

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

· Exposure controls**· General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

· **Respiratory protection:** Suitable respiratory protective device recommended.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product.

· Eye protection:

Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· **Body protection:** Protective work clothing

· Limitation and supervision of exposure into the environment:

No further relevant information available.

9 Physical and chemical properties**· Information on basic physical and chemical properties****· Appearance**

Form: Liquid

(Cont'd. on page 8)

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 7)

<ul style="list-style-type: none"> · Colour: Clear to light yellow. · Odour: Mineral-oil-like · Odour threshold: Not determined.
<ul style="list-style-type: none"> · pH-value: Not determined. · Melting point/freezing point: Not determined. · Initial boiling point and boiling range: Not determined.
<ul style="list-style-type: none"> · Flash point: 57 °C
<ul style="list-style-type: none"> · Auto/Self-ignition temperature: Not determined.
<ul style="list-style-type: none"> · Decomposition temperature: Not determined.
<ul style="list-style-type: none"> · Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<ul style="list-style-type: none"> · Explosion limits <ul style="list-style-type: none"> Lower: Not determined. Upper: Not determined. · Oxidising properties: Non-oxidising.
<ul style="list-style-type: none"> · Vapour pressure: Not determined.
<ul style="list-style-type: none"> · Density: <ul style="list-style-type: none"> Relative density: Not determined. Vapour density: Not determined. Evaporation rate: Not determined.
<ul style="list-style-type: none"> · Solubility in / Miscibility with water: Not miscible or difficult to mix.
<ul style="list-style-type: none"> · Partition coefficient: n-octanol/water: Not determined.
<ul style="list-style-type: none"> · Viscosity <ul style="list-style-type: none"> Dynamic: Not determined. Kinematic: Not determined. · Other information: No further relevant information available.

10 Stability and reactivity

- **Reactivity:** No further relevant information available.
- **Chemical stability:** Stable under normal temperatures and pressures.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions:** Flammable liquid and vapour. Used empty containers may contain product gases which form explosive mixtures with air. Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
- **Conditions to avoid:** Keep ignition sources away - Do not smoke.
- **Incompatible materials:** Oxidising agents
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

(Cont'd. on page 9)

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 8)

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:** None.
- **Primary irritant effect**
- **Skin corrosion/irritation:** Irritant to skin and mucous membranes.
- **Serious eye damage/irritation:** Causes eye irritation.
- **Respiratory or skin sensitisation:** Based on available data, the classification criteria are not met.

· **IARC (International Agency for Research on Cancer):**

98-82-8	Cumene	2B
91-20-3	Naphthalene	2B

· **Probable routes of exposure:**

Ingestion.
Inhalation.
Eye contact.
Skin contact.

- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:**
Harmful to aquatic life with long lasting effects.

64742-94-5 Solvent naphtha (petroleum), heavy arom.

LC50 | 3.6 mg/l (Oncorhynchus mykiss)

91-20-3 Naphthalene

LC50 | 1-10 mg/l (daphnia)

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

(Cont'd. on page 10)

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 9)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

· **DOT** NA1993
 · **ADR/RID/ADN, IMDG, IATA** UN1268

- **UN proper shipping name**

· **DOT** Combustible liquid, n.o.s. (Distillates (petroleum), hydro- treated light, 2-butoxyethanol)
 · **ADR/RID/ADN, IMDG** PETROLEUM DISTILLATES, N.O.S.
 · **IATA** Petroleum distillates. n.o.s.

- **Transport hazard class(es)**

- **DOT**



· **Class** 3
 · **Label** 3

- **ADR/RID/ADN**



· **Class** 3 (F1)
 · **Label** 3

- **IMDG, IATA**



· **Class** 3
 · **Label** 3

- **Packing group**

· **DOT, ADR/RID/ADN, IMDG, IATA** III

(Cont'd. on page 11)

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 10)

· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	30
· EMS Number:	F-E,S-E
· Transport in bulk according to Annex II of Marpol and the IBC Code	
	Not applicable.
· Transport/Additional information:	
· DOT	Classified as combustible under US DOT regulations. Labeling is only required for single packages 119 US gal / 450 L.

· ADR/RID/ADN	
· Transport category	3
· Tunnel restriction code	D/E

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· IARC (International Agency for Research on Cancer)		
98-82-8	Cumene	2B
91-20-3	Naphthalene	2B

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H226 Flammable liquid and vapour.

H227 Combustible liquid.

H228 Flammable solid.

H302 Harmful if swallowed.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H316 Causes mild skin irritation.

H319 Causes serious eye irritation.

H320 Causes eye irritation.

H332 Harmful if inhaled.

H333 May be harmful if inhaled.

H335 May cause respiratory irritation.

(Cont'd. on page 12)

Safety Data Sheet

in accordance with SANS

Revision: 04.02.2021

Trade name: Rislone® Diesel Fuel System Treatment - Right Side

(Cont'd. from page 11)

H336 May cause drowsiness or dizziness.
 H351 Suspected of causing cancer. Route of exposure: Inhalation.
 H400 Very toxic to aquatic life.
 H401 Toxic to aquatic life.
 H402 Harmful to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

• **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bio-accumulable, Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 3: Flammable liquids – Category 3
 Flam. Liq. 4: Flammable liquids – Category 4
 Flam. Sol. 2: Flammable solids – Category 2
 Acute Tox. 4: Acute toxicity – Category 4
 Acute Tox. 5: Acute toxicity – Category 5
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Skin Corr. 3: Skin corrosion/irritation – Category 3
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2
 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

• **Sources**

Website, European Chemicals Agency (echa.europa.eu)
 Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)
 Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)
 Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6
 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.
 Safety Data Sheets, Individual Manufacturers

SDS Prepared by:
 ChemTel Inc.
 1305 North Florida Avenue
 Tampa, Florida USA 33602-2902
 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
 Website: www.chemtelinc.com