# acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

# Printing date: 03 August 2018 Revision: 14 July 2022 **1** Identification Product identifier • Trade name: Rislone® Jack Oil with Stop Leak · Product code: 32012 · Recommended use and restriction on use · Recommended use: Lubricant · Restrictions on use: No relevant information available. <sup>•</sup> Details of the supplier of the Safety Data Sheet · Manufacturer/Supplier: Rislone P.O. Box 187 **RÍSLONE** Holly, MI 48442 USA Phone: (810) 603-1321 · Emergency telephone number: ChemTel Inc. (800)255-3924 (North America) +1 (813)248-0585 (International) 2 Hazard(s) identification · Classification of the substance or mixture Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. · Label elements · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms: GHS08 · Signal word: Danger · Hazard statements: H304 May be fatal if swallowed and enters airways. · Precautionary statements: P301+P310 If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. P331 P405 Store locked up. Dispose of contents/container in accordance with local/regional/national/international P501 regulations. • Other hazards There are no other hazards not otherwise classified that have been identified.

# **3** Composition/information on ingredients

#### <sup>•</sup> Chemical characterization: Mixtures

· Components:

## acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: 03 August 2018

Revision: 14 July 2022

#### Trade name: Rislone® Jack Oil with Stop Leak

	(Cont'd. of page 1)
64742-55-8 Distillates (petroleum), hydrotreated light paraffinic	60-80%
64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic	20-40%

#### · Additional information:

Note L: The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This product meets these requirements. For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

## 4 First-aid measures

#### <sup>•</sup> Description of first aid measures · After inhalation: Supply fresh air; consult doctor in case of complaints. Provide oxygen treatment if affected person has difficulty breathing. In case of irregular breathing or respiratory arrest provide artificial respiration. In case of unconsciousness place patient stably in side position for transportation. • After skin contact: Wash with soap and water. If skin irritation is experienced, consult a doctor. • After eye contact: Remove contact lenses if worn. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. · After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting: immediately call for medical help. A person vomiting while lying on their back should be turned onto their side. Most important symptoms and effects, both acute and delayed: Breathing difficulty Coughing Slight irritant effect on eves. Slight irritant effect on skin and mucous membranes. Gastric or intestinal disorders when ingested. Nausea in case of ingestion. Danger: Danger of impaired breathing. May be fatal if swallowed and enters airways. Indication of any immediate medical attention and special treatment needed: If swallowed or in case of vomiting, danger of entering the lungs. If necessary oxygen respiration treatment. Later observation for pneumonia and pulmonary edema. Medical supervision for at least 48 hours. If medical advice is needed, have product container or label at hand.

## acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: 03 August 2018

Revision: 14 July 2022

## Trade name: Rislone® Jack Oil with Stop Leak

(Cont'd. of page 2)

## **5 Fire-fighting measures**

## Extinguishing media

### Suitable extinguishing agents:

Foam

Gaseous extinguishing agents

Carbon dioxide

Fire-extinguishing powder

For safety reasons unsuitable extinguishing agents: Water

• Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

## Advice for firefighters

• Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

# 6 Accidental release measures

## • Personal precautions, protective equipment and emergency procedures

Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Particular danger of slipping on leaked/spilled product.

#### Environmental precautions

Avoid release to the environment.

Prevent from spreading (e.g. by damming-in or oil barriers).

#### · Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Remove from the water surface (e.g. skim or suck off).

Send for recovery or disposal in suitable receptacles.

### Reference to other sections

## See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

#### <sup>·</sup> Handling

· Precautions for safe handling:

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

Information about protection against explosions and fires: No special measures required.

# Conditions for safe storage, including any incompatibilities

· Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame. Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

(Cont'd. on page 4)

## acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: 03 August 2018

Revision: 14 July 2022

Trade name: Rislone® Jack Oil with Stop Leak

(Cont'd. of page 3)

Store away from foodstuffs.

Store away from oxidizing agents.

Specific end use(s) No relevant information available.

# 8 Exposure controls/personal protection

## · Control parameters

· Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

## • Exposure controls

#### · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid close or long term contact with the skin.

· Engineering controls: No relevant information available.

#### · Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

# Protection of hands:



Protective gloves

Gloves are advised for repeated or prolonged contact.

Wear protective gloves to handle contents of damaged or leaking units.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. · Eye protection:



Safety glasses

- · Body protection: Oil resistant protective clothing
- · Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

# 9 Physical and chemical properties

<sup>•</sup> Information on basic physical and chemical properties · Appearance:

(Cont'd. on page 5)

# acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: 03 August 2018

Revision: 14 July 2022

# Trade name: Rislone® Jack Oil with Stop Leak

		(Cont'd. of pag
Form:	Liquid	
Color:	Amber colored	
Odor:	Petroleum-like	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Melting point/Melting range:	Not determined.	
Boiling point/Boiling range:	Not determined.	
Flash point:	>93 °C (>199.4 °F)	
Flammability (solid, gaseous):	Not applicable.	
Auto-ignition temperature:	Not determined.	
Decomposition temperature:	Not determined.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits		
Lower:	Not determined.	
Upper:	Not determined.	
Oxidizing properties:	Non-oxidizing.	
Vapor pressure:	Not determined.	
Density:		
Relative density:	0.8-0.9	
Vapor density:	Not determined.	
Evaporation rate:	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ter): Not determined.	
Viscosity		
Dynamic:	Not determined.	
Kinematic at 40 °C (104 °F):	11.50-13.50 cSt	
Other information	No relevant information available.	

# 10 Stability and reactivity

• **Reactivity:** No relevant information available.

• Chemical stability: Stable under normal temperatures and pressures.

· Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

To avoid thermal decomposition, do not overheat.

Possibility of hazardous reactions

Toxic fumes may be released if heated above the decomposition point.

Reacts with strong oxidizing agents.

• Conditions to avoid Excessive heat.

· Incompatible materials Oxidizers

(Cont'd. on page 6)

## acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: 03 August 2018

Revision: 14 July 2022

Trade name: Rislone® Jack Oil with Stop Leak

(Cont'd. of page 5)

# <sup>•</sup> Hazardous decomposition products

Carbon monoxide and carbon dioxide

Hydrocarbons

# 11 Toxicological information

## <sup>·</sup> Information on toxicological effects

• Acute toxicity: Based on available data, the classification criteria are not met.

- · LD/LC50 values that are relevant for classification: None.
- · Primary irritant effect:

• On the skin: Slight irritant effect on skin and mucous membranes.

- On the eye: Slight irritant effect on eyes.
- · Sensitization: No sensitizing effects known.

# · IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

## • NTP (National Toxicology Program):

None of the ingredients are listed.

## · OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

## • Probable route(s) of exposure:

Ingestion.

Inhalation.

Eye contact.

Skin contact.

• Germ cell mutagenicity: Based on available data, the classification criteria are not met.

- · Carcinogenicity: Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.

• STOT-single exposure: Based on available data, the classification criteria are not met.

• STOT-repeated exposure: Based on available data, the classification criteria are not met.

• Aspiration hazard: May be fatal if swallowed and enters airways.

# **12 Ecological information**

- <sup>·</sup> Toxicity
- · Aquatic toxicity No relevant information available.
- Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- Ecotoxical effects:

• Remark: Due to mechanical actions of the product (e.g. agglutinations), damages may occur.

· Additional ecological information

- · General notes: Avoid release to the environment.
- <sup>·</sup> Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

#### · vPvB: Not applicable.

(Cont'd. on page 7)

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: 03 August 2018

Revision: 14 July 2022

Trade name: Rislone® Jack Oil with Stop Leak

(Cont'd. of page 6)

• Other adverse effects No relevant information available.

# **13 Disposal considerations**

## <sup>•</sup> Waste treatment methods

· Recommendation:

Contact waste processors for recycling information.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

## <sup>·</sup> Uncleaned packagings

• **Recommendation:** Disposal must be made according to official regulations.

UN-Number	
DOT, ADR, IMDG, IATA	Not regulated.
UN proper shipping name	
DOT, ADR, IMDG, IATA	Not regulated.
Transport hazard class(es)	
DOT, ADR, IMDG, IATA	
Class	Not regulated.
Packing group	
DOT, ADR, IMDG, IATA	Not regulated.
Environmental hazards	
Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.

# 15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture

· United States (USA)

·SARA

• Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 355 (extremely hazardous substances):

(Cont'd. on page 8)

## acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: 03 August 2018

Revision: 14 July 2022

#### Trade name: Rislone® Jack Oil with Stop Leak

(Cont'd. of page 7)

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

· TSCA (Toxic Substances Control Act)

All ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· Canadian Domestic Substances List (DSL) (Substances not listed.):

All ingredients are listed.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent OSHA: Occupational Safety & Health Administration Asp. Tox. 1: Aspiration hazard - Category 1 Sources Website, European Chemicals Agency (echa.europa.eu) Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do) Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org) Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6 Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5. Safety Data Sheets, Individual Manufacturers SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com