According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7<sup>th</sup> Revised Edition

Printing Date: 29 August 2022 Revision: 05 October 2022

## 1. Identification

#### **Product identifier**

Trade name: Rislone® Diesel Fuel System Treatment - Left Side

Product code: 44740

Recommended use and restriction on use Recommended use: Treatment for diesel fuel

Restrictions on use: No further relevant information available.

# Details of the supplier of the Safety Data Sheet Manufacturer/Supplier:

Rislone P.O. Box 187 Holly, MI 48442 USA Phone: (810) 603-1321



### **Distributor:**

Smits Group Pty Ltd. 59 Greenmount Dr, East Tamaki, Auckland, New Zealand NZ Telephone: +09 274 6871 1 AUS Telephone 1800 883 888

### **Emergency telephone number:**

ChemTel Inc. (800) 255-3924 (North America) +1 (813) 248-0585 (International)

New Zealand 0800 764 766 (National Poison Control Centre) Australia 131126 (NSW Poison Control Centre)

## 2. Hazards identification

## **GHS Classification**

Flammable liquids	Category 4 – (H227)
Aspiration hazard	Category 1 – (H304)
Germ cell mutagenicity	Category 1B – (H340)
Carcinogenicity	Category 1B – (H350)

### Label elements

Health hazard

Page **2** of **14** 

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7<sup>th</sup> Revised Edition

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side



Signal word: Danger Hazard Statements: H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

H340 May cause genetic defects

H350 May cause cancer

## **Precautionary Statements- Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

## **Precautionary Statements- Response**

IF exposed or concerned: Get medical advice/attention

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

## **Precautionary Statements- Storage**

Store locked up

Store in a well-ventilated place. Keep cool

## **Precautionary Statements- Disposal**

Dispose of contents/container to an approved waste disposal plant

### Other hazards which do not result in classification

May be harmful if swallowed.

May be harmful in contact with skin.

Toxic to aquatic life with long lasting effects.

General Hazards: No information available.

## 3. Composition and information on ingredients

Substance: Not applicable.

**Chemical characterization: Mixtures** 

Chemical name	CAS No	Weight-%
Petroleum distillates, hydrotreated light	64742-47-8	80-100%

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7<sup>th</sup> Revised Edition

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

2-Ethylhexyl nitrate	27247-96-7	1-5%
Naphtha (petroleum), heavy aromatic	64742-94-5	1-5%
Petroleum naphtha, light aromatic	64742-95-6	1-5%
1,2,4 Trimethylbenzene	95-63-6	0.1-1%
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	0.1-1%
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	0.1-1%
2,6-Di-ter-butylphenol	128-39-2	0.1-1%
Third Party Formulation	-	0-10%

#### **Note**

## 4. First-aid measures

## Description of first aid measures

### General advice:

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.

## **Emergency telephone number**

Poisons Information Center, Australia: 13 11 26

Poisons Information Center, New Zealand: 0800 764 766

## After inhalation:

Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical advice/attention. Delayed pulmonary edema may occur.

### After eye contact:

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing.

### After skin contact:

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

#### After inaestion:

Aspiration hazard if swallowed- can enter lungs and cause damage. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Get immediate medical advice/attention.

#### Self-protection of the first aider:

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required.

## Most important symptoms and effects, both acute and delayed:

Difficulty in breathing.

Coughing and/or wheezing.

Dizziness.

# Indication of any immediate medical attention and special treatment needed Note to physicians:

Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

## 5. Fire-fighting measures

## Extinguishing media

## Suitable extinguishing agents:

Dry chemical

Carbon dioxide (CO2)

Water spray

Alcohol resistant foam

For safety reasons unsuitable extinguishing agents: No information available.

## Special hazards arising from the substance or mixture:

Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

Hazardous combustion products: Carbon oxides.

## Advice for firefighters

#### **Protective equipment:**

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment

Hazchem code: •3Z

### 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures Personal precautions

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material. Ensure adequate ventilation.

Other information: Refer to protective measures listed in Sections 7 and 8.

For emergency responders: Use personal protection recommended in Section 8.

#### **Environmental precautions:**

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so

## Methods and material for containment and cleaning up

## **Methods for containment**

Stop leak if you can do it without risk. Do not touch or walk through spilled material. Dike far ahead of liquid spill for later disposal.

### Methods for cleanup

Take precautionary measures against static discharges. Dam up. Soap up with inert absorbent material. Pick up and transfer to properly labeled containers.

### Precautions to prevent secondary hazards

**Prevention of secondary hazards:** Clean contaminated objects and areas thoroughly observing environmental regulations.

Page **5** of **14** 

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7<sup>th</sup> Revised Edition

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

## 7. Handling and storage

## Handling:

## Precautions for safe handling

Use personal protection equipment. Do not breathe vapor or mist. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use with local exhaust ventilation. Hand in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes.

## General hygiene considerations:

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

# Conditions for safe storage, including any incompatibilities Storage conditions:

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with particular national regulation. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials. **Incompatible materials:** None known based on information supplied.

## 8. Exposure controls/personal protection

# Control parameters Exposure limits

Chemical name Australia **ACGIH TLV** Petroleum distillates, hydrotreated light TWA: 5 ma/m<sup>3</sup> 64742-47-8 STEL: 10 ma/m<sup>3</sup> (as oil mist) 1,2,4 Trimethylbenzene TWA: 10 ppm 95-63-6 Petroleum distillates, hydrotreated light TWA: 5 mg/m<sup>3</sup> STEL: 10 mg/m<sup>3</sup> paraffinic 64742-55-8 (as oil mist) TWA: 5 mg/m<sup>3</sup>, as oil mist, mineral Petroleum distillates, hydrotreated heavy paraffinic STEL: TWA: 10 mg/m3. as oil mist, mineral 64742-54-7 Third Party Formulation 10 ppm TWA TWA: 10 ppm 52 mg/m<sup>3</sup> TWA S\* 15 ppm STEL 79 mg/m3 STEL

**Legend:** See section 16 for terms and abbreviations

Chemical name	Australia	ACGIH
Third Party Formulation		- (1-Naphthol with hydrolysis plus 2-
-		Napthol with hydrolysis)- end of shift

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7<sup>th</sup> Revised Edition

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

Appropriate engineering controls

Individual protection measures, such as personal protective equipment

**Eye/face protection Skin and body protection**Tight sealing safety goggles.
Wear suitable protective clothing.

**Hand protection** Wear suitable gloves.

Respiratory protection 
No protective equipment is needed under normal use conditions. If

exposure limits are exceeded or irritation is experienced, ventilation and

evacuation may be required.

Environmental exposure controls No information available.

## 9. Physical and chemical properties

## Information on basic physical and chemical properties

#### **General information**

	T
Appearance	
Form	Liquid
Colour	Green
Odour	Petroleum
Odour threshold	Not determined.
Change in condition	
Melting point/Melting range	Not determined.
Boiling point/Boiling range	150°C (302°F)
Flammability (solid, gaseous)	Flammable.
Explosive properties	No information available.
Explosion limits	
Lower	Not determined.
Upper	Not determined.
Oxidising properties	Non-oxidising.
Flash point	62°C (144°F)
Auto/Self-ignition temperature	Not determined.
Decomposition temperature	Not determined.
pH-value	Not determined.
Viscosity	
Dynamic	Not determined.
Kinematic	Not determined.
Solubility in/Miscibility with water	Immiscible
Partition coefficient (n-	
octanol/water) at 20°C	Not determined.
Vapour pressure	Not determined.
Density	
Relative density	0.82
Vapour density	Not determined.
Evaporation rate	Not determined.
Particle characteristics	Not determined.

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7<sup>th</sup> Revised Edition

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

Other information	No further relevant information available.
-------------------	--

## 10. Stability and Reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Sensitivity to Mechanical Impact: None Sensitivity to Static Discharge: Yes

**Possibility of hazardous reactions:** None under normal processing **Hazardous Polymerization:** Hazardous polymerization does not occur.

Conditions to avoid: Heat, flames and sparks.

Incompatible materials None known based on information supplied.

Hazardous decomposition products Carbon oxides

## 11. Toxicological information

## Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

#### **Product information**

#### Inhalation:

Specific teat data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.

### Eve contact:

Specific test data for the substance or mixture is not available. May cause irritation.

#### Skin contact:

Repeated exposure may cause skin dryness or cracking. May be harmful in contact with skin.

#### Ingestion:

Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

## Symptoms:

Difficulty breathing.

Coughing and/or wheezing.

Dizziness.

## **Numerical measures of toxicity**

0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7<sup>th</sup> Revised Edition

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Mg/kg (rat) Estimated

## **Component information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates,	>5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	>5.2 mg/L (Rat) 4h
hydrotreated light			
2-Ethylhexyl nitrate	>9600 mg/kg (Rat)	>4800 mg/kg (Rabbit)	>14 mg/L (Rat) 4h
Naphtha (petroleum), heavy	>5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	>590 mg/m³ (Rat) 4h
aromatic			
Petroleum naphtha, light	=8400 mg/kg (Rat)	>2000 mg/kg (Rabbit)	=3400 ppm (Rat) 4h
aromatic			
1,2,4 Trimethylbenzene	=3280 mg/kg (Rat)	>3160 mg/kg (Rabbit)	=18 g/m³ (Rat) 4h
Petroleum distillates,	-	-	=3900 mg/m <sup>3</sup> (Rat) 4h
hydrotreated light paraffinic			
Petroleum distillates,	>15 g/kg (Rat)	>5000 mg/kg (Rabbit)	-
hydrotreated heavy paraffinic			
2,6-Di-tert-butylphenol	>5000 mg/kg (Rat)	>10 g/kg (Rabbit)	-
Third Party Formulation	=1110 mg/kg (Rat)	=1120 mg/kg (Rabbit)	>0.4 mg/L (Rat) 4h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation: No information available.
Serious eye damage/irritation: No information available.
Respiratory or skin sensitisation: No information available.

Germ cell mutagenicity: Contains a known or suspected mutagen. Classification based on data

available for ingredients. May cause genetic defects.

Carcinogenicity: Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia
Petroleum naphtha, light aromatic	Carc. 1A
Petroleum distillates, hydrotreated light paraffinic	Carc. 1B
Petroleum distillates, hydrotreated heavy paraffinic	Carc. 1B
Third Party Formulation	Carc. 2

Reproductive toxicity: No information available. STOT-single exposure: No information available. STOT-repeated exposure: No information available.

Aspiration hazard: May be fatal if swallowed and enters airways.

## 12. Ecological information

## **Ecotoxicity**

**Ecotoxicity:** Toxic to aquatic life with long lasting effects

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7<sup>th</sup> Revised Edition

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

**Unknown aquatic toxicity:** 0% of the mixture consists of component(s) of unknown hazards to the aquatic environment.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum distillates, hydrotreated light	No data available	96h LC50: =2.2 mg/L (Lepomis macrochirus) 96h LC50: =2.4 mg/L (Oncorhynchus mykiss) 96h LC50: =45 mg/L (Pimephales promelas)	No data available	No data available
2-Ethylhexyl nitrate	No data available	96h LC50: =2 mg/L (Danio rerio)	EC50 = 100 mg/L 15 min	No data available
Naphtha (petroleum), heavy aromatic	No data available	96h LC50: =1740 mg/L (Lepomis macrochirus) 96h LC50: =19 mg/L (Pimephales promelas) 96h LC50: =2.34 mg/L (Oncorhynchus mykiss) 96h LC50: =41 mg/L (Pimephales promelas) 96h LC50: =45 mg/L (Pimephales promelas)	No data available	48h EC50: =0.95 mg/L (Daphnia magna)
Petroleum naphtha, light aromatic	No data available	96h LC50: =9.22 mg/L (Oncorhynchus mykiss)	No data available	48h EC50: =6.14 mg/L (Daphnia magna)
1,2,4 Trimethylbenzene	No data available	96h LC50: 7.19-8.28 mg/L (Pimephales promelas)	No data available	48h EC50: =6.14 mg/L (Daphnia magna)
Petroleum distillates, hydrotreated light paraffinic	No data available	96h LC50: >5000 mg/L (Oncorhynchus mykiss)	No data available	48h EC50: >1000 mg/L (Oncorhynchus mykiss)
Petroleum distillates, hydrotreated heavy paraffinic	No data available	96h LC50: >5000 mg/L (Oncorhynchus mykiss)	No data available	48h EC50: >1000 mg/L (Daphnia magna)
2,6-Di-tert- butylphenol	No data available	No data available	No data available	48h EC50: =0.45 mg/L (Daphnia magna)
Third Party Formulation	No data available	96h LC50:0.91-2.82 mg/L (Oncorhynchus mykiss) 96h LC50: 5.74-6.44 mg/L (Pimephales promelas) 96h LC50: =1.6 mg/L (Oncorhynchus mykiss)	EC50 =0.93 mg/L 30 min EC50 >20 mg/L 18 h	48h EC50: 1.09- 3.4 mg/L (Daphnia magna) 48h EC50: =1.96 mg/L (Daphnia magna)

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7<sup>th</sup> Revised Edition

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

96h LC50: =1.99 mg/L	48h LC50: =2.16
(Pimephales promelas)	mg/L (Daphnia
96h LC50: =31.0265	magna)
mg/L (Lepomis	,
macrochirus)	

Persistence and degradability: No information available

Bioaccumulative potential Component information

Chemical name	Partition coefficient
2-Ethylhexyl nitrate	5.24
Naphtha (petroleum), heavy aromatic	6.5
1,2,4 Trimethylbenzene	3.63
2,6-Di-tert-butylphenol	4.5
Third Party Formulation	3.4

**Mobility in soil:** No information available **Mobility:** No information available

Other adverse effects: No information available

## 13. Disposal considerations

### Waste treatment methods

## Waste from residues/unused products

Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

## Contaminated packaging:

Do not reuse empty containers.

## 14. Transport information

ADG Not applicable

Hazchem code •3Z

IATA Not applicable

IMDG/IMO Not applicable

Hazard Class N/A

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available.

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

## 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

## **National regulations**

### **Australia**

See section 8 for national exposure control parameters

## Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

The below table provides the relevant information for classification of this product according to the regulation. This information should be used to appropriately determine if a classification is relevant to the overall product.

Chemical name	Weight-%	Poison Schedule Number	Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)
Petroleum distillates, hydrotreated light	88.2533	5	5: including Kerosene, Diesel [distillate], Mineral turpentine, White petroleum spirit, Toluene, Xylene and light mineral and paraffin oils but except their derivative; except a) Toluene and Xylene when included in Schedule 6, b) Benzene and liquid aromatic hydrocarbons when included in Schedule 7, c) food grade and pharmaceutical grade White mineral oil, d) in solid or semi-solid preparations, e) in preparations containing <=25% of designated solvents, f) in preparations packed in pressurized spray packs, g) in adhesives packed in containers containing <=50 grams of adhesive, h) in writing correction fluids and thinners for writing correction fluids packed in containers having a capacity of <=20mL, or i) in other preparations when packed in containers with a capacity of <=2mL
Third Party Formulation	0-10%	6	6: except its derivatives; except in liquid hydrocarbons

## **National pollutant inventory**

Subject to reporting requirement

Chemical name	National pollutant inventory
Naphtha (petroleum), heavy aromatic	20 MW Threshold category 2b total
	60000 MWH Threshold category 2b total
	1 tonne/h Threshold category 2a total
	25 tonne/yr Threshold category 1a total
	400 tonne/yr Threshold category 2a total
	2000 tonne/yr Threshold category 2b total

According to The Model Work Health and Safety Regulations, and the Globally Harmonized System of Classification and Labelling of Chemicals 7<sup>th</sup> Revised Edition

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

1,2,4 Trimethylbenzene	20 MW Threshold category 2b total	
	60000 MWH Threshold category 2b total	
	1 tonne/h Threshold category 2a total	
	25 tonne/yr Threshold category 1a total	
	400 tonne/yr Threshold category 2a total	
	2000 tonne/yr Threshold category 2b total	
Third Party Formulation	20 MW Threshold category 2b total	
	60000 MWH Threshold category 2b total	
	1 tonne/h Threshold category 2a total	
	25 tonne/yr Threshold category 1a total	
	400 tonne/yr Threshold category 2a total	
	2000 tonne/yr Threshold category 2b total	

#### International inventories

**TSCA** Contact supplier for inventory compliance status. DSL/NDSL Contact supplier for inventory compliance status. **EINECS/ELINCS** Contact supplier for inventory compliance status. **ENCS** Contact supplier for inventory compliance status. Contact supplier for inventory compliance status. **IECSC** KECL Contact supplier for inventory compliance status. **PICCS** Contact supplier for inventory compliance status. **AICS** Contact supplier for inventory compliance status.

### Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

## **International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer: Not applicable

The Stockholm Convention on Persistent Organic Pollutants: Not applicable

The Rotterdam Convention: Not applicable

## 16. Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Date of preparation of latest revision of SDS

October 5, 2022: Revised SDS to comply with The Model Work Health and Safety Regulation, and the Globally Harmonized System of Classification and Labelling of Chemicals 7<sup>th</sup> Revised Edition.

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

#### Abbreviations and acronyms:

TWA Ceiling TWA (time-weighted average) Maximum STEL STEL (Short Term Exposure Limit) limit value - Skin designation

C Carcinogen

## Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database European Food Safety Authority (EFSA)

EPA (Environmental Protection Agency) Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

Organization for Economic Co-operation and Development High Production Volume Chemicals Program Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID) Japan GHS Classification

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS) NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED) National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications U.S. Environmental Protection Agency High Production Volume Chemicals

Organization for Economic Co-operation and Development Screening Information Data Set RTECS (Registry of Toxic Effects of Chemical Substances)

World Health Organization

SDS Prepared by: Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501

**Document Review: ATTENTION!** 

**Standard for Uniform Scheduling of Medicines and Poisons (SUSMP):** The below table provides the relevant information for classification of this product according to the regulation. This information should be used to appropriately determine if a classification is relevant to the overall product.

**Poison Schedule Number:** 6 **Source Information:** Present

Chemical name	Poison Schedule Number	Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)
Petroleum distillates, hydrotreated light	5	5: including Kerosene, Diesel [distillate], Mineral turpentine, White petroleum spirit, Toluene, Xylene and light mineral and paraffin oils but except their derivative; except a) Toluene and Xylene when included in Schedule 6, b) Benzene and

Revision: 05 October 2022

Trade Name: Rislone® Diesel Fuel System Treatment – Left Side

		liquid aromatic hydrocarbons when included in Schedule 7, c) food grade and pharmaceutical grade White mineral oil, d) in solid or semisolid preparations, e) in preparations containing <=25% of designated solvents, f) in preparations packed in pressurized spray packs, g) in adhesives packed in containers each containing <=50 grams of adhesive, h) in writing correction fluids and thinners for writing correction fluids packed in containers having a capacity of <=20 mL, or i) in other preparations when packed in containers with a capacity of <=2 mL
Third Party Formulation	6	6: except its derivatives; except in liquid hydrocarbons

Flammable liquids Category 4

H227- Combustible liquid

Other hazards May be harmful if swallowed. May be harmful in contact with skin. Toxic

to aquatic life. Combustible liquid.

Composition 99.749

Inhalation Statement Liquid or Aerosol
Health hazards Health hazard
Health hazards Health hazard
Environmental hazards Environment

Packing Group in Arabic Number 999