

SAFETY DATA SHEET

Rislone CVT Transmission Fix

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

▼ *Trade name:* Rislone CVT Transmission Fix

Product no.: 24514

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Lubricant Uses advised against: None known.

1.3. Details of the supplier of the safety data sheet

▼ Company and address: **Rislone**

P.O. Box 187 Holly, MI 48442

USA

(810) 603-1321 www.Rislone.com

▼ *E-mail*: support@rislone.com

SDS date: 30 January 2024

1.4. ▼ Emergency telephone number

ChemTel Inc.

(800) 255-3924 (North America) +1 (813) 248-0585 (International)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Not classified according to NOM-018-STPS-2015.

2.2. Label elements

Hazard pictogram(s):

Signal word:

Not applicable.

Not applicable.

Hazard statement(s):

Precautionary statement(s):

General: -



Prevention:

Response:

Storage:

Disposal:

Hazardous substances: Distillates (petroleum), hydrotreated light

paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt

at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based; Baseoil unspecified; [A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons

range of C15 through C30 and produces a finished oil having a viscosity of

having carbon numbers predominantly in the

approximately 15cSt at 40 °C. It contains a relatively large proportion of saturated

hydrocabons.]

Additional labelling: Not applicable.

2.3. Other hazards

This mixture/product does not contain any Additional warnings: substances known to fulfil the criteria for PBT

and vPvB classification.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. **Substances**

Not applicable. This product is a mixture.

3.2. **Mixtures**

| Product/substance | Identifiers | % w/w | Classification | Note |
|---------------------------------------|--|-------|-------------------|------|
| , , , , , , , , , , , , , , , , , , , | CAS No.: 64742-55-8 EC No.: 265-158-7 | 5-10% | Asp. Tox. 1, H304 | [19] |
| paraffinic;Baseoil - | LC No 203-130-7 | | | |
| unspecified;[A complex | | | | |



| | T | I | | |
|------------------------------|---------------------|-----------|-----------------------|------|
| combination of | | | | |
| hydrocarbons obtained | | | | |
| by treating a petroleum | | | | |
| fraction with hydrogen in | | | | |
| the presence of a | | | | |
| catalyst. It consists of | | | | |
| hydrocarbons having | | | | |
| carbon numbers | | | | |
| predominantly in the | | | | |
| range of C15 through C30 | | | | |
| and produces a finished | | | | |
| oil with a viscosity of less | | | | |
| than 100 SUS at 100 °F | | | | |
| (19cSt at 40 °C). It | | | | |
| contains a relatively large | | | | |
| proportion of saturated | | | | |
| hydrocarbons.] | | | | |
| Lubricating oils | CAS No.: 72623-86-0 | 3-5% | Asp. Tox. 1, H304 | [19] |
| (petroleum), C15-30, | EC No.: 276-737-9 | 3 3 70 | 7.3p. 10X. 1, 11304 | ניטן |
| hydrotreated neutral oil- | 270 737 3 | | | |
| based;Baseoil - | | | | |
| unspecified;[A complex | | | | |
| combination of | | | | |
| hydrocarbons obtained | | | | |
| by treating light vacuum | | | | |
| gas oil and heavy vacuum | | | | |
| gas oil with hydrogen in | | | | |
| the presence of a catalyst | | | | |
| in a two stage process | | | | |
| with dewaxing being | | | | |
| carried out between the | | | | |
| two stages. It consists | | | | |
| predominantly of | | | | |
| hydrocarbons having | | | | |
| carbon numbers | | | | |
| predominantly in the | | | | |
| range of C15 through C30 | | | | |
| and produces a finished | | | | |
| oil having a viscosity of | | | | |
| approximately 15cSt at | | | | |
| 40 °C. It contains a | | | | |
| relatively large | | | | |
| proportion of saturated | | | | |
| hydrocabons.] | | | | |
| p-dodecylphenol | CAS No.: 104-43-8 | <0.05% | Skin Corr. 1C, H314 | |
| | D D 1 NU 1 U4-4 3-0 | こうしきしょうがり | 13NIT CULL. TC. F1314 | i |



| EC No.: 203-202-9 | Eye Dam. 1, H318 | |
|-------------------|------------------|--|
| | Repr. 1B, H360 | |

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information: In the case of accident: Contact a doctor or

casualty department – bring the label or this

safety data sheet.

Contact a doctor if in doubt about the injured

person's condition or if the symptoms persist. Never give an unconscious person

water or other drink.

Inhalation: In case of discomfort: bring the person into

fresh air.

Skin contact: Upon irritation: rinse with water. In the event

of continued irritation, seek medical

assistance.

Eve contact: If in eyes: Flush eyes with plenty of water or

salt water (20-30 °C) and continue until irritation stops. Remove contact lenses.

Ingestion: Rinse and flush mouth thoroughly and

consume large quantities of water. In case of

continued discomfort: seek medical

assistance and bring this safety data sheet.

Burns: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed None known.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.



Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters. If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the national poisons emergency services in order to obtain further advice.

Fire fighters should wear appropriate personal protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area. See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Recommended storage material: Always store in containers of the same

material as the original container.

Storage temperature: Tightly closed container

Away from heat.
Protect from sunlight.

Keep in properly labeled containers. Keep out of the reach of children.

Incompatible materials: Oxidizing agents



7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No substances are listed with a permissible exposure limit in the Official Mexican standard NOM-010-STPS-2014

DNEL:

Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]

| Duration: | Route of exposure: | DNEL: | |
|---|--------------------|------------------------|--|
| Long term – Systemic effects - Workers | Dermal | 970 µg/kgbw/day | |
| Long term – Local effects - General population | Inhalation | 1.19 mg/m ³ | |
| Long term – Local effects - Workers | Inhalation | 5.58 mg/m ³ | |
| Long term – Systemic effects - Workers | Inhalation | 2.73 mg/m ³ | |
| Long term – Systemic effects - General population | Oral | 740 µg/kgbw/day | |

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 °C. It contains a relatively large proportion of saturated hydrocabons.]

| Duration: | Route of exposure: | DNEL: | |
|---|--------------------|------------------------|--|
| Long term – Systemic effects - Workers | Dermal | 970 µg/kgbw/day | |
| Long term – Local effects - General population | Inhalation | 1.19 mg/m ³ | |
| Long term – Local effects - Workers | Inhalation | 5.58 mg/m ³ | |
| Long term – Systemic effects - Workers | Inhalation | 2.73 mg/m ³ | |
| Long term – Systemic effects - General population | Oral | 740 µg/kgbw/day | |

PNEC:

Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]

| Route of exposure: | Duration of Exposure: | PNEC: | |
|--------------------|-----------------------|------------|--|
| Predators | | 9.33 mg/kg | |

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy



vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 °C. It contains a relatively large proportion of saturated hydrocabons.]

| Route of exposure: | | Duration of Exposure: | PNEC: | |
|--------------------|-----------|-----------------------|------------|--|
| F | Predators | | 9.33 mg/kg | |

8.2. Exposure controls

Apply general control to prevent unnecessary exposure

General recommendations: Smoking, drinking and consumption of food

is not allowed in the work area.

Exposure scenarios: There are no exposure scenarios

implemented for this product.

Exposure limits: Occupational exposure limits have not been

defined for the substances in this product.

Appropriate technical measures: Apply standard precautions during use of the

product. Avoid inhalation of vapours.

Hygiene measures: Wash hands after use.

Measures to avoid environmental exposure: No specific requirements.

Individual protection measures, such as personal protective equipment

Generally: Use only CE marked protective equipment.

Respiratory Equipment:
No specific requirements

Skin protection:

No specific requirements.

Hand protection:

No specific requirements.

Eve protection:

| Туре | Standards | |
|-----------------------------------|-----------|--|
| Safety glasses with side shields. | EN166 | |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Form: Liquid Colour: Amber

Odour: Petroleum-like

Odour threshold (ppm): Testing not relevant or not possible due to

the nature of the product.

pH: Testing not relevant or not possible due to



the nature of the product.

Density (g/cm³):

Relative density: 8.835
Kinematic viscosity: 56-90

Phase changes

Melting point (°C): Testing not relevant or not possible due to

the nature of the product.

Boiling point (°C): Testing not relevant or not possible due to

the nature of the product.

Vapour pressure: Testing not relevant or not possible due to

the nature of the product.

Relative vapour density: Testing not relevant or not possible due to

the nature of the product.

Decomposition temperature (°C): Testing not relevant or not possible due to

the nature of the product.

Evaporation rate (n-butylacetate = 100):

Data on fire and explosion hazards

Flash point (°C): Testing not relevant or not possible due to

the nature of the product.

Flammability (°C): Not applicable

Auto-ignition temperature (°C): Testing not relevant or not possible due to

the nature of the product.

Explosion limits (% v/v): Testing not relevant or not possible due to

the nature of the product.

Explosive properties: Product does not present an explosion

hazard

Oxidizing properties: Non-oxidising

Solubility

Solubility in water: Insoluble

n-octanol/water coefficient (LogKow): Testing not relevant or not possible due to

the nature of the product.

Solubility in fat (g/L): Testing not relevant or not possible due to

the nature of the product.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.



10.4. Conditions to avoid

Excessive heat

10.5. Incompatible materials

Strong acids Oxidizing agents

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

None known.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No data available.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.



12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Product is not covered by regulations on dangerous waste.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

| | | 14.2 UN proper shipping name | 14.3 Hazard class(es) | | | Other information: |
|------|---|---------------------------------|--------------------------|---|---|--------------------|
| ADR | - | - | - | - | - | - |
| IMDG | - | - | - | - | - | - |
| IATA | - | - | - | - | - | - |

^{*} Packing group

Additional information

Not dangerous goods according to SCT, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application: No special.

Demands for specific education: No specific requirements.

Additional information: Not applicable.

National Inventory of Chemical Substances of Mexico Lubricating oils (petroleum), C15-30,

^{**} Environmental hazards



(INSQ):

hydrotreated neutral oil-based;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating light vacuum gas oil and heavy vacuum gas oil with hydrogen in the presence of a catalyst in a two stage process with dewaxing being carried out between the two stages. It consists predominantly of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil having a viscosity of approximately 15cSt at 40 °C. It contains a relatively large proportion of saturated

hydrocabons.] is listed

No specific requirements.

Official Mexican standard NOM-018-STPS-

2015, Harmonized System for the

identification and communication of hazards

and risks from hazardous chemical substances in the workplace

15.2. Chemical safety assessment

Nο

Sources:

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H304, May be fatal if swallowed and enters airways.

H314, Causes severe skin burns and eye damage.

H318, Causes serious eye damage.

H360, May damage fertility or the unborn child.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

DOF = The national registry of laws

ECOL (SEMARNAT) = Secretariat of the Environment and Natural Resources

EINECS = European Inventory of Existing Commercial chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

INSQ = National Inventory of Chemical Substances of Mexico

LogKoc = Soil adsorption coefficient



LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NOM = Official Mexican standard

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

SCL = Specific concentration limit.

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

STPS = Ministry of Labor and Social Welfare

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VLE-CT = Short-term exposure limit

VLE-P = Ceiling value

VLE-PPT = Time Weighted Average Exposure Limit Value

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

No substances are listed with a permissible exposure limit in the Official Mexican standard NOM-010-STPS-2014

A safety data sheet is not required for this product. This safety data sheet has been created on a voluntary basis to distribute relevant information.

▼ The safety data sheet is validated by

NL

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: MX-en