



Conforms to NOM-018-STPS-2015

## SAFETY DATA SHEET

# Rislone DPF Cleaner

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

*Trade name:* Rislone DPF Cleaner  
*Product no.:* 24744

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

*Relevant identified uses of the substance or mixture:* Additive  
*Uses advised against:* None known.

#### 1.3. Details of the supplier of the safety data sheet

*Company and address:*

**Rislone**  
P.O. Box 187  
Holly, MI 48442 USA  
(810) 603-1321  
www.Rislone.com

*E-mail:* support@rislone.com  
*SDS date:* 29 March 2024  
*SDS Version:* 2.0  
*Date of previous version:* 19 February 2024 (2.0)

#### 1.4. Emergency telephone number

ChemTel Inc.  
(800) 255-3924 (North America)  
+1 (813) 248-0585 (International)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Flam. Liq. 4; H227, Combustible liquid  
Acute Tox. 4; H302, Harmful if swallowed.  
Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.  
Skin Irrit. 3; H316, Causes mild skin irritation  
Acute Tox. 4; H332, Harmful if inhaled.  
Muta. 1B; H340, May cause genetic defects.  
Carc. 1B; H350, May cause cancer.  
STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

#### 2.2. Label elements



Conforms to NOM-018-STPS-2015

*Hazard pictogram(s):*



*Signal word:*

Danger

*Hazard statement(s):*

Combustible liquid (H227)  
Harmful if swallowed or if inhaled.  
(H302+H332)  
May be fatal if swallowed and enters airways.  
(H304)  
Causes mild skin irritation (H316)  
May cause genetic defects. (H340)  
May cause cancer. (H350)  
May cause damage to organs through  
prolonged or repeated exposure. (H373)

*Precautionary statement(s):*

*General:*

If medical advice is needed, have product  
container or label at hand. (P101)  
Keep out of reach of children. (P102)

*Prevention:*

Obtain special instructions before use. (P201)  
Wear eye protection/protective  
gloves/protective clothing. (P280)

*Response:*

IF exposed or concerned: Get medical  
advice/attention. (P308+P313)  
Get medical advice/attention if you feel  
unwell. (P314)

*Storage:*

Store locked up. (P405)

*Disposal:*

Dispose of contents/container in accordance  
with local regulation  
(P501)

*Hazardous substances:*

Distillates (petroleum), hydrotreated light  
paraffinic;Baseoil - unspecified;[A complex  
combination of hydrocarbons obtained by  
treating a petroleum fraction with hydrogen  
in the presence of a catalyst. It consists of  
hydrocarbons having carbon numbers  
predominantly in the range of C15 through  
C30 and produces a finished oil with a  
viscosity of less than 100 SUS at 100 °F (19cSt  
at 40 °C). It contains a relatively large  
proportion of saturated hydrocarbons.]  
p-xylene;m-xylene;xylene;o-xylene  
Solvent naphtha (petroleum), heavy arom.  
ethylbenzene

*Additional labelling:*

Restricted to professional users.

### 2.3. Other hazards

*Additional warnings:*

This mixture/product does not contain any  
substances known to fulfil the criteria for PBT



Conforms to NOM-018-STPS-2015

and vPvB classification.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1. Substances**

Not applicable. This product is a mixture.

**3.2. Mixtures**

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]	CAS No.: 64742-55-8 EC No.: 265-158-7	25-40%	Asp. Tox. 1, H304	[19]
p-xylene;m-xylene;xylene;o-xylene	CAS No.: 1330-20-7 EC No.: 215-535-7	5-10%	Flam. Liq. 3, H226 Acute Tox. 4, H312 Skin Irrit. 2, H315 Acute Tox. 4, H332	
Solvent naphtha (petroleum), heavy arom.	CAS No.: 64742-94-5 EC No.: 265-198-5	1-3%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336	[19]
ethylbenzene	CAS No.: 100-41-4 EC No.: 202-849-4	1-3%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Acute Tox. 4, H332 STOT RE 2, H373	
naphthalene	CAS No.: 91-20-3 EC No.: 202-049-5	<1%	Acute Tox. 4, H302 Carc. 2, H351	



Conforms to NOM-018-STPS-2015

phenol, 2-dodecyl-, branched;phenol, dodecyl-, branched;phenol, 3-dodecyl-, branched;phenol, (tetrapropenyl) derivatives;phenol, 4-dodecyl-, branched	CAS No.: 210555-94-5 EC No.: 640-104-9	<0.25%	Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360	[19]
ethylenediamine;1,2-diaminoethane	CAS No.: 107-15-3 EC No.: 203-468-6	<0.25%	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 3, H311 Skin Corr. 1B, H314 Skin Sens. 1B, H317 Acute Tox. 4, H332 Resp. Sens. 1B, H334	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### *General information:*

In the case of accident: Contact a doctor or casualty department – bring the label or this safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### *Inhalation:*

Upon breathing difficulties or irritation of the respiratory tract: Bring the injured person into fresh air. Make sure the injured person is continuously monitored. Prevent shock by keeping the injured person warm and calm. If breathing ceases, give mouth-to-mouth resuscitation. If unconscious, roll the injured person into recovery position. Call an ambulance.

#### *Skin contact:*

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin



*Eye contact:*

thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

*Ingestion:*

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

*Burns:*

Not applicable.

**4.2. Most important symptoms and effects, both acute and delayed**

Headache, Methaemoglobinaemia (naphthalene)

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

**4.3. Indication of any immediate medical attention and special treatment needed**

IF exposed or concerned:

Get immediate medical advice/attention.

**Information to medics**

Bring this safety data sheet or the label from this product.

**SECTION 5: FIREFIGHTING MEASURES**

**5.1. Extinguishing media**

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

**5.2. Special hazards arising from the substance or mixture**

Combustible liquid

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon



Conforms to NOM-018-STPS-2015

direct exposure contact the national poisons emergency services in order to obtain further advice.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.  
Ensure adequate ventilation, especially in confined areas.  
Avoid inhalation of vapours from spilled material.  
Contaminated areas may be slippery.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.  
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.  
See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Avoid direct contact with the product.  
Avoid contact during pregnancy and while nursing.  
Smoking, drinking and consumption of food is not allowed in the work area.  
See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

<i>Recommended storage material:</i>	Always store in containers of the same material as the original container.
<i>Storage temperature:</i>	Dry, cool and well ventilated
<i>Incompatible materials:</i>	Combustible materials

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

p-xylene;m-xylene;xylene;o-xylene  
Time Weighted Average Exposure Limit Value (VLE-PPT): 150 ppm



Conforms to NOM-018-STPS-2015

Ceiling value (VLE-P): 100 ppm

Annotations:

A4 = Not classified as a human carcinogen

IBE = Biological limit value recommended for the substance.

ethylbenzene

Ceiling value (VLE-P): 20 ppm

Annotations:

A3 = Carcinogenic effect detected in animals. Results of studies relating to the carcinogenicity are not necessarily applicable to humans.

IBE = Biological limit value recommended for the substance.

naphthalene

Time Weighted Average Exposure Limit Value (VLE-PPT): 15 ppm

Ceiling value (VLE-P): 10 ppm

Annotations:

A4 = Not classified as a human carcinogen

PIEL = The ability of the substance to be absorbed through the skin, mucous membranes or eyes in significant quantities, increases the risk from exposure to the substance.

ethylenediamine;1,2-diaminoethane

Ceiling value (VLE-P): 10 ppm

Annotations:

A4 = Not classified as a human carcinogen

PIEL = The ability of the substance to be absorbed through the skin, mucous membranes or eyes in significant quantities, increases the risk from exposure to the substance.

Official Mexican standard NOM-010-STPS-2014, Contaminating chemical agents in the work environment – inspection, evaluation, and control.

**DNEL:**

Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	970 µg/kgbw/day
Long term – Local effects - General population	Inhalation	1.19 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	5.58 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	2.73 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	740 µg/kgbw/day

ethylbenzene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	180 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	442 mg/m <sup>3</sup>



Conforms to NOM-018-STPS-2015

Long term – Systemic effects - General population	Inhalation	15 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	77 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	293 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	1.6 mg/kg bw/day

ethylenediamine;1,2-diaminoethane

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	6.25 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	25 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	110 µg/kgbw/day

naphthalene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	3.57 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	25 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	25 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	25 mg/m <sup>3</sup>

p-xylene;m-xylene;xylene;o-xylene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	125 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	212 mg/kg bw/day
Long term – Local effects - General population	Inhalation	65.3 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	221 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	65.3 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	221 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	260 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	442 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	260 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	442 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	5 mg/kg bw/day

Solvent naphtha (petroleum), heavy arom.

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	280 µg/kgbw/day
Long term – Systemic effects - Workers	Dermal	950 µg/kgbw/day
Long term – Local effects - General population	Inhalation	690 µg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	2.31 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	690 µg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	2.31 mg/m <sup>3</sup>





Conforms to NOM-018-STPS-2015

Short term – Local effects - General population	Inhalation	143.5 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	160.23 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	226 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	384 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	30 µg/kgbw/day
Short term – Systemic effects - General population	Oral	25.6 mg/kg bw/day

**PNEC:**

Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]

Route of exposure:	Duration of Exposure:	PNEC:
Predators		9.33 mg/kg

ethylbenzene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		100 µg/L
Freshwater sediment		13.7 mg/kg
Intermittent release (freshwater)		100 µg/L
Marine water		10-100 µg/L
Marine water sediment		1.37 mg/kg
Predators		20 mg/kg
Sewage treatment plant		9.6 mg/L
Soil		2.68 mg/kg

ethylenediamine;1,2-diaminoethane

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		16 µg/L
Freshwater sediment		7.68 mg/kg
Intermittent release (freshwater)		167 µg/L
Marine water		2 µg/L
Marine water sediment		768 µg/kg
Predators		4.9 mg/kg
Sewage treatment plant		320 µg/L
Soil		4.36 mg/kg

naphthalene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		2.4 µg/L
Freshwater		2.4 µg/L



Conforms to NOM-018-STPS-2015

Freshwater sediment		67.2 µg/kg
Freshwater sediment		67.2 µg/kg
Intermittent release (freshwater)		20 µg/L
Intermittent release (freshwater)		20 µg/L
Marine water		2.4 µg/L
Marine water		2.4 µg/L
Marine water sediment		67.2 µg/kg
Marine water sediment		67.2 µg/kg
Sewage treatment plant		2.9 mg/L
Soil		53.3 µg/kg
Soil		53.3 µg/kg

p-xylene;m-xylene;xylene;o-xylene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		44-327 µg/L
Freshwater sediment		2.52-12.46 mg/kg
Intermittent release (freshwater)		10-327 µg/L
Intermittent release (marine water)		1 µg/L
Marine water		4.4-327 µg/L
Marine water sediment		252-12460 µg/kg
Sewage treatment plant		1.6-6.58 mg/L
Soil		852-2310 µg/kg

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

*General recommendations:*

Smoking, drinking and consumption of food is not allowed in the work area.

*Exposure scenarios:*

There are no exposure scenarios implemented for this product.

*Exposure limits:*

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

*Appropriate technical measures:*

Do not recirculate outlet air that contain the substances.  
The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the product. Avoid inhalation of vapours.



Conforms to NOM-018-STPS-2015

*Hygiene measures:*

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

*Measures to avoid environmental exposure:*

Keep damming materials near the workplace. If possible, collect spillage during work.

**Individual protection measures, such as personal protective equipment**


*Generally:*

Use only CE marked protective equipment.


*Respiratory Equipment:*

No specific requirements


*Skin protection:*

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

*Hand protection:*

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Gloves	-	-	EN374	

*Eye protection:*

Type	Standards	
Safety glasses with side shields.	EN166	

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

<i>Form:</i>	Liquid
<i>Colour:</i>	Amber
<i>Odour:</i>	Petroleum distillates
<i>Odour threshold (ppm):</i>	No data available
<i>pH:</i>	No data available
▼ <i>Density (g/cm<sup>3</sup>):</i>	1
<i>Relative density:</i>	No data available
<i>Kinematic viscosity:</i>	Testing not relevant or not possible due to the nature of the product.

**Phase changes**

<i>Melting point (°C):</i>	No data available
----------------------------	-------------------



Conforms to NOM-018-STPS-2015

<i>Boiling point (°C):</i>	No data available
<i>Vapour pressure:</i>	No data available
<i>Relative vapour density:</i>	No data available
<i>Decomposition temperature (°C):</i>	No data available
<i>Evaporation rate (n-butylacetate = 100):</i>	No data available

#### **Data on fire and explosion hazards**

<i>Flash point (°C):</i>	63
<i>Flammability (°C):</i>	No data available
<i>Auto-ignition temperature (°C):</i>	No data available
<i>Explosion limits (% v/v):</i>	No data available
<i>Explosive properties:</i>	No data available
<i>Oxidizing properties:</i>	No data available

#### **Solubility**

<i>Solubility in water:</i>	No data available
<i>n-octanol/water coefficient (LogKow):</i>	Testing not relevant or not possible due to the nature of the product.
<i>Solubility in fat (g/L):</i>	No data available

#### **9.2. Other information**

▼ <i>Sensitivity to shock:</i>	No
▼ <i>Evaporation rate (n-butylacetate = 100):</i>	No data available

### **SECTION 10: STABILITY AND REACTIVITY**

#### **10.1. Reactivity**

No data available.

#### **10.2. Chemical stability**

The product is stable under the conditions, noted in section 7 "Handling and storage".

#### **10.3. Possibility of hazardous reactions**

None known.

#### **10.4. Conditions to avoid**

Heat, flames, and sparks  
Excessive heat

#### **10.5. Incompatible materials**

Strong acids  
Strong oxidizing agents  
Strong bases

#### **10.6. Hazardous decomposition products**

The product is not degraded when used as specified in section 1.

### **SECTION 11: TOXICOLOGICAL INFORMATION**



Conforms to NOM-018-STPS-2015

## 11.1. Information on toxicological effects

### Acute toxicity

Harmful if swallowed.  
Harmful if inhaled.

### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

### Serious eye damage/irritation

Based on available data, the classification criteria are not met.

### Respiratory sensitisation

Based on available data, the classification criteria are not met.

### Skin sensitisation

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

May cause genetic defects.

### Carcinogenicity

May cause cancer.  
p-xylene;m-xylene;xylene;o-xylene has been classified by IARC as a group 3 carcinogen.

### Reproductive toxicity

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard

May be fatal if swallowed and enters airways.

### Long term effects

Carcinogenic effects: This product contains substances considered or proven to be carcinogenic. The carcinogenic effects may be triggered subsequent to exposure through inhalation, skin contact or ingestion.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

No data available.

### 12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

### 12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.



Conforms to NOM-018-STPS-2015

**12.6. Other adverse effects**  
None known.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

Dispose of contents/container to an approved waste disposal plant.

**Contaminated packing**

Packaging containing residues of the product must be disposed of similarly to the product.

**SECTION 14: TRANSPORT INFORMATION**

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1268	UN1268 PETROLEUM PRODUCTS, N.O.S., COMBUSTIBLE LIQUID, III; NON-BULK PACKAGES ARE EXEMPTED FROM THE PROVISIONS OF 49 CFR IN USA JURISDICTIONS		III	No	See below for additional information.
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

\* Packing group

\*\* Environmental hazards

**▼ Additional information**

Not dangerous goods according to SCT, IATA and IMDG.

**14.6. Special precautions for user**  
Not applicable.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**  
No data available.

**SECTION 15: REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

*Restrictions for application:*

Restricted to professional users.  
People under the age of 18 shall not be exposed to this product.  
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.



Conforms to NOM-018-STPS-2015

*Demands for specific education:*

No specific requirements.

*Additional information:*

Tactile warning.

If this product is sold in retail, it must be delivered with child-resistant fastening.

*National Inventory of Chemical Substances of Mexico (INSQ):*

p-xylene;m-xylene;xylene;o-xylene is listed  
Solvent naphtha (petroleum), heavy arom. is listed

ethylbenzene is listed

naphthalene is listed

ethylenediamine;1,2-diaminoethane is listed

*Sources:*

Federal Regulations on Safety and Health at Work (DOF: 13/11/2014)

Official Mexican standard NOM-018-STPS-2015, Harmonized System for the identification and communication of hazards and risks from hazardous chemical substances in the workplace

## 15.2. Chemical safety assessment

No

## SECTION 16: OTHER INFORMATION

### Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H302, Harmful if swallowed.

H304, May be fatal if swallowed and enters airways.

H311, Toxic in contact with skin.

H312, Harmful in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H332, Harmful if inhaled.

H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H336, May cause drowsiness or dizziness.

H351, Suspected of causing cancer.

H360, May damage fertility or the unborn child.

H373, May cause damage to organs through prolonged or repeated exposure.

### The full text of identified uses as mentioned in section 1

None known.

### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor



Conforms to NOM-018-STPS-2015

---

CAS = Chemical Abstracts Service  
DOF = The national registry of laws  
ECOL (SEMARNAT) = Secretariat of the Environment and Natural Resources  
EINECS = European Inventory of Existing Commercial chemical Substances  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer  
IATA = International Air Transport Association  
IMDG = International Maritime Dangerous Goods  
INSQ = National Inventory of Chemical Substances of Mexico  
LogKoc = Soil adsorption coefficient  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
NOM = Official Mexican standard  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
SCL = Specific concentration limit.  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
STPS = Ministry of Labor and Social Welfare  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VLE-CT = Short-term exposure limit  
VLE-P = Ceiling value  
VLE-PPT = Time Weighted Average Exposure Limit Value  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

#### **Additional information**

The classification of the mixture in regard of health hazards is in accordance with the calculation methods.

#### **▼ The safety data sheet is validated by**

NL

#### **▼ Other**

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: MX-en