

SAFETY DATA SHEET

Rislone Complete Fuel System Cleaner - Left Side

SECTION 1: IDENTIFICATION

1.1. Product identifier

Trade name: Rislone Complete Fuel System Cleaner -

Left Side

Product no.: 34700

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Fuel additive Uses advised against: None known.

1.3. Details of the supplier of the safety data sheet

Company and address: Rislone

P.O. Box 187 Holly, MI 48442

USA

(810) 603-1321 www.Rislone.com

E-mail: support@rislone.com

SDS date: 18 April 2025

SDS Version: 1.0

1.4. Emergency telephone number

ChemTel Inc.

(800) 255-3924 (North America) +1 (813) 248-0585 (International)

SECTION 2: HAZARD(S) IDENTIFICATION

Classified as hazardous according to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272).

2.1. Classification of the substance or mixture

Flam. Liq. 4; H227, Combustible liquid

2.2. Label elements

Hazard pictogram(s): Not applicable.

Signal word: Warning

Hazard statement(s): Combustible liquid (H227)

Precautionary statement(s):

General: Keep out of reach of children. (P102)



Prevention: Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking. (P210)

Response: In case of fire: Use water mist/carbon

dioxide/alcohol-resistant foam to extinguish.

(P370+P378)

Store in a well-ventilated place. Keep cool.

(P403+P235)

Disposal: Dispose of contents/container in accordance

with local regulation

(P501)

Hazardous substances: Does not contain any substances required to

report

Additional labelling: Not applicable.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum),	CAS No.: 64742-55-8	25-40%	Asp. Tox. 1, H304	[19]
hydrotreated light				
paraffinic;Baseoil -				
unspecified;[A complex				
combination of				
hydrocarbons obtained				
by treating a petroleum				
fraction with hydrogen in				
the presence of a				
catalyst. It consists of				
hydrocarbons having				
carbon numbers				
predominantly in the				
range of C15 through C30				
and produces a finished				
oil with a viscosity of less				
than 100 SUS at 100 °F				
(19cSt at 40 °C). It				
contains a relatively large				
proportion of saturated				
hydrocarbons.]				
2-butoxyethanol	CAS No.: 111-76-2	1-3%	Acute Tox. 4, H302	
			Skin Irrit. 2, H315	



	Eye Irrit. 2, H319	
	Acute Tox. 4, H332	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

General information: If breathing is irregular, drowsiness, loss of

consciousness or cramps: Call 911 and give

immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms

persist. Never give an unconscious person

water or other drink.

Inhalation: Upon breathing difficulties or irritation of the

respiratory tract: Bring the person into fresh

air and stay with him/her.

Skin contact: Remove contaminated clothing and shoes

immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents

or thinners.

Eye contact: If in eyes: Flush eyes with water or saline

water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during

transport.

Ingestion: If the person is conscious, rinse the mouth

with water and stay with the person. Never

give the person anything to drink.
In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking

on vomited material.

Burns: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed



None known.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Combustible liquid

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters. If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact a poison centre in order to obtain further advice. See section 1 "Emergency telephone number".

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas. Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste. See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE



7.1. Precautions for safe handling

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material: Always store in containers of the same

material as the original container.

Storage conditions: Tightly closed container

Dry, cool and well ventilated

Incompatible materials: heat, sparks, flame, and other sources of

ignition

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

ALBERTA

2-butoxyethanol

Long term exposure limit (8 hours) (ppm): 20

Long term exposure limit (8 hours) (mg/m³): 97

Annotations:

3 = Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.

p-xylene;m-xylene;xylene;o-xylene

Long term exposure limit (8 hours) (ppm): 100 Long term exposure limit (8 hours) (mg/m³): 434 Short term exposure limit (15 minutes) (ppm): 150 Short term exposure limit (15 minutes) (mg/m³): 651

ethylbenzene

Long term exposure limit (8 hours) (ppm): 100 Long term exposure limit (8 hours) (mg/m³): 434 Short term exposure limit (15 minutes) (ppm): 125 Short term exposure limit (15 minutes) (mg/m³): 543

Occupational Health and Safety Code 2009 Order, Alta Reg 87/2009 (revised in 2018)

BRITISH COLUMBIA

2-butoxyethanol

Time-Weighted Average Limit (TWA): 20 ppm

p-xylene;m-xylene;xylene;o-xylene

Time-Weighted Average Limit (TWA): 100 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 150 ppm

ethylbenzene



Time-Weighted Average Limit (TWA): 20 ppm

OHS Regulation Part 5: Chemical Agents and Biological Agents.

ONTARIO

2-butoxyethanol

Time-Weighted Average Limit (TWA): 20 ppm

p-xylene;m-xylene;xylene;o-xylene

Time-Weighted Average Limit (TWA): 100 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 150 ppm

ethylbenzene

Time-Weighted Average Limit (TWA): 20 ppm

Regulation 833 (Control of Exposure to Biological or Chemical Agents) and Ontario Regulation

490/09 (Designated Substances)

QUEBEC

2-butoxyethanol

Long term exposure limit (8 hours) (ppm): 20

Annotations:

Note 3 = Where the use of these products is permitted.

p-xylene;m-xylene;xylene;o-xylene

Long term exposure limit (8 hours) (ppm): 100 Long term exposure limit (8 hours) (mg/m³): 434

ethylbenzene

Long term exposure limit (8 hours) (ppm): 20

Annotations:

Note 3 = Where the use of these products is permitted.

Regulation respecting occupational health and safety (Chapter S-2.1, r. 13)

SASKATCHEWAN

2-butoxyethanol

Long term exposure limit (8 hours) (ppm): 20

Short term exposure limit (15 minutes) (ppm): 30

p-xylene;m-xylene;xylene;o-xylene

Long term exposure limit (8 hours) (ppm): 100

Short term exposure limit (15 minutes) (ppm): 150

ethylbenzene

Long term exposure limit (8 hours) (ppm): 100

Short term exposure limit (15 minutes) (ppm): 125

Annotations:

T20 = Substance is also included in Table 20 of The Occupational Health and Safety Regulations and subject to Sections 306 and 311

The Occupational Health and Safety Regulations, 2020, Chapter S15.1 Reg 10.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations: Smoking, drinking and consumption of food

is not allowed in the work area.

Exposure scenarios: There are no exposure scenarios

implemented for this product.

Exposure limits: Professional users are subjected to the

Rislone Complete Fuel System Cleaner - Left Side



legally set maximum concentrations for occupational exposure. See occupational

hygiene limit values above.

Appropriate technical measures: The formation of vapours must be kept at a

minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the

product. Avoid inhalation of vapours.

Hygiene measures: In between use of the product and at the end

of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and

face.

Measures to avoid environmental exposure: No specific requirements.

Individual protection measures, such as personal protective equipment

Generally: Use only protective equipment with a

recognized certification mark, e.g. the UL

mark.

Respiratory Equipment:
No specific requirements

Skin protection:

Recommended	Type/Category	Standards	
Wear suitable protective clothing.		Wear suitable protective clothing.	

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Gloves	-	-	EN374	

Eye protection:

No specific requirements.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: Orange

Odour: Petroleum-like
Odour threshold (ppm): No data available.
pH: Not determined



Density (g/cm³):

Relative density: 0.77

Kinematic viscosity: No data available.

Particle characteristics: Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C): No data available

Softening point/range (°F): Does not apply to liquids.

Boiling point (°C):

Vapour pressure:No data availableRelative vapour density:No data available.Decomposition temperature (°C):No data available

Data on fire and explosion hazards

Flash point (°C): 87

Flammability (°C):

Auto-ignition temperature (°C):

Explosion limits (% v/v):

No data available

No data available

Solubility

Solubility in water: Insoluble

*n-octanol/water coefficient (LogKow):*No data available.
Solubility in fat (g/L):
No data available.

9.2. Other information

Evaporation rate (n-butylacetate = 100):

Other physical and chemical parameters:

No data available.

Oxidizing properties:

No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Heat, flames, and sparks

10.5. Incompatible materials

heat, sparks, flame, and other sources of ignition

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.



SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

None known.

Other information

2-butoxyethanol has been classified by IARC as a group 3 carcinogen. p-xylene;m-xylene;cylene;o-xylene has been classified by IARC as a group 3 carcinogen. ethylbenzene has been classified by IARC as a group 2B carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No data available.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.



12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

p-xylene;m-xylene;xylene;o-xylene is listed with EPA Hazardous Waste Number: U239

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

		14.2 UN proper shipping name	14.3 Hazard class(es)	· ·		Other informat ion:
TDG	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

^{*} Packing group

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Canadian lists

NDSL: None of the components are listed

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of

Rislone Complete Fuel System Cleaner - Left Side

^{**} Environmental hazards



hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] 2-butoxyethanol p-xylene;m-xylene;xylene;o-xylene ethylbenzene

15.4. Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

15.5. Demands for specific education

No specific requirements.

Additional information

Not applicable.

15.7. Chemical safety assessment

No

Sources

Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H302, Harmful if swallowed.

H304, May be fatal if swallowed and enters airways.

H315. Causes skin irritation.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ANSI = American National Standards Institute

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

DSL = Domestic Substances List

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HHNOC = Health Hazards Not Otherwise Classified

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

NDSL = Non-domestic substances list

OECD = Organisation for Economic Co-operation and Development



PBT = Persistent, Bioaccumulative and Toxic

PHNOC = Physical Hazards Not Otherwise Classified

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

SCL = A specific concentration limit.

SOR = Statutory Orders and Regulations

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TDG = Transportation of Dangerous Goods

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

WHIMS = Workplace Hazardous Materials Information System

Additional information

Not applicable.

The safety data sheet is validated by

NL

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: CA-en