SAFETY DATA SHEET

Rislone Complete Fuel System Cleaner - Left Side

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: Rislone Complete Fuel System Cleaner -

Left Side

Product no.: 44700

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Fuel additive Uses advised against: None known.

1.3. Details of the supplier of the safety data sheet

Company and address: RISLONE Nordic AB

Rydståvägen 45 S-424 91 OLOFSTORP

Sweden

+46 (0)31 55 50 88

https://www.rislonenordic.com/

Contact person: Support Department E-mail: info@rislonenordic.com

Revision: 25 April 2025

SDS Version: 1.0

1.4. Emergency telephone number

ChemTel Inc.

(800) 255-3924 (North America) +1 (813) 248-0585 (International)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP).

2.2. Label elements

Hazard pictogram(s):Not applicable.Signal word:Not applicable.Hazard statement(s):Not applicable.

Precautionary statement(s):

General: -



Prevention: -

Response: -

Storage: -

Disposal: -

Hazardous substances: Does not contain any substances required to

report

Additional labelling: Not applicable.

2.3. Other hazards

Additional warnings: This mixture/product does not contain any

substances known to fulfil the criteria for PBT

and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU)

2023/707.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum),	CAS No.: 64742-55-8	25-40%	Asp. Tox. 1, H304	[12],
hydrotreated light	EC No.: 265-158-7			[19]
paraffinic;Baseoil -	REACH: 01-2119487077-29-			
unspecified;[A complex	xxxx			
combination of	Index No.: 649-468-00-3			
hydrocarbons obtained				
by treating a petroleum				
fraction with hydrogen in				
the presence of a				
catalyst. It consists of				
hydrocarbons having				
carbon numbers				
predominantly in the				
range of C15 through C30				
and produces a finished				
oil with a viscosity of less				
than 100 SUS at 100 °F				
(19cSt at 40 °C). It				
contains a relatively large				
proportion of saturated				



hydrocarbons.]				
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0 REACH: 01-2119475108-36- XXXX Index No.: 603-014-00-0	1-3%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	[1]
p-xylene;m- xylene;xylene;o-xylene	CAS No.: 1330-20-7 EC No.: 215-535-7 REACH: 01-2119488216-32- XXXX Index No.: 601-022-00-9	<1%	Flam. Liq. 3, H226 Acute Tox. 4, H312 Skin Irrit. 2, H315 Acute Tox. 4, H332	[1]
ethylbenzene	CAS No.: 100-41-4 EC No.: 202-849-4 REACH: 01-2119489370-35- XXXX Index No.: 601-023-00-4	<1%	Asp. Tox. 1, H304 Acute Tox. 4, H332 STOT RE 2, H373 Aquatic Chronic 3, H412	[1]
naphthalene	CAS No.: 91-20-3 EC No.: 202-049-5 REACH: 01-2119561346-37- XXXX Index No.: 601-052-00-2	<0.0001%	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[12] The classification as a carcinogen will not be taken into account as the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method' (CLP, Annex VI, note L).

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information:

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person



water or other drink.

Inhalation: In case of discomfort: bring the person into

fresh air.

Skin contact: Upon irritation: rinse with water. In the event

of continued irritation, seek medical

assistance.

Eye contact: Rinse gently with lukewarm water. Remove

any contact lenses if this is easy to do. Continue rinsing. In case of persistent eye irritation or discomfort: Seek medical help.

Ingestion: Rinse and flush mouth thoroughly and

consume large quantities of water. In case of

continued discomfort: seek medical

assistance and bring this safety data sheet.

Burns: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed Headache, Methaemoglobinaemia (naphthalene)

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters. If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

5.3. Advice for firefighters

No specific requirements.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation, especially in confined areas. Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. Keep unauthorized persons away from the spill



6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Recommended storage material: Always store in containers of the same

material as the original container.

Storage conditions: Tightly closed container

Dry, cool and well ventilated

Incompatible materials: heat, sparks, flame, and other sources of

ignition

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

2-butoxyethanol

Long term exposure limit (8 hours) (mg/m³): 50

Long term exposure limit (8 hours) (ppm): 10

Annotations:

E = The EU has set an indicative limit value and/or remark for the substance.

H = Chemicals that can be absorbed through the skin.

p-xylene;m-xylene;xylene;o-xylene

Long term exposure limit (8 hours) (mg/m³): 108

Long term exposure limit (8 hours) (ppm): 25

Annotations:

E = The EU has set an indicative limit value and/or remark for the substance.

H = Chemicals that can be absorbed through the skin.

ethylbenzene

Long term exposure limit (8 hours) (mg/m³): 20

Long term exposure limit (8 hours) (ppm): 5

Annotations:



E = The EU has set an indicative limit value and/or remark for the substance.

H = Chemicals that can be absorbed through the skin.

K = Carcinogenic substance.

naphthalene

Long term exposure limit (8 hours) (mg/m³): 50 Long term exposure limit (8 hours) (ppm): 10 Annotations:

E = The EU has set an indicative limit value and/or remark for the substance.

Regulations concerning action and limit values for physical and chemical agents in the working environment and classified biological agents (Regulations concerning Action and Limit values) FOR-2011-12-06-1358. Last update: FOR-2024-04-05-581.

DNEL

2-butoxyethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	59 mg/m³
Long term – Systemic effects - Workers	Inhalation	98 mg/m³
Short term – Local effects - General population	Inhalation	147 mg/m³
Short term – Local effects - Workers	Inhalation	246 mg/m³
Short term – Systemic effects - General population	Inhalation	426 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1091 mg/m ³
Long term – Systemic effects - General population	Oral	6.3 mg/kg bw/day
Short term – Systemic effects - General population	Oral	26.7 mg/kg bw/day

Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	970 μg/kg bw/day
Long term – Local effects - General population	Inhalation	1.19 mg/m³
Long term – Local effects - Workers	Inhalation	5.58 mg/m ³
Long term – Systemic effects - Workers	Inhalation	2.73 mg/m ³
Long term – Systemic effects - General population	Oral	740 µg/kg bw/day

ethylbenzene

early is enzerie			
Duration:	Route of exposure:	DNEL:	
Long term – Systemic effects - Workers	Dermal	180 mg/kg bw/day	
Long term – Local effects - Workers	Inhalation	442 mg/m³	
Long term – Systemic effects - General population	Inhalation	15 mg/m ³	



Long term – Systemic effects - Workers	Inhalation	77 mg/m³
Short term – Local effects - Workers	Inhalation	293 mg/m³
Long term – Systemic effects - General population	Oral	1.6 mg/kg bw/day

naphthalene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	3.57 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	25 mg/m³
Long term – Local effects - Workers	Inhalation	25 mg/m³
Long term – Systemic effects - Workers	Inhalation	25 mg/m³

p-xylene;m-xylene;xylene;o-xylene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	125 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	212 mg/kg bw/day
Long term – Local effects - General population	Inhalation	65.3 mg/m ³
Long term – Local effects - Workers	Inhalation	221 mg/m³
Long term – Systemic effects - General population	Inhalation	65.3 mg/m ³
Long term – Systemic effects - Workers	Inhalation	221 mg/m³
Short term – Local effects - General population	Inhalation	260 mg/m ³
Short term – Local effects - Workers	Inhalation	442 mg/m³
Short term – Systemic effects - General population	Inhalation	260 mg/m³
Short term – Systemic effects - Workers	Inhalation	442 mg/m³
Long term – Systemic effects - General population	Oral	5 mg/kg bw/day

PNEC

2-butoxyethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		8.8 mg/L
Freshwater sediment		34.6 mg/kg
Intermittent release (freshwater)		26.4 mg/L
Marine water		880 μg/L
Marine water sediment		3.46 mg/kg
Predators		20 mg/kg
Sewage treatment plant		463 mg/L
Soil		2.33 mg/kg

Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100



°F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]

Route of exposure:	Duration of Exposure:	PNEC:
Predators		9.33 mg/kg

ethylbenzene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		100 μg/L
Freshwater sediment		13.7 mg/kg
Intermittent release (freshwater)		100 μg/L
Marine water		10-100 μg/L
Marine water sediment		1.37 mg/kg
Predators		20 mg/kg
Sewage treatment plant		9.6 mg/L
Soil		2.68 mg/kg

naphthalene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		2.4 μg/L
Freshwater		2.4 μg/L
Freshwater sediment		67.2 μg/kg
Freshwater sediment		67.2 μg/kg
Intermittent release (freshwater)		20 μg/L
Intermittent release (freshwater)		20 μg/L
Marine water		2.4 μg/L
Marine water		2.4 μg/L
Marine water sediment		67.2 μg/kg
Marine water sediment		67.2 μg/kg
Sewage treatment plant		2.9 mg/L
Soil		53.3 μg/kg
Soil		53.3 μg/kg

p-xylene;m-xylene;xylene;o-xylene

Route of exposure:	Duration of Exposure:	PNEC:	
Freshwater		44-327 μg/L	
Freshwater sediment		2.52-12.46 mg/kg	
Intermittent release (freshwater)		10-327 μg/L	
Intermittent release (marine water)		1 μg/L	
Marine water		4.4-327 μg/L	
Marine water sediment		252-12460 µg/kg	
Sewage treatment plant		1.6-6.58 mg/L	
Soil		852-2310 µg/kg	



8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations: Smoking, drinking and consumption of food

is not allowed in the work area.

Exposure scenarios: There are no exposure scenarios

implemented for this product.

Exposure limits: Professional users are subjected to the

legally set maximum concentrations for occupational exposure. See occupational

hygiene limit values above.

Appropriate technical measures: The formation of vapours must be kept at a

minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the

product. Avoid inhalation of vapours.

Hygiene measures: Wash hands after use.

Measures to avoid environmental exposure: No specific requirements.

Individual protection measures, such as personal protective equipment

Generally: Use only CE marked protective equipment.

Respiratory Equipment:
No specific requirements

Skin protection:

Recommended	Type/Category	Standards	
Wear suitable	Wear suitable protective	Wear suitable protective	
protective clothing.	clothing.	clothing.	

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Gloves	-	-	EN374	

Eye protection:

No specific requirements.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: Orange

Odour / Odour threshold: Petroleum-like



pH: Not determined

Density (g/cm³):

Relative density: 0.77

Kinematic viscosity: No data available.

Particle characteristics: Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C):

No data available

Softening point/range (°C): Does not apply to liquids.

Boiling point (°C):

Vapour pressure:No data availableRelative vapour density:No data available.Decomposition temperature (°C):No data available

Data on fire and explosion hazards

Flash point (°C): 87

Flammability (°C):

Auto-ignition temperature (°C):

Lower and upper explosion limit (% v/v):

No data available

No data available

Solubility

Solubility in water: Insoluble

*n-octanol/water coefficient (LogKow):*No data available.
Solubility in fat (g/L):
No data available.

9.2. Other information

Evaporation rate (n-butylacetate = 100): No data available
Other physical and chemical parameters: No data available.
Oxidizing properties: No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Heat, flames, and sparks

10.5. Incompatible materials

heat, sparks, flame, and other sources of ignition

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be



produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

None known.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

2-butoxyethanol has been classified by IARC as a group 3 carcinogen. p-xylene;m-xylene;xylene;o-xylene has been classified by IARC as a group 3 carcinogen. ethylbenzene has been classified by IARC as a group 2B carcinogen. naphthalene has been classified by IARC as a group 2B carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Based on available data, the classification criteria are not met.



12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Disposal to the sewer is discouraged.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code: Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)		Env**	Other informat ion:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION



15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application: Pregnant women and women breastfeeding

must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate

exposure, must be considered.

Demands for specific education:

No specific requirements.

SEVESO - Categories / dangerous substances: Not applicable.

REACH, Annex XVII: p-xylene;m-xylene;xylene;o-xylene is subject

to REACH restrictions (entry 40).

Additional information: Not applicable.

Sources: Act no. 62 of 17th June 2005 relating to

working environment, working hours and employment protection, etc. (Working

Environment Act).

Commission Regulation (EU) No 1357/2014 of

18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the

European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures

(CLP).

Regulation (EC) No 1907/2006 of the

European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.

H302, Harmful if swallowed.

H304, May be fatal if swallowed and enters airways.

H312, Harmful in contact with skin.

H315, Causes skin irritation.

H319, Causes serious eye irritation.

H332, Harmful if inhaled.

H351, Suspected of causing cancer.

H373, May cause damage to organs through prolonged or repeated exposure.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H412, Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms



ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

Not applicable.

The safety data sheet is validated by

NL

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.



It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification. Country-language: NO-en