



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

## SAFETY DATA SHEET

# Rislone Gas Fuel System Cleaner

### SECTION 1: IDENTIFICATION

#### 1.1. Product identifier

*Trade name:* Rislone Gas Fuel System Cleaner  
*▼ Product no.:* 4700

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

*Relevant identified uses of the substance or mixture:* Fuel additive

*Uses advised against :* None known.

#### 1.3. Details of the supplier of the safety data sheet

*Company and address:* **Rislone**  
P.O. Box 187  
Holly, MI 48442  
USA  
(810) 603-1321  
www.Rislone.com

*E-mail:* support@rislone.com  
*SDS date:* 20 November 2025  
*SDS Version:* 3.0  
*Date of previous version:* 26 August 2025 (2.0)

#### 1.4. Emergency telephone number

ChemTel Inc.  
(800) 255-3924 (North America)  
+1 (813) 248-0585 (International)

### SECTION 2: HAZARD(S) IDENTIFICATION

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### 2.1. ▼ Classification of the substance or mixture

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

#### 2.2. Label elements



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

Hazard pictogram(s):



Signal word:

Danger

▼ Hazard statement(s):

May be fatal if swallowed and enters airways. (H304)

Precautionary statement(s):

General:

If medical advice is needed, have product container or label at hand. (P101)  
Keep out of reach of children. (P102)

▼ Prevention:

Not applicable.

▼ Response:

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)  
Do NOT induce vomiting. (P331)

▼ Storage:

Store locked up. (P405)

Disposal:

Dispose of contents/container in accordance with local regulation. (P501)

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substances

Not applicable. This product is a mixture.

#### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at	CAS No.: 64742-55-8	25-40%	Asp. Tox. 1, H304	[19]



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

40 °C). It contains a relatively large proportion of saturated hydrocarbons.]				
Cyclohexyldimethylamine	CAS No.: 98-94-2	<0.25%	Flam. Liq. 3, H226 Acute Tox. 3, H301 Acute Tox. 3, H311 Skin Corr. 1B, H314 Eye Dam. 1, H318 Acute Tox. 3, H331	

Where the concentration of an ingredient is expressed as a range the exact concentration has been withheld as a trade secret.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

**Other information**

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

**SECTION 4: FIRST-AID MEASURES**

**4.1. Description of first aid measures**

*General information:*

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

*Inhalation:*

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

*Skin contact:*

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

*Eye contact:*

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes.



*Ingestion:*

Remove contact lenses. Seek medical assistance and continue flushing during transport.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

*Burns:*

Not applicable.

**4.2. Most important symptoms and effects, both acute and delayed**

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

**4.3. Indication of any immediate medical attention and special treatment needed**

IF exposed or concerned:

Get immediate medical advice/attention.

**Information to medics**

Bring this safety data sheet or the label from this product.

**SECTION 5: FIRE-FIGHTING MEASURES**

**5.1. Extinguishing media**

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

**5.2. ▼ Special hazards arising from the substance or mixture**

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the Poison Help Line on 1-800-222-1222 (24/7) in order to obtain further advice.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid direct contact with spilled substances.



Ensure adequate ventilation, especially in confined areas.  
Contaminated areas may be slippery.

**6.2. Environmental precautions**

Avoid discharge to lakes, streams, sewers, etc.  
Keep unauthorized persons away from the spill

**6.3. ▼ Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

**6.4. Reference to other sections**

See section 13 "Disposal considerations" on handling of waste.  
See section 8 "Exposure controls/personal protection" for protective measures.

**SECTION 7: HANDLING AND STORAGE**

**7.1. Precautions for safe handling**

Avoid direct contact with the product.  
Smoking, drinking and consumption of food is not allowed in the work area.  
See section 8 "Exposure controls/personal protection" for information on personal protection.

**7.2. Conditions for safe storage, including any incompatibilities**

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

*Recommended storage material:*

Always store in containers of the same material as the original container.

*Storage conditions:*

Cool, dry conditions in well sealed receptacles  
Avoid storage near extreme heat, ignition sources or open flame  
Keep in properly labeled containers.  
Store locked up.

*Incompatible materials:*

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

**7.3. Specific end use(s)**

This product should only be used for applications quoted in section 1.2.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

2-butoxyethanol



Long term exposure limit (OSHA Table Z-1) (mg/m<sup>3</sup>): 240  
Long term exposure limit (OSHA Table Z-1) (ppm): 50  
Long term exposure limit (ACGIH TLV) (ppm): 20

p-xylene;m-xylene;xylene;o-xylene  
Short term exposure limit (STEL) (ACGIH TLV) (ppm): 150  
Short term exposure limit (STEL) (NIOSH REL) (ppm): 150  
Long term exposure limit (OSHA Table Z-1) (mg/m<sup>3</sup>): 435  
Long term exposure limit (OSHA Table Z-1) (ppm): 100  
Long term exposure limit (ACGIH TLV) (ppm): 100

Part 1910 - Occupational Safety and Health Standards (29 CFR 1910.1000 TABLE Z-1 - Limits for Air Contaminants)

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

*General recommendations:*

Smoking, drinking and consumption of food is not allowed in the work area.

*Exposure scenarios:*

There are no exposure scenarios implemented for this product.

*Exposure limits:*

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

*Appropriate technical measures:*

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

*Hygiene measures:*

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

*Measures to avoid environmental exposure:*

Keep damming materials near the workplace. If possible, collect spillage during work.

## Individual protection measures, such as personal protective equipment



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

*Generally:*

Use only protective equipment with a recognized certification mark, e.g. the UL mark.

*Respiratory Equipment:*

No specific requirements.

*Skin protection:*

Recommended	Type/Category	Standards	
Wear suitable protective clothing.	Wear suitable protective clothing.	Wear suitable protective clothing.	

*Hand protection:*

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Gloves	-	-	EN374	

*Eye protection:*

Type	Standards	
Tight sealing safety goggles	Tight sealing safety goggles	

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Color:</i>	Orange
<i>Odor:</i>	Petroleum-like
<i>Odor threshold (ppm):</i>	No data available.
<i>pH:</i>	No data available.
<i>Density (g/cm<sup>3</sup>):</i>	No data available.
	-
<i>Relative density:</i>	0.77
<i>Kinematic viscosity:</i>	No data available.
▼ <i>Dynamic viscosity:</i>	1.4 mm <sup>2</sup> /s
<i>Particle characteristics:</i>	Does not apply to liquids.

### Phase changes

<i>Melting point/freezing point (°F):</i>	No data available
<i>Softening point/range (°F):</i>	Does not apply to liquids.
<i>Boiling point (°F):</i>	199



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

<i>Boiling point (°C):</i>	93
<i>Vapor pressure:</i>	No data available
<i>Relative vapor density:</i>	No data available.
<i>Decomposition temperature (°F):</i>	No data available

#### **Data on fire and explosion hazards**

<i>Flash point (°F):</i>	183-189
<i>Flash point (°C):</i>	84-87
<i>Flammability (°F):</i>	No data available
<i>Auto-ignition temperature (°F):</i>	No data available
<i>Explosion limits (% v/v):</i>	No data available.

#### **Solubility**

<i>Solubility in water:</i>	Insoluble
<i>n-octanol/water coefficient (LogKow):</i>	No data available.
<i>Solubility in fat (g/L):</i>	No data available.

#### **9.2. Other information**

<i>Evaporation rate (n-butylacetate = 100):</i>	No data available
<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	No data available.

### **SECTION 10: STABILITY AND REACTIVITY**

#### **10.1. Reactivity**

No data available.

#### **10.2. Chemical stability**

The product is stable under the conditions, noted in section 7 "Handling and storage".

#### **10.3. Possibility of hazardous reactions, including those associated with foreseeable emergencies**

None known.

#### **10.4. Conditions to avoid**

Heat, flames, and sparks

#### **10.5. Incompatible materials**

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### **10.6. Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### **SECTION 11: TOXICOLOGICAL INFORMATION**



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

---

### 11.1. Information on toxicological effects

#### ▼ Acute toxicity

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Skin corrosion/irritation

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Serious eye damage/irritation

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Respiratory sensitisation

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Skin sensitisation

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Germ cell mutagenicity

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Carcinogenicity

Based on available data for the mixture, the classification criteria are not met.

#### ▼ Reproductive toxicity

Based on available data for the mixture, the classification criteria are not met.

#### ▼ STOT-single exposure

Based on available data for the mixture, the classification criteria are not met.

#### ▼ STOT-repeated exposure

Based on available data for the mixture, the classification criteria are not met.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

#### Long term effects

None known.

#### Other information

2-butoxyethanol has been classified by IARC as a group 3 carcinogen.

p-xylene;m-xylene;xylene;o-xylene has been classified by IARC as a group 3 carcinogen.

---

## SECTION 12: ECOLOGICAL INFORMATION

---

### 12.1. ▼ Toxicity

Based on available data for the mixture, the classification criteria are not met.

### 12.2. ▼ Persistence and degradability

Based on available data for the mixture, the classification criteria are not met.

### 12.3. ▼ Bioaccumulative potential

Based on available data for the mixture, the classification criteria are not met.

### 12.4. Mobility in soil

No data available.



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

**12.5. Results of PBT and vPvB assessment**

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

**12.6. Other adverse effects**

None known.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**RCRA Hazardous waste ("P" and "U" list) (40 CFR 261)**

p-xylene;m-xylene;xylene;o-xylene is listed with EPA Hazardous Waste Number: U239

**Specific labelling**

**Contaminated packing**

Packaging containing residues of the product must be disposed of similarly to the product.

**SECTION 14: TRANSPORT INFORMATION**

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
DOT	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

\* Packing group

\*\* Environmental hazards

**Additional information**

Not dangerous goods according to DOT, IATA and IMDG.

**14.6. Special precautions for user**

Not applicable.

**14.7. Transport in bulk according to IMO instruments**

No data available.

**SECTION 15: REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.2. U.S. Federal regulations**

*TSCA (the non-confidential portion):*

Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen



in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] is listed

2-butoxyethanol is listed

p-xylene;m-xylene;xylene;o-xylene is listed

1,2,4-trimethylbenzene is listed

mesitylene;1,3,5-trimethylbenzene is listed

Cyclohexyldimethylamine is listed

*Clean Air Act:*

p-xylene;m-xylene;xylene;o-xylene is regulated as a hazardous air pollutant (HAPS)

*EPCRA Section 302:*

None of the components are listed

*EPCRA Section 304:*

None of the components are listed

*EPCRA section 313:*

p-xylene;m-xylene;xylene;o-xylene is listed

1,2,4-trimethylbenzene is listed

*CERCLA:*

p-xylene;m-xylene;xylene;o-xylene is regulated with a Reportable Quantity (RQ) of: 100 pounds

*Hazardous chemical inventory reporting:*

This product is subject to Tier II reporting.

## **State regulations**

*California / Prop. 65:*

None of the components are listed

*Massachusetts / Right To Know Act:*

Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] is listed

2-butoxyethanol is listed

p-xylene;m-xylene;xylene;o-xylene is listed

1,2,4-trimethylbenzene is listed

mesitylene;1,3,5-trimethylbenzene is listed

*New Jersey / Right To Know Act:*

2-butoxyethanol / Substance number: 0275



2-butoxyethanol is on the Special Health Hazard Substance List

—  
p-xylene;m-xylene;xylene;o-xylene /  
Substance number: 2014

p-xylene;m-xylene;xylene;o-xylene is on the Special Health Hazard Substance List

—  
1,2,4-trimethylbenzene / Substance number: 2716

—  
Cyclohexyldimethylamine / Substance number: 0749

Cyclohexyldimethylamine is on the Special Health Hazard Substance List

*New York / Right To Know Act:*

—  
2-butoxyethanol is listed  
2-butoxyethanol is regulated with a Treshold Reporting Quantity (TRQ) of: 10 pounds

—  
p-xylene;m-xylene;xylene;o-xylene is listed  
p-xylene;m-xylene;xylene;o-xylene is regulated with a Reportable Quantity (RQ) of: 1000 pounds

p-xylene;m-xylene;xylene;o-xylene is regulated with a Treshold Reporting Quantity (TRQ) of: 0 pounds

—  
1,2,4-trimethylbenzene is listed  
1,2,4-trimethylbenzene is regulated with a Treshold Reporting Quantity (TRQ) of: 100 pounds

—  
mesitylene;1,3,5-trimethylbenzene is listed  
mesitylene;1,3,5-trimethylbenzene is regulated with a Treshold Reporting Quantity (TRQ) of: 100 pounds

—  
Cyclohexyldimethylamine is listed  
Cyclohexyldimethylamine is regulated with a Treshold Reporting Quantity (TRQ) of: 100 pounds

*Pennsylvania / Right To Know Act:*

—  
2-butoxyethanol is listed  
—



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

p-xylene;m-xylene;xylene;o-xylene is listed  
p-xylene;m-xylene;xylene;o-xylene is  
hazardous to the environment (E)

—  
1,2,4-trimethylbenzene is listed  
1,2,4-trimethylbenzene is hazardous to the  
environment (E)

—

#### **15.4. Restrictions for application**

No special.

#### **15.5. Demands for specific education**

No specific requirements.

#### **▼ 15.6. Additional information**

Not applicable.

#### **15.7. Chemical safety assessment**

No

#### **15.8. Sources**

OSHA Hazard Communication Standard (29 CFR 1910.1200)

## **SECTION 16: OTHER INFORMATION**

### **Full text of H-phrases as mentioned in section 3**

H226, Flammable liquid and vapour.

H301, Toxic if swallowed.

H304, May be fatal if swallowed and enters airways.

H311, Toxic in contact with skin.

H314, Causes severe skin burns and eye damage.

H318, Causes serious eye damage.

H331, Toxic if inhaled.

### **The full text of identified uses as mentioned in section 1**

None known.

### **Abbreviations and acronyms**

ACGIH = American Conference of Governmental Industrial Hygienists

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response Compensation and Liability Act

DOT = Department of Transportation

EINECS = European Inventory of Existing Commercial chemical Substances



Conforms to OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200 / revised 2024)

---

EPCRA = Emergency Planning and Community Right-To-Know Act  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
HCIS = Hazardous Chemical Information System  
HNOC = Hazards Not Otherwise Classified  
IARC = International Agency for Research on Cancer  
IATA = International Air Transport Association  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
NFPA = National Fire Protection Association  
NIOSH = National Institute for Occupational Safety and Health  
OECD = Organisation for Economic Co-operation and Development  
OSHA = Occupational Safety and Health Administration  
PBT = Persistent, Bioaccumulative and Toxic  
RCRA = Resource Conservation and Recovery Act  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SARA = Superfund Amendments and Reauthorization Act  
SCL = A specific concentration limit.  
STEL = Short-term exposure limits  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TSCA = The Toxic Substances Control Act  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

### **Additional information**

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by HCS (29 CFR 1910.1200).

### **The safety data sheet is validated by**

NL

### **Other**

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: US-en