



Conforms to SANS 11014:2010 – South Africa

SAFETY DATA SHEET

Rislone Diesel Fuel System Treatment

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product identifier

<i>Trade name:</i>	Rislone Diesel Fuel System Treatment
<i>Product no.:</i>	44740

Relevant identified uses of the substance or mixture and uses advised against

<i>Relevant identified uses of the substance or mixture:</i>	Fuel additive
<i>Uses advised against :</i>	None known.

Details of the supplier of the safety data sheet

<i>Company and address:</i>	Rislone P.O. Box 187 Holly, MI 48442 USA (810) 603-1321 www.Rislone.com
-----------------------------	---

Importer:

<i>E-mail:</i>	support@rislone.com
<i>SDS date:</i>	27 March 2026
<i>SDS Version:</i>	2.0
<i>Date of previous version:</i>	25 November 2025 (1.0)

Emergency telephone number

ChemTel Inc.
(800) 255-3924 (North America)
+1 (813) 248-0585 (International)

999 / 112 Botswana Emergency Services

SECTION 2: HAZARDS IDENTIFICATION

Classified according to GHS.



Conforms to SANS 11014:2010 – South Africa

▼ Classification of the substance or mixture

Flam. Liq. 4; H227, Combustible liquid

Skin Irrit. 2; H315, Causes skin irritation.

Aquatic Acute 3; H402, Harmful to aquatic life.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

Label elements

▼ Hazard pictogram(s):



Signal word:

Warning

▼ Hazard statement(s):

Combustible liquid (H227)

Causes skin irritation. (H315)

Harmful to aquatic life. (H402)

Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s):

General:

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

▼ Prevention:

Wash hands and exposed skin thoroughly after handling. (P264)

Avoid release to the environment. (P273)

Wear eye protection/protective gloves/protective clothing. (P280)

▼ Response:

In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)

Storage:

Store in a well-ventilated place. Keep cool. (P403+P235)

Disposal:

Dispose of contents/container in accordance with local regulation. (P501)

▼ Hazardous substances:

Contains no substances that need to be listed on the label.

Additional labelling:

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not applicable. This product is a mixture.

▼ Mixtures



Conforms to SANS 11014:2010 – South Africa

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated light	CAS No.: 64742-47-8 EC No.: 265-149-8	60-80%	Asp. Tox. 1, H304	[19]
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0	5-10%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	
Solvent naphtha (petroleum), light arom.	CAS No.: 64742-95-6 EC No.: 265-199-0	3-5%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	[19]
2-ethylhexyl nitrate	CAS No.: 27247-96-7 EC No.: 248-363-6	3-5%	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Aquatic Chronic 2, H411	
Solvent naphtha (petroleum), heavy arom.	CAS No.: 64742-94-5 EC No.: 265-198-5	3-5%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	[19]
1,2,4-trimethylbenzene	CAS No.: 95-63-6 EC No.: 202-436-9	1-3%	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Aquatic Chronic 2, H411	
2,6-di-tert-butylphenol	CAS No.: 128-39-2 EC No.: 204-884-0	<1%	Skin Irrit. 2, H315 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
naphthalene	CAS No.: 91-20-3 EC No.: 202-049-5	<1%	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST AID MEASURES



Conforms to SANS 11014:2010 – South Africa

▼ Description of first aid measures

General information:

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact Tygerberg Poison Information Centre: 861 555 777 (24-hour service)

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

▼ *Skin contact:*

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact:

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes.

Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion:

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns:

Not applicable.

▼ Most important symptoms and effects, both acute and delayed

Headache, Methaemoglobinaemia (naphthalene)

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Indication of any immediate medical attention and special treatment needed



Conforms to SANS 11014:2010 – South Africa

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

Special hazards arising from the substance or mixture

Combustible liquid
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health.
Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Nitrogen oxides (NO_x)
Carbon oxides (CO / CO₂)

Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact Tygerberg Poison Information Centre (tel: 861 555 777) to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES

▼ Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Contaminated areas may be slippery.

Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

Reference to other sections

See section 13 "Disposal considerations" on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.



Conforms to SANS 11014:2010 – South Africa

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material:

Keep only in original packaging.

Storage conditions:

Dry, cool and well ventilated

Incompatible materials:

Oxidizing agents

Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

▼ Control parameters

2-butoxyethanol

Long term exposure limit (8 hours) (ppm): 40 (Max. limit)

naphthalene

Long term exposure limit (8 hours) (ppm): 20

Annotations:

CARC = The substance is carcinogenic based on IARC categorisation including category 1A, 1B and Category 2

SKIN = Danger of cutaneous absorption. Refers to the potential significant contribution to the overall exposure by the cutaneous route including mucous membranes and the eyes by contact with vapours, liquids and solids. Overexposure may also occur following dermal contact with liquids and aerosols, even when airborne exposures at-/or below the OEL.

p-xylene;m-xylene;xylene;o-xylene

Short term exposure limit (15 minutes) (ppm): 300

Long term exposure limit (8 hours) (ppm): 200

Annotations:

SKIN = Danger of cutaneous absorption. Refers to the potential significant contribution to the overall exposure by the cutaneous route including mucous membranes and the eyes by contact with vapours, liquids and solids. Overexposure may also occur following dermal contact with liquids and aerosols, even when airborne exposures at-/or below the OEL.



Conforms to SANS 11014:2010 – South Africa

Trimethylbenzene
Long term exposure limit (8 hours) (ppm): 50

: Regulations for Hazardous Chemical Agents
(2021)



1,2,4-trimethylbenzene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	9512 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	16171 mg/kg bw/day
Long term – Local effects - General population	Inhalation	29.4 mg/m ³
Long term – Local effects - Workers	Inhalation	100 mg/m ³
Long term – Systemic effects - General population	Inhalation	29.4 mg/m ³
Long term – Systemic effects - Workers	Inhalation	100 mg/m ³
Short term – Local effects - General population	Inhalation	29.4 mg/m ³
Short term – Local effects - Workers	Inhalation	100 mg/m ³
Short term – Systemic effects - General population	Inhalation	29.4 mg/m ³
Short term – Systemic effects - Workers	Inhalation	100 mg/m ³
Long term – Systemic effects - General population	Oral	15 mg/kg bw/day

2-butoxyethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	59 mg/m ³
Long term – Systemic effects - Workers	Inhalation	98 mg/m ³
Short term – Local effects - General population	Inhalation	147 mg/m ³
Short term – Local effects - Workers	Inhalation	246 mg/m ³
Short term – Systemic effects - General population	Inhalation	426 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1091 mg/m ³
Long term – Systemic effects - General population	Oral	6.3 mg/kg bw/day
Short term – Systemic effects - General population	Oral	26.7 mg/kg bw/day

2-ethylhexyl nitrate

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Dermal	22 µg/cm ²
Long term – Local effects - Workers	Dermal	44 µg/cm ²
Long term – Systemic effects - General population	Dermal	520 µg/kg bw/day
Long term – Systemic effects - Workers	Dermal	1 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	87 µg/m ³



Conforms to SANS 11014:2010 – South Africa

Long term – Systemic effects - Workers	Inhalation	350 µg/m ³
Long term – Systemic effects - General population	Oral	25 µg/kg bw/day

2,6-di-tert-butylphenol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	6.75 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	11.25 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	20.9 mg/m ³
Long term – Systemic effects - Workers	Inhalation	70.61 mg/m ³
Long term – Systemic effects - General population	Oral	6.75 mg/kg bw/day

naphthalene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	3.57 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	25 mg/m ³
Long term – Local effects - Workers	Inhalation	25 mg/m ³
Long term – Systemic effects - Workers	Inhalation	25 mg/m ³

p-xylene;m-xylene;xylene;o-xylene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	125 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	212 mg/kg bw/day
Long term – Local effects - General population	Inhalation	65.3 mg/m ³
Long term – Local effects - Workers	Inhalation	221 mg/m ³
Long term – Systemic effects - General population	Inhalation	65.3 mg/m ³
Long term – Systemic effects - Workers	Inhalation	221 mg/m ³
Short term – Local effects - General population	Inhalation	260 mg/m ³
Short term – Local effects - Workers	Inhalation	442 mg/m ³
Short term – Systemic effects - General population	Inhalation	260 mg/m ³
Short term – Systemic effects - Workers	Inhalation	442 mg/m ³
Long term – Systemic effects - General population	Oral	2.5 mg/kg bw/day

Solvent naphtha (petroleum), heavy arom.

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	1.64 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	7.7 mg/kg bw/day
Long term – Local effects - General population	Inhalation	690 µg/m ³
Long term – Local effects - Workers	Inhalation	2.31 mg/m ³
Long term – Systemic effects - General population	Inhalation	10.66 mg/m ³

Long term – Systemic effects - Workers	Inhalation	50 mg/m ³
Short term – Local effects - General population	Inhalation	143.5 mg/m ³
Short term – Local effects - Workers	Inhalation	250 mg/m ³
Short term – Systemic effects - General population	Inhalation	226 mg/m ³
Short term – Systemic effects - Workers	Inhalation	384 mg/m ³
Long term – Systemic effects - General population	Oral	5 mg/kg bw/day
Short term – Systemic effects - General population	Oral	25.6 mg/kg bw/day

Solvent naphtha (petroleum), light arom.

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	178.57 mg/m ³
Long term – Local effects - Workers	Inhalation	837.5 mg/m ³
Long term – Systemic effects - General population	Inhalation	410 µg/m ³
Long term – Systemic effects - Workers	Inhalation	1.9 mg/m ³
Short term – Local effects - General population	Inhalation	640 mg/m ³
Short term – Local effects - Workers	Inhalation	1,066.67 mg/m ³
Short term – Systemic effects - General population	Inhalation	1,152 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1,286.4 mg/m ³

▼ PNEC

1,2,4-trimethylbenzene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		120 µg/L
Freshwater sediment		13.56 mg/kg
Intermittent release (freshwater)		120 µg/L
Marine water		120 µg/L
Marine water sediment		13.56 mg/kg
Sewage treatment plant		2.41 mg/L
Soil		2.34 mg/kg

2-butoxyethanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		8.8 mg/L
Freshwater sediment		34.6 mg/kg
Intermittent release (freshwater)		26.4 mg/L
Marine water		880 µg/L
Marine water sediment		3.46 mg/kg
Predators		20 mg/kg



Conforms to SANS 11014:2010 – South Africa

Sewage treatment plant		463 mg/L
Soil		2.33 mg/kg

2-ethylhexyl nitrate

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		830 ng/L
Freshwater sediment		470 µg/kg
Intermittent release (freshwater)		8.3 µg/L
Intermittent release (marine water)		830 ng/L
Marine water		83 ng/L
Marine water sediment		47 µg/kg
Sewage treatment plant		10 mg/L
Soil		93.5 µg/kg

2,6-di-tert-butylphenol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		700 ng/L
Freshwater sediment		317 µg/kg
Intermittent release (freshwater)		4.5 µg/L
Marine water		70 ng/L
Marine water sediment		31.7 µg/kg
Predators		60 mg/kg
Sewage treatment plant		10 mg/L
Soil		697 µg/kg

naphthalene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		2.4 µg/L
Freshwater		2.4 µg/L
Freshwater sediment		67.2 µg/kg
Freshwater sediment		67.2 µg/kg
Intermittent release (freshwater)		20 µg/L
Intermittent release (freshwater)		20 µg/L
Marine water		2.4 µg/L
Marine water		2.4 µg/L
Marine water sediment		67.2 µg/kg
Marine water sediment		67.2 µg/kg
Sewage treatment plant		2.9 mg/L



Conforms to SANS 11014:2010 – South Africa

Soil		53.3 µg/kg
Soil		53.3 µg/kg

p-xylene;m-xylene;xylene;o-xylene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0.044 mg/L
Freshwater sediment		2.52 mg/kg
Intermittent release (freshwater)		0.01 mg/L
Intermittent release (marine water)		0.001 mg/L
Marine water		0.004 mg/L
Marine water sediment		0.252 mg/kg
Sewage treatment plant		1.6 mg/L
Soil		0.852 mg/kg

Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations:

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios:

There are no exposure scenarios implemented for this product.

Exposure limits:

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures:

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

▼ *Hygiene measures:*

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure:

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally:

Use only CE marked protective equipment.

Respiratory Equipment:

Work situation	Type	Class	Colour	Standards	
In case of inadequate ventilation	Combination filter AXP1		Brown/White	EN14387, EN143	

Skin protection:

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection:

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
When there is risk of splash- / intermittent exposure	Cotton/Nitril	-	> 240	EN374-2, EN16523-1, EN388	

Eye protection:

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

<i>Form:</i>	Liquid
▼ <i>Colour:</i>	Green, Yellow
<i>Odour:</i>	Petroleum-like
<i>Odour threshold (ppm):</i>	No data available.
<i>pH:</i>	Not determined
<i>Density (g/cm³):</i>	-
<i>Relative density:</i>	0.80-0.83
<i>Kinematic viscosity:</i>	Not determined

Particle characteristics

Does not apply to liquids.

Phase changes

<i>Melting point (°C):</i>	Not determined
----------------------------	----------------



Conforms to SANS 11014:2010 – South Africa

<i>Boiling point (°C):</i>	92
<i>Vapour pressure:</i>	Not determined
<i>Relative vapour density:</i>	No data available.
<i>Decomposition temperature (°C):</i>	No data available.
<i>Evaporation rate (n-butylacetate = 100):</i>	Not determined

Data on fire and explosion hazards

<i>Flash point (°C):</i>	62
<i>Flammability (°C):</i>	Not applicable
<i>Auto-ignition temperature (°C):</i>	215
<i>Explosion limits (% v/v):</i>	Not applicable

Solubility

<i>Solubility in water:</i>	Insoluble
<i>n-octanol/water coefficient (LogKow):</i>	No data available.
<i>Solubility in fat (g/L):</i>	No data available.

Other information

<i>Evaporation rate (n-butylacetate = 100):</i>	Not determined
<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	No data available.

SECTION 10: STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

Possibility of hazardous reactions

None known.

Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.
Heat, flames, and sparks

Incompatible materials

Oxidizing agents

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION



Conforms to SANS 11014:2010 – South Africa

Information on toxicological effects

▼ Acute toxicity

Based on available data, the classification criteria are not met.

▼ Skin corrosion/irritation

Causes skin irritation.

▼ Serious eye damage/irritation

Based on available data, the classification criteria are not met.

▼ Respiratory sensitisation

Based on available data, the classification criteria are not met.

▼ Skin sensitisation

Based on available data, the classification criteria are not met.

▼ Germ cell mutagenicity

Based on available data, the classification criteria are not met.

▼ Carcinogenicity

Based on available data, the classification criteria are not met.

▼ Reproductive toxicity

Based on available data, the classification criteria are not met.

▼ STOT-single exposure

Based on available data, the classification criteria are not met.

▼ STOT-repeated exposure

Based on available data, the classification criteria are not met.

▼ Aspiration hazard

Based on available data, the classification criteria are not met.

▼ Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

2-butoxyethanol has been classified by IARC as a group 3 carcinogen.

naphthalene has been classified by IARC as a group 2B carcinogen.

p-xylene;m-xylene;xylene;o-xylene has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Harmful to aquatic life with long lasting effects.

▼ Persistence and degradability

Based on available data, the classification criteria are not met.

▼ Bioaccumulative potential



Conforms to SANS 11014:2010 – South Africa

Based on available data, the classification criteria are not met.

Mobility in soil

No data available.

Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Dispose of contents/container to an approved waste disposal plant.

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR/ADN/RID	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Transport hazard class: 9 Label: 9 Classification code: M6 	III	No	Limited quantities: 5 L Tunnel restriction code: (-) See below for additional information.
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

▼ Additional information

These substances when carried in single or combination packaging's containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of ADR/ADN/RID/IMDG/IATA provided the packaging's meet the general provisions of 4.1.1.1, 4.1.1.2, 4.1.1.4 - 4.1.1.8 (ADR, IMDG) / 5.0.2.4.1, 5.0.2.6.1.1, 5.0.2.8 (IATA).

-



Conforms to SANS 11014:2010 – South Africa

ADR/ADN/RID / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

Not dangerous goods according to SABS Code 0228.

Special precautions for user

Not applicable.

Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application:

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education:

No specific requirements.

Additional information:

Not applicable.

Sources:

National Environmental Management:
Waste Act 2008 (Act no. 59 of 2008)
Waste Classification and Management
Regulations
Minimum Requirements for the Handling,
Classification and Disposal of Hazardous
Waste (MRHW)
SANS 10234 : 1.01ED 2008 GLOBALLY
HARMONIZED SYSTEM OF CLASSIFICATION
AND LABELLING OF CHEMICALS (GHS)

Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

▼ Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.

H302, Harmful if swallowed.

H304, May be fatal if swallowed and enters airways.

H312, Harmful in contact with skin.

H315, Causes skin irritation.



H319, Causes serious eye irritation.
H332, Harmful if inhaled.
H335, May cause respiratory irritation.
H336, May cause drowsiness or dizziness.
H351, Suspected of causing cancer.
H400, Very toxic to aquatic life.
H410, Very toxic to aquatic life with long lasting effects.
H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CERCLA = Comprehensive Environmental Response Compensation and Liability Act
DOT = Department of Transportation
EINECS = European Inventory of Existing Commercial chemical Substances
EPCRA = Emergency Planning and Community Right-To-Know Act
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
HCIS = Hazardous Chemical Information System
HNOC = Hazards Not Otherwise Classified
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogKow = logarithm of the n-octanol/water coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NFPA = National Fire Protection Association
NIOSH = National Institute for Occupational Safety and Health
OECD = Organisation for Economic Co-operation and Development
OSHA = Occupational Safety and Health Administration
PBT = Persistent, Bioaccumulative and Toxic
RCRA = Resource Conservation and Recovery Act
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SARA = Superfund Amendments and Reauthorization Act
SCL = A specific concentration limit.
STEL = Short-term exposure limits
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure



Conforms to SANS 11014:2010 – South Africa

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

▼ Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by SANS 10234

The classification of the mixture in regard of environmental hazards are in accordance with the calculation methods given by SANS 10234

The safety data sheet is validated by

NL

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: ZA-en