



Conforms to SANS 11014:2010 – South Africa

SAFETY DATA SHEET

Rislone Super Coolant

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name: Rislone Super Coolant
Product no.: 41300

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Coolant/Anti-freeze
For private use
Uses advised against : None known.

Details of the supplier of the safety data sheet

Company and address: **Rislone**
P.O. Box 187
Holly, MI 48442
USA
(810) 603-1321
www.Rislone.com

Distributor: **Keizin Automotive**
Unit B6, Glen Murray Ind. Park
PO Box 201728, Durban North, 4016
South Africa

E-mail: support@rislone.com

SDS date: 05 February 2026

SDS Version: 1.0

Emergency telephone number

ChemTel Inc.
(800) 255-3924 (North America)
+1 (813) 248-0585 (International)
Keizin Automotive Ltd
27 (31) 569 2221

SECTION 2: HAZARDS IDENTIFICATION

Classified according to GHS.

Classification of the substance or mixture



Conforms to SANS 11014:2010 – South Africa

Eye Dam. 1; H318, Causes serious eye damage.
Aquatic Acute 3; H402, Harmful to aquatic life.
Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

Label elements

Hazard pictogram(s):



Signal word:

Danger

Hazard statement(s):

Causes serious eye damage. (H318)
Harmful to aquatic life. (H402)
Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s):

General:

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

Prevention:

Avoid release to the environment. (P273)
Wear protective gloves/protective clothing/eye protection/face protection. (P280)

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. (P305+P351+P338)
Immediately call a POISON CENTER/doctor. (P310)

Storage:

Not applicable.

Disposal:

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances:

Potassium 2-ethylhexanoate
Sodium benzothiazol-2-yl sulphide
Poly(oxy-1,2-ethanediyl), α -[(1,1,3,3-tetramethylbutyl)phenyl]- ω -hydroxy-

Additional labelling:

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not applicable. This product is a mixture.

Mixtures



Conforms to SANS 11014:2010 – South Africa

Product/substance	Identifiers	% w/w	Classification	Note
Potassium 2-ethylhexanoate	CAS No.: 3164-85-0 EC No.: 221-625-7	3-5%	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 1B, H360D	
Sodium benzothiazol-2-yl sulphide	CAS No.: 2492-26-4 EC No.: 219-660-8	<1%	Met. Corr. 1, H290 Skin Corr. 1C, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
Poly(oxy-1,2-ethanediyl), α-[(1,1,3,3-tetramethylbutyl)phenyl] -ω-hydroxy-	CAS No.: 9036-19-5 EC No.: 618-541-1	<1%	Acute Tox. 4, H302 Eye Dam. 1, H318 Aquatic Chronic 3, H412	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

-

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General information:

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact Tygerberg Poison Information Centre: 861 555 777 (24-hour service)
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact:

IF ON SKIN: Wash with plenty of water and soap.
If skin irritation occurs: Get medical advice/attention.

Eye contact:

If in eyes: Flush eyes with plenty of water or saline solution (20-30 °C) for at least 30 minutes and continue until irritation stops.



Conforms to SANS 11014:2010 – South Africa

Ingestion:

Remove contact lenses. Make sure you flush under the upper and lower eyelids. Seek medical assistance immediately and continue flushing during transport.

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns:

Not applicable.

Most important symptoms and effects, both acute and delayed

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media

Not applicable.

Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health.

Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

Some metal oxides

Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact Tygerberg Poison Information Centre (tel: 861 555 777) to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES



Conforms to SANS 11014:2010 – South Africa

Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.
Contaminated areas may be slippery.

Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material:

Always store in containers of the same material as the original container.

Storage conditions:

Cool, dry conditions in well sealed receptacles

Incompatible materials:

Strong acids

Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Control parameters

No substances are listed with an occupational exposure limit in The Hazardous Chemical Substances Regulations



Conforms to SANS 11014:2010 – South Africa

Potassium 2-ethylhexanoate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	1.19 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	2.38 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	4.14 mg/m ³
Long term – Systemic effects - Workers	Inhalation	16.79 mg/m ³
Long term – Systemic effects - General population	Oral	1.19 mg/kg bw/day

Sodium benzothiazol-2-yl sulphide

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	1.5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	2.8 mg/kg bw/day
Long term – Local effects - General population	Inhalation	1 mg/m ³
Long term – Local effects - Workers	Inhalation	1 mg/m ³
Long term – Systemic effects - General population	Inhalation	2.5 mg/m ³
Long term – Systemic effects - Workers	Inhalation	10 mg/m ³
Short term – Local effects - Workers	Inhalation	1 mg/m ³
Long term – Systemic effects - General population	Oral	1.5 mg/kg bw/day

PNEC

Potassium 2-ethylhexanoate

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		360 µg/L
Freshwater sediment		6.37 mg/kg
Intermittent release (freshwater)		493 µg/L
Marine water		36 µg/L
Marine water sediment		637 µg/kg
Sewage treatment plant		85.4 mg/L
Soil		1.06 mg/kg

Sodium benzothiazol-2-yl sulphide

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		4.1 µg/L
Freshwater sediment		147 µg/kg
Intermittent release (freshwater)		5 µg/L
Marine water		410 ng/L
Marine water sediment		14.7 µg/kg
Sewage treatment plant		300 µg/L
Soil		27 µg/kg

Exposure controls

Apply general control to prevent unnecessary exposure

General recommendations:

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios:

There are no exposure scenarios implemented for this product.

Exposure limits:

Occupational exposure limits have not been defined for the substances in this product.

Appropriate technical measures:

Ensure that eyewash stations and safety showers are located within easy reach. Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures:

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure:

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally:

Take off contaminated clothing and wash it before reuse.
Use only CE marked protective equipment.

Respiratory Equipment:

No specific requirements.

Skin protection:

Recommended	Type/Category	Standards	
Protective work clothing	Protective work clothing		

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Gloves	-	-	EN374	

Eye protection:

Type	Standards	
Safety glasses	EN ISO 16321-1	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

<i>Form:</i>	Liquid
<i>Colour:</i>	Green
<i>Odour:</i>	None
<i>Odour threshold (ppm):</i>	No data available.
<i>pH:</i>	Slightly alkaline
<i>Density (g/cm³):</i>	0.972-1.032
<i>Kinematic viscosity:</i>	Not determined

Particle characteristics

Does not apply to liquids.

Phase changes

<i>Melting point (°C):</i>	Not applicable
<i>Boiling point (°C):</i>	100
<i>Vapour pressure:</i>	Not determined
<i>Relative vapour density:</i>	Not determined
<i>Decomposition temperature (°C):</i>	Not determined
<i>Evaporation rate (n-butylacetate = 100):</i>	

Data on fire and explosion hazards

<i>Flash point (°C):</i>	Not applicable
<i>Flammability (°C):</i>	The material is not combustible.
<i>Auto-ignition temperature (°C):</i>	Not determined
<i>Explosion limits (% v/v):</i>	Not determined

Solubility

<i>Solubility in water:</i>	Soluble
<i>n-octanol/water coefficient (LogKow):</i>	No data available.
<i>Solubility in fat (g/L):</i>	No data available.

Other information

<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	Non-oxidizing



Conforms to SANS 11014:2010 – South Africa

SECTION 10: STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

Possibility of hazardous reactions

None known.

Conditions to avoid

Avoid acids

Incompatible materials

Strong acids

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity

Based on available data for the mixture, the classification criteria are not met.

Skin corrosion/irritation

Based on available data for the mixture, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory sensitisation

Based on available data for the mixture, the classification criteria are not met.

Skin sensitisation

Based on available data for the mixture, the classification criteria are not met.

Germ cell mutagenicity

Based on available data for the mixture, the classification criteria are not met.

Carcinogenicity

Based on available data for the mixture, the classification criteria are not met.

Reproductive toxicity

Based on available data for the mixture, the classification criteria are not met.

STOT-single exposure

Based on available data for the mixture, the classification criteria are not met.

STOT-repeated exposure

Based on available data for the mixture, the classification criteria are not met.



Conforms to SANS 11014:2010 – South Africa

Aspiration hazard

Based on available data for the mixture, the classification criteria are not met.

Long term effects

The product contains substances that cause serious eye damage. Contact with these substances can cause irreversible effects on the eye / serious eye damage.

Other information

None known.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Harmful to aquatic life with long lasting effects.

Persistence and degradability

Based on available data for the mixture, the classification criteria are not met.

Bioaccumulative potential

Based on available data for the mixture, the classification criteria are not met.

Mobility in soil

No data available.

Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods**Specific labelling****Contaminated packing**

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION



Conforms to SANS 11014:2010 – South Africa

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
ADR/ADN/ RID	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR/ADN/RID, IATA and IMDG.

Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.

-

Special precautions for user

Not applicable.

Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application:

No special.

Demands for specific education:

No specific requirements.

Additional information:

Not applicable.

Sources:

National Environmental Management:
Waste Act 2008 (Act no. 59 of 2008)
Waste Classification and Management
Regulations
Minimum Requirements for the Handling,
Classification and Disposal of Hazardous
Waste (MRHW)
SANS 10234 : 1.01ED 2008 GLOBALLY
HARMONIZED SYSTEM OF CLASSIFICATION
AND LABELLING OF CHEMICALS (GHS)

Chemical safety assessment

No

SECTION 16: OTHER INFORMATION



Full text of H-phrases as mentioned in section 3

H290, May be corrosive to metals.
H302, Harmful if swallowed.
H314, Causes severe skin burns and eye damage.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H318, Causes serious eye damage.
H360D, May damage the unborn child.
H400, Very toxic to aquatic life.
H410, Very toxic to aquatic life with long lasting effects.
H412, Harmful to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CERCLA = Comprehensive Environmental Response Compensation and Liability Act
DOT = Department of Transportation
EINECS = European Inventory of Existing Commercial chemical Substances
EPCRA = Emergency Planning and Community Right-To-Know Act
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
HCIS = Hazardous Chemical Information System
HNOC = Hazards Not Otherwise Classified
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NFPA = National Fire Protection Association
NIOSH = National Institute for Occupational Safety and Health
OECD = Organisation for Economic Co-operation and Development
OSHA = Occupational Safety and Health Administration
PBT = Persistent, Bioaccumulative and Toxic
RCRA = Resource Conservation and Recovery Act
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SARA = Superfund Amendments and Reauthorization Act
SCL = A specific concentration limit.



Conforms to SANS 11014:2010 – South Africa

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by SANS 10234

The classification of the mixture in regard of environmental hazards are in accordance with the calculation methods given by SANS 10234

The safety data sheet is validated by

NL

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: ZA-en