



Conforms to SANS 11014:2010 – South Africa

SAFETY DATA SHEET

Rislone Gas Fuel System Cleaner

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product identifier

<i>Trade name:</i>	Rislone Gas Fuel System Cleaner
<i>Product no.:</i>	44700

Relevant identified uses of the substance or mixture and uses advised against

<i>Relevant identified uses of the substance or mixture:</i>	Fuel additive
<i>Uses advised against :</i>	None known.

Details of the supplier of the safety data sheet

<i>Company and address:</i>	Rislone P.O. Box 187 Holly, MI 48442 USA (810) 603-1321 www.Rislone.com
-----------------------------	---

Importer:

<i>E-mail:</i>	support@rislone.com
<i>SDS date:</i>	04 June 2026
<i>SDS Version:</i>	2.0
<i>Date of previous version:</i>	10 February 2026 (1.0)

Emergency telephone number

ChemTel Inc.
(800) 255-3924 (North America)
+1 (813) 248-0585 (International)

999 / 112 (Eswatini Emergency Services)

SECTION 2: HAZARDS IDENTIFICATION

Classified according to GHS.



Conforms to SANS 11014:2010 – South Africa

▼ Classification of the substance or mixture

Flam. Liq. 4; H227, Combustible liquid

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Label elements

Hazard pictogram(s):



Signal word:

Danger

▼ *Hazard statement(s):*

Combustible liquid (H227)

May be fatal if swallowed and enters airways. (H304)

Precautionary statement(s):

General:

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

▼ *Prevention:*

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

▼ *Response:*

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)
Do NOT induce vomiting. (P331)
In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)

Storage:

Store locked up. (P405)

Disposal:

Dispose of contents/container in accordance with local regulation. (P501)

▼ *Hazardous substances:*

Distillates (petroleum), hydrotreated light paraffinic

Additional labelling:

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not applicable. This product is a mixture.

▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated light	CAS No.: 64742-55-8 EC No.: 265-158-7	25-40%	Asp. Tox. 1, H304	[19]



Conforms to SANS 11014:2010 – South Africa

paraffinic				
------------	--	--	--	--

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General information:

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact Tygerberg Poison Information Centre: 861 555 777 (24-hour service)

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact:

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact:

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion:

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical



Conforms to SANS 11014:2010 – South Africa

pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns:

Not applicable.

Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

▼ Special hazards arising from the substance or mixture

Combustible liquid
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health.
Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact Tygerberg Poison Information Centre (tel: 861 555 777) to obtain further advice.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Contaminated areas may be slippery.

Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.
Keep unauthorized persons away from the spill

Methods and material for containment and cleaning up



Conforms to SANS 11014:2010 – South Africa

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material:

Always store in containers of the same material as the original container.

Storage conditions:

Cool, dry conditions in well sealed receptacles

Avoid storage near extreme heat, ignition sources or open flame

Keep in properly labeled containers.

Store locked up.

Incompatible materials:

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

▼ Control parameters

2-butoxyethanol

Long term exposure limit (8 hours) (ppm): 40 (Max. limit)

p-xylene;m-xylene;xylene;o-xylene

Short term exposure limit (15 minutes) (ppm): 300

Long term exposure limit (8 hours) (ppm): 200

Annotations:



Conforms to SANS 11014:2010 – South Africa

SKIN = Danger of cutaneous absorption. Refers to the potential significant contribution to the overall exposure by the cutaneous route including mucous membranes and the eyes by contact with vapours, liquids and solids. Overexposure may also occur following dermal contact with liquids and aerosols, even when airborne exposures at-/or below the OEL.

ethylbenzene

Long term exposure limit (8 hours) (ppm): 40

Annotations:

CARC = The substance is carcinogenic based on IARC categorisation including category 1A, 1B and Category 2

SKIN = Danger of cutaneous absorption. Refers to the potential significant contribution to the overall exposure by the cutaneous route including mucous membranes and the eyes by contact with vapours, liquids and solids. Overexposure may also occur following dermal contact with liquids and aerosols, even when airborne exposures at-/or below the OEL.

: Regulations for Hazardous Chemical Agents (2021)



2-butoxyethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	59 mg/m ³
Long term – Systemic effects - Workers	Inhalation	98 mg/m ³
Short term – Local effects - General population	Inhalation	147 mg/m ³
Short term – Local effects - Workers	Inhalation	246 mg/m ³
Short term – Systemic effects - General population	Inhalation	426 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1,091 mg/m ³
Long term – Systemic effects - General population	Oral	6.3 mg/kg bw/day
Short term – Systemic effects - General population	Oral	26.7 mg/kg bw/day

Distillates (petroleum), hydrotreated light paraffinic

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	0.97 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	5.58 mg/m ³
Long term – Systemic effects - Workers	Inhalation	2.73 mg/m ³
Long term – Systemic effects - General population	Oral	0.74 mg/kg bw/day

ethylbenzene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	180 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	442 mg/m ³



Conforms to SANS 11014:2010 – South Africa

Long term – Systemic effects - General population	Inhalation	15 mg/m ³
Long term – Systemic effects - Workers	Inhalation	77 mg/m ³
Short term – Local effects - Workers	Inhalation	293 mg/m ³
Long term – Systemic effects - General population	Oral	1.6 mg/kg bw/day

p-xylene;m-xylene;xylene;o-xylene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	125 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	212 mg/kg bw/day
Long term – Local effects - General population	Inhalation	65.3 mg/m ³
Long term – Local effects - Workers	Inhalation	221 mg/m ³
Long term – Systemic effects - General population	Inhalation	65.3 mg/m ³
Long term – Systemic effects - Workers	Inhalation	221 mg/m ³
Short term – Local effects - General population	Inhalation	260 mg/m ³
Short term – Local effects - Workers	Inhalation	442 mg/m ³
Short term – Systemic effects - General population	Inhalation	260 mg/m ³
Short term – Systemic effects - Workers	Inhalation	442 mg/m ³
Long term – Systemic effects - General population	Oral	2.5 mg/kg bw/day

▼ PNEC

2-butoxyethanol

Route of exposure:	Duration of Exposure:	PNEC:
Sewage treatment plant		66 mg/L

Distillates (petroleum), hydrotreated light paraffinic

Route of exposure:	Duration of Exposure:	PNEC:
Predators		9.33 mg/kg

ethylbenzene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0.1 mg/L
Freshwater sediment		13.7 mg/kg
Intermittent release (freshwater)		0.1 mg/L
Marine water		0.01 mg/L
Marine water sediment		1.37 mg/kg
Predators		0.02 g/kg
Sewage treatment plant		9.6 mg/L
Soil		2.68 mg/kg

p-xylene;m-xylene;xylene;o-xylene



Conforms to SANS 11014:2010 – South Africa

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0.044 mg/L
Freshwater sediment		2.52 mg/kg
Intermittent release (freshwater)		0.01 mg/L
Intermittent release (marine water)		0.001 mg/L
Marine water		0.004 mg/L
Marine water sediment		0.252 mg/kg
Sewage treatment plant		1.6 mg/L
Soil		0.852 mg/kg

Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations:

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios:

There are no exposure scenarios implemented for this product.

Exposure limits:

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures:

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures:

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure:

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally:

Use only CE marked protective equipment.

Respiratory Equipment:

No specific requirements.

Skin protection:

Recommended	Type/Category	Standards	
Wear suitable protective clothing.	Wear suitable protective clothing.	Wear suitable protective clothing.	

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Gloves	-	-	EN374	

Eye protection:

Type	Standards	
Tight sealing safety goggles	Tight sealing safety goggles	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

<i>Form:</i>	Liquid
<i>Colour:</i>	Orange
<i>Odour:</i>	Petroleum-like
<i>Odour threshold (ppm):</i>	No data available.
<i>pH:</i>	No data available.
<i>Density (g/cm³):</i>	-
<i>Relative density:</i>	0.77
<i>Kinematic viscosity:</i>	No data available.
▼ <i>Dynamic viscosity:</i>	1.4 mm ² /s (40 °C)

Particle characteristics

Does not apply to liquids.

Phase changes

<i>Melting point (°C):</i>	No data available
<i>Boiling point (°C):</i>	93
<i>Vapour pressure:</i>	No data available
<i>Relative vapour density:</i>	No data available.
<i>Decomposition temperature (°C):</i>	No data available
<i>Evaporation rate (n-butylacetate = 100):</i>	No data available



Conforms to SANS 11014:2010 – South Africa

Data on fire and explosion hazards

<i>Flash point (°C):</i>	84-87
<i>Flammability (°C):</i>	No data available
<i>Auto-ignition temperature (°C):</i>	No data available
<i>Explosion limits (% v/v):</i>	No data available.

Solubility

<i>Solubility in water:</i>	Insoluble
<i>n-octanol/water coefficient (LogKow):</i>	No data available.
<i>Solubility in fat (g/L):</i>	No data available.

Other information

<i>Evaporation rate (n-butylacetate = 100):</i>	No data available
<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	No data available.

SECTION 10: STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

Possibility of hazardous reactions

None known.

Conditions to avoid

Heat, flames, and sparks

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation



Conforms to SANS 11014:2010 – South Africa

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Long term effects

None known.

Other information

2-butoxyethanol has been classified by IARC as a group 3.

p-xylene;m-xylene;xylene;o-xylene has been classified by IARC as a group 3.

ethylbenzene has been classified by IARC as a group 2B.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Based on available data, the classification criteria are not met.

Persistence and degradability

Based on available data, the classification criteria are not met.

Bioaccumulative potential

Based on available data, the classification criteria are not met.

Mobility in soil

No data available.

Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

Other adverse effects

None known.



Conforms to SANS 11014:2010 – South Africa

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Product is not covered by regulations on dangerous waste.

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR/A DN/RI D	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to SABS Code 0228.

Special precautions for user

Not applicable.

Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application:

No special.

Demands for specific education:

No specific requirements.

Additional information:

Not applicable.

Sources:

National Environmental Management:
Waste Act 2008 (Act no. 59 of 2008)
Waste Classification and Management
Regulations
Minimum Requirements for the Handling,
Classification and Disposal of Hazardous
Waste (MRHW)



Conforms to SANS 11014:2010 – South Africa

SANS 10234 : 1.01ED 2008 GLOBALLY
HARMONIZED SYSTEM OF CLASSIFICATION
AND LABELLING OF CHEMICALS (GHS)

Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

▼ Full text of H-phrases as mentioned in section 3

H304, May be fatal if swallowed and enters airways.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response Compensation and Liability Act

DOT = Department of Transportation

EINECS = European Inventory of Existing Commercial chemical Substances

EPCRA = Emergency Planning and Community Right-To-Know Act

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

HCIS = Hazardous Chemical Information System

HNOC = Hazards Not Otherwise Classified

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogKow = logarithm of the n-octanol/water coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NFPA = National Fire Protection Association

NIOSH = National Institute for Occupational Safety and Health

OECD = Organisation for Economic Co-operation and Development

OSHA = Occupational Safety and Health Administration

PBT = Persistent, Bioaccumulative and Toxic

RCRA = Resource Conservation and Recovery Act

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SARA = Superfund Amendments and Reauthorization Act

SCL = A specific concentration limit.



Conforms to SANS 11014:2010 – South Africa

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TSCA = The Toxic Substances Control Act

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by SANS 10234

The safety data sheet is validated by

NL

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: ZA-en