



According to JIS Z 7253

## SAFETY DATA SHEET

# Rislone CAT Complete

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

*Trade name:* Rislone CAT Complete  
*Product no.:* 4720, 44720

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

*Relevant identified uses of the substance or mixture:* Fuel additive  
*Uses advised against:* None known.

#### 1.3. Details of the supplier of the safety data sheet

*Company and address:* **Rislone**  
P.O. Box 187  
Holly, MI 48442  
USA  
(810) 603-1321  
www.Rislone.com

*Importer:* **MOBILY Corp.**  
5655 Takayama-cho, Ikoma-shi, Nara 630-0101, Japan

Japan  
+81 0743-21-0005  
info@n-mobily.com

*E-mail:*  
*SDS date:* 12 June 2025  
*SDS Version:* 1.0

#### 1.4. Emergency telephone number

ChemTel Inc.  
(800) 255-3924 (North America)  
+1 (813) 248-0585 (International)

### SECTION 2: HAZARDS IDENTIFICATION

Classified according to JIS Z 7252.

#### 2.1. Classification of the substance or mixture

Flam. Liq. 4; H227, Combustible liquid  
Aquatic Acute 3; H402, Harmful to aquatic life.  
Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.



According to JIS Z 7253

## 2.2. Label elements

<i>Hazard pictogram(s):</i>	Not applicable.
<i>Signal word:</i>	Warning
<i>Hazard statement(s):</i>	Combustible liquid (H227) Harmful to aquatic life. (H402) Harmful to aquatic life with long lasting effects. (H412)
<i>Precautionary statement(s):</i>	
<i>General:</i>	Keep out of reach of children. (P102)
<i>Prevention:</i>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210) Avoid release to the environment. (P273)
<i>Response:</i>	In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)
<i>Storage:</i>	Store in a well-ventilated place. Keep cool. (P403+P235)
<i>Disposal:</i>	Dispose of contents/container in accordance with local regulation (P501)
<i>Hazardous substances:</i>	2-butoxyethanol p-xylene;m-xylene;xylene;o-xylene Tricarbonyl(methylcyclopentadienyl)manganese
<i>Additional labelling:</i>	Not applicable.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having	CAS No.: 64742-55-8 EC No.: 265-158-7	25-40%	Asp. Tox. 1, H304	[19]



According to JIS Z 7253

carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]				
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0	5-10%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	
Distillates (petroleum), hydrotreated light;Kerosine - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150 °C to 290 °C (302 °F to 554 °F).]	CAS No.: 64742-47-8 EC No.: 265-149-8	3-5%	Asp. Tox. 1, H304	[19]
Paraffins (petroleum), normal C5-20	CAS No.: 64771-72-8 EC No.: 265-233-4	3-5%	Asp. Tox. 1, H304	[19]
p-xylene;m-xylene;xylene;o-xylene	CAS No.: 1330-20-7 EC No.: 215-535-7	1-3%	Flam. Liq. 3, H226 Acute Tox. 4, H312 Skin Irrit. 2, H315 Acute Tox. 4, H332	
Solvent naphtha (petroleum), light arom.	CAS No.: 64742-95-6 EC No.: 265-199-0	1-3%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	[19]



According to JIS Z 7253

Tricarbonyl(methylcyclopentadienyl)manganese	CAS No.: 12108-13-3 EC No.: 235-166-5	<1%	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 1, H330 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
--	--	-----	--	--

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

### Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### *General information:*

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### *Inhalation:*

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### *Skin contact:*

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

#### *Eye contact:*

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

#### *Ingestion:*

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.



According to JIS Z 7253

*Burns:*

Not applicable.

**4.2. Most important symptoms and effects, both acute and delayed**

None known.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**Information to medics**

Bring this safety data sheet or the label from this product.

---

**SECTION 5: FIREFIGHTING MEASURES**

---

**5.1. Extinguishing media**

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

**5.2. Special hazards arising from the substance or mixture**

Combustible liquid

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact emergency services (119) in order to obtain further advice.

---

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

---

**6.1. Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

**6.2. Environmental precautions**

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

**6.3. Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

**6.4. Reference to other sections**

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

---

**SECTION 7: HANDLING AND STORAGE**

---



According to JIS Z 7253

### 7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

*Recommended storage material:*

Properly labeled containers

*Storage conditions:*

Dry, cool and well ventilated

Tightly closed container

*Incompatible materials:*

heat, sparks, flame, and other sources of ignition

Combustible materials

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

2-butoxyethanol

Ceiling limit (mg/m<sup>3</sup>): 97

Ceiling limit (ppm): 20

Skin = Skin absorption. A significant dose from the view of systemic health effects or absorption of the substance concerned may be absorbed through the skin when the substance is in contact with the skin. OEL are set at conditions under which no skin absorption will take place.

p-xylene;m-xylene;xylene;o-xylene

Long term exposure limit (8 hours) (mg/m<sup>3</sup>):

Long term exposure limit (8 hours) (ppm): 50

ethylbenzene

Long term exposure limit (8 hours) (mg/m<sup>3</sup>):

Long term exposure limit (8 hours) (ppm): 20

Skin = Skin absorption. A significant dose from the view of systemic health effects or absorption of the substance concerned may be absorbed through the skin when the substance is in contact with the skin. OEL are set at conditions under which no skin absorption will take place.

1,2,4-trimethylbenzene

Long term exposure limit (8 hours) (mg/m<sup>3</sup>):

Long term exposure limit (8 hours) (ppm): 25

Mesitylene

Long term exposure limit (8 hours) (mg/m<sup>3</sup>):

Long term exposure limit (8 hours) (ppm): 25

Recommendation of occupational exposure limits (2023 - 2024), The Japan Society for Occupational Health May 10, 2023



According to JIS Z 7253

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

*General recommendations:*

Smoking, drinking and consumption of food is not allowed in the work area.

*Exposure scenarios:*

There are no exposure scenarios implemented for this product.

*Exposure limits:*

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

*Appropriate technical measures:*

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the product. Avoid inhalation of vapours.

*Hygiene measures:*

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

*Measures to avoid environmental exposure:*

Keep damming materials near the workplace. If possible, collect spillage during work.

## Individual protection measures, such as personal protective equipment


*Generally:*

Use only CE marked protective equipment.


*Respiratory Equipment:*

No specific requirements

*Skin protection:*

Recommended	Type/Category	Standards	
Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.	-	-	

*Hand protection:*

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Gloves	-	-	EN374	

*Eye protection:*



According to JIS Z 7253

Type	Standards	
Tight sealing safety goggles	Tight sealing safety goggles	

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<i>Form:</i>	Liquid
<i>Colour:</i>	Brown
<i>Odour:</i>	Petroleum-like
<i>Odour threshold (ppm):</i>	No data available.
<i>pH:</i>	No data available.
<i>Density (g/cm<sup>3</sup>):</i>	-
<i>Relative density:</i>	0.81
<i>Kinematic viscosity:</i>	No data available
<i>Dynamic viscosity:</i>	23.4 mPa.s
<i>Particle characteristics:</i>	Does not apply to liquids.

### Phase changes

<i>Melting point/Freezing point (°C):</i>	No data available
<i>Softening point/range (°C):</i>	Does not apply to liquids.
<i>Boiling point (°C):</i>	No data available
<i>Vapour pressure:</i>	No data available
<i>Relative vapour density:</i>	No data available.
<i>Decomposition temperature (°C):</i>	No data available
<i>Evaporation rate (n-butylacetate = 100):</i>	

### Data on fire and explosion hazards

<i>Flash point (°C):</i>	67
<i>Flammability (°C):</i>	No data available
<i>Auto-ignition temperature (°C):</i>	No data available
<i>Explosion limits (% v/v):</i>	No data available.

### Solubility

<i>Solubility in water:</i>	Insoluble
<i>n-octanol/water coefficient (LogKow):</i>	No data available.
<i>Solubility in fat (g/L):</i>	No data available.

### 9.2. Other information

<i>VOC:</i>	
<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	No data available.



According to JIS Z 7253

---

## SECTION 10: STABILITY AND REACTIVITY

---

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

### 10.3. Possibility of hazardous reactions

None known.

### 10.4. Conditions to avoid

Heat, flames, and sparks

### 10.5. Incompatible materials

heat, sparks, flame, and other sources of ignition  
Combustible materials

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

---

## SECTION 11: TOXICOLOGICAL INFORMATION

---

### 11.1. Information on toxicological effects

#### Acute toxicity

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation

Based on available data, the classification criteria are not met.

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

Based on available data, the classification criteria are not met.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

2-butoxyethanol has been classified by IARC as a group 3 carcinogen.

p-xylene;m-xylene;xylene;o-xylene has been classified by IARC as a group 3 carcinogen.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

Based on available data, the classification criteria are not met.

#### STOT-repeated exposure

Based on available data, the classification criteria are not met.



According to JIS Z 7253

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Long term effects**

None known.

**SECTION 12: ECOLOGICAL INFORMATION**

**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

**12.2. Persistence and degradability**

Based on available data, the classification criteria are not met.

**12.3. Bioaccumulative potential**

Based on available data, the classification criteria are not met.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

**12.6. Other adverse effects**

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Specific labelling**

**Contaminated packing**

Packaging containing residues of the product must be disposed of similarly to the product.

**SECTION 14: TRANSPORT INFORMATION**

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

\* Packing group

\*\* Environmental hazards

**Additional information**



According to JIS Z 7253

Not dangerous goods according to ADR, IATA and IMDG.

Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.

-

**14.6. Special precautions for user**

Not applicable.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

**SECTION 15: REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

*Restrictions for application:*

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

*Demands for specific education:*

No specific requirements.

*Additional information:*

Not applicable.

*List of Existing and New Chemical Substances (ENCS):*

p-xylene;m-xylene;xylene;o-xylene is listed

*Poisonous and Deleterious Substances Control Law (PDSCL):*

None of the components are listed

*Pollutant release and transfer act (PRTR):*

p-xylene;m-xylene;xylene;o-xylene is included in list of Class 1 designated chemical substances  
ethylbenzene is included in list of Class 1 designated chemical substances  
Tricarbonyl(methylcyclopentadienyl)manganese is included in list of Class 1 designated chemical substances  
1,2,4-trimethylbenzene is included in list of Class 1 designated chemical substances  
Mesitylene is included in list of Class 1 designated chemical substances

*Organic Solvent Poisoning Prevention Regulations:*

2-butoxyethanol is included (Type 2)  
p-xylene;m-xylene;xylene;o-xylene is included (Type 2)  
Naphtha (petroleum), hydrotreated heavy;Low boiling point hydrogen treated naphtha;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C6 through



According to JIS Z 7253

Sources:

C13 and boiling in the range of approximately 65°C to 230°C (149°F to 446°F.) is included (Type 3)

Organic Solvent Poisoning Prevention Regulations (The Ministry of Labour Ordinance No. 36, 1972)  
Japanese Industrial Standard Z 7252 – Classification of Chemicals  
Japanese Industrial Standard Z 7253 – Methods of communication - labels, signs in the workplace and Safety Data Sheet (SDS)

## SECTION 16: OTHER INFORMATION

### Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.  
H301, Toxic if swallowed.  
H302, Harmful if swallowed.  
H304, May be fatal if swallowed and enters airways.  
H310, Fatal in contact with skin.  
H312, Harmful in contact with skin.  
H315, Causes skin irritation.  
H319, Causes serious eye irritation.  
H330, Fatal if inhaled.  
H332, Harmful if inhaled.  
H336, May cause drowsiness or dizziness.  
H400, Very toxic to aquatic life.  
H410, Very toxic to aquatic life with long lasting effects.  
H411, Toxic to aquatic life with long lasting effects.

### The full text of identified uses as mentioned in section 1

None known.

### Abbreviations and acronyms

ACGIH = American Conference of Governmental Industrial Hygienists  
ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CERCLA = Comprehensive Environmental Response Compensation and Liability Act  
DOT = Department of Transportation  
EINECS = European Inventory of Existing Commercial chemical Substances  
EPCRA = Emergency Planning and Community Right-To-Know Act  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
HCIS = Hazardous Chemical Information System  
HNOC = Hazards Not Otherwise Classified  
IARC = International Agency for Research on Cancer  
IATA = International Air Transport Association



According to JIS Z 7253

---

IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
NFPA = National Fire Protection Association  
NIOSH = National Institute for Occupational Safety and Health  
OECD = Organisation for Economic Co-operation and Development  
OSHA = Occupational Safety and Health Administration  
PBT = Persistent, Bioaccumulative and Toxic  
RCRA = Resource Conservation and Recovery Act  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SARA = Superfund Amendments and Reauthorization Act  
SCL = A specific concentration limit.  
STEL = Short-term exposure limits  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TSCA = The Toxic Substances Control Act  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

#### **Additional information**

The classification of the mixture in regard of environmental hazards are in accordance with the calculation methods given by JIS Z 7252.

#### **The safety data sheet is validated by**

NL

#### **Other**

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: JP-en