



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

SAFETY DATA SHEET

Rislone Octane Booster

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: Rislone Octane Booster

Product no.: 44747

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Fuel additive

Uses advised against : None known.

1.3. Details of the supplier of the safety data sheet

Company and address: **Rislone**
P.O. Box 187
Holly, MI 48442
USA
(810) 603-1321
www.Rislone.com

▼ *Importer:* **Smits Group Pty Ltd.**
50 Radius Drive
Larapinda
QLD4110
Australia
AUS Telephone 1800 883 888
NZ Telephone 09 274 6871

E-mail: support@rislone.com

SDS date: 06 February 2026

SDS Version: 2.0

Date of previous version: 26 February 2024 (1.0)

1.4. ▼ Emergency telephone number

ChemTel Inc.
(800) 255-3924 (North America)
+1 (813) 248-0585 (International)

911 (Samoa Emergency Services)

SECTION 2: HAZARDS IDENTIFICATION

This material is considered hazardous according to the Work Health and Safety Regulations.

2.1. ▼ Classification of the substance or mixture

Flam. Liq. 4; H227, Combustible liquid

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Skin Irrit. 2; H315, Causes skin irritation.

Eye Irrit. 2; H319, Causes serious eye irritation.

Acute Tox. 3; H331, Toxic if inhaled.

2.2. Label elements

Hazard pictogram(s):



Signal word:

Danger

▼ *Hazard statement(s):*

Combustible liquid (H227)

May be fatal if swallowed and enters airways. (H304)

Causes skin irritation. (H315)

Causes serious eye irritation. (H319)

Toxic if inhaled. (H331)

Precautionary statement(s):

General:

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

▼ *Prevention:*

Avoid breathing mist/vapour. (P261)

Use only outdoors or in a well-ventilated area. (P271)

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. (P304+P340)

Specific treatment (see instructions on this label). (P321)

Storage:

Store locked up. (P405)

▼ *Disposal:*

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances:

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]
2-butoxyethanol
Tricarbonyl(methylcyclopentadienyl)manganese

▼ *Additional labelling:*

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]	CAS No.: 64742-55-8 EC No.: 265-158-7	25-40%	Asp. Tox. 1, H304	[19]
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0	10-15%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

Tricarbonyl(methylcyclopentadienyl)manganese	CAS No.: 12108-13-3 EC No.: 235-166-5	1-3%	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 1, H330	
--	--	------	--	--

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information:

In the case of accident: Contact a doctor or casualty department – bring the label or this safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the injured person into fresh air. Make sure the injured person is continuously monitored. Prevent shock by keeping the injured person warm and calm. If breathing ceases, give mouth-to-mouth resuscitation. If unconscious, roll the injured person into recovery position. Call an ambulance.

Skin contact:

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact:

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower



Ingestion:

eyelids. If irritation continues, contact a doctor. Continue flushing during transport.
IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns:

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:
Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Combustible liquid
In use may form flammable/explosive vapour-air mixture.
Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:
Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure call the NSW Poisons Information Centre on 13 11 26 (Available 24/7) in order to obtain further advice.



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Avoid inhalation of vapours from spilled material.
Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.
Keep unauthorized persons away from the spill

6.3. ▼ Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid direct contact with the product.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. ▼ Conditions for safe storage, including any incompatibilities

Store locked up. A sign warning of toxic materials shall be affixed the room and cupboard containing the product(s).
Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material:

Always store in containers of the same material as the original container.

Storage conditions:

Cool, dry conditions in well sealed receptacles
Away from heat.
Keep in properly labeled containers.
Keep out of the reach of children.
Store locked up.

Incompatible materials:

Strong acids
Strong oxidizing agents



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

Strong bases

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. ▼ Control parameters

2-butoxyethanol

Long term exposure limit (8 hours) (ppm): 20

Long term exposure limit (8 hours) (mg/m³): 96.9

Short term exposure limit (15 minutes) (ppm): 50

Short term exposure limit (15 minutes) (mg/m³): 242

Annotations:

Sk = Absorption through the skin may be a significant source of exposure.

Tricarbonyl(methylcyclopentadienyl)manganese

Long term exposure limit (8 hours) (mg/m³): 0.2

Annotations:

Sk = Absorption through the skin may be a significant source of exposure.

Workplace exposure standards for airborne contaminants (Safe Work Australia). (January 2024)

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations:

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios:

There are no exposure scenarios implemented for this product.

Exposure limits:

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures:

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

Hygiene measures:

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure:

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally:

Use only protective equipment that carries the RCM symbol.

▼ *Respiratory Equipment:*

No specific requirements.

Skin protection:

Recommended	Type/Category	Standards	
Protective work clothing	Protective work clothing		
NA	NA	Long sleeved clothing	

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Gloves	-	-	EN374	

Eye protection:

Type	Standards	
Tight sealing safety goggles	Tight sealing safety goggles	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Form:

Liquid

Colour:

Yellow

Odour:

Petroleum-like

▼ *Odour threshold (ppm):*

No data available.

pH:

Not determined

▼ *Density (g/cm³):*

0.78

Relative density:

0.78

▼ *Kinematic viscosity:*

No data available.

▼ *Particle characteristics:*

Does not apply to liquids.



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

Phase changes

<i>Melting point/Freezing point (°C):</i>	No data available
▼ <i>Softening point/range (°C):</i>	Does not apply to liquids.
▼ <i>Boiling point (°C):</i>	No data available.
<i>Vapour pressure:</i>	No data available
<i>Relative vapour density:</i>	No data available
<i>Decomposition temperature (°C):</i>	No data available

Data on fire and explosion hazards

<i>Flash point (°C):</i>	70
▼ <i>Flammability (°C):</i>	No data available.
▼ <i>Auto-ignition temperature (°C):</i>	No data available.
▼ <i>Explosion limits (% v/v):</i>	No data available.

Solubility

<i>Solubility in water:</i>	Not miscible or difficult to mix
▼ <i>n-octanol/water coefficient (LogKow):</i>	No data available.
▼ <i>Solubility in fat (g/L):</i>	No data available.

9.2. Other information

▼ <i>Evaporation rate (n-butylacetate = 100):</i>	No data available
▼ <i>Other physical and chemical parameters:</i>	No data available.
▼ <i>Oxidizing properties:</i>	No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Heat, flames, and sparks
Excessive heat

10.5. Incompatible materials

Strong acids
Strong oxidizing agents
Strong bases

10.6. ▼ Hazardous decomposition products



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

▼ Acute toxicity

Toxic if inhaled.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

2-butoxyethanol has been classified by IARC as a group 3 carcinogen.

Reproductive toxicity

Based on available data, the classification criteria are not met.

▼ STOT-single exposure

Based on available data, the classification criteria are not met.

▼ STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

SECTION 12: ECOLOGICAL INFORMATION

12.1. ▼ Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Dispose of contents/container to an approved waste disposal plant.

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
ADG	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

▼ Additional information

This product is within scope of the regulations of transport of dangerous goods.
Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.

-

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application:

People under the age of 18 shall not be exposed to this product.
Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education:

No specific requirements.

Control of major hazard facilities:

Not applicable.

Additional information:

Tactile warning.

The Australian Inventory of Industrial Chemicals (AIIC):

If this product is sold in retail, it must be delivered with child-resistant fastening.
Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] is listed
2-butoxyethanol is listed
Tricarbonyl(methylcyclopentadienyl)manganese is listed

Sources:

Model Work Health and Safety Regulations as at 1 January 2021.

15.2. Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H301, Toxic if swallowed.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H310, Fatal in contact with skin.
H315, Causes skin irritation.
H319, Causes serious eye irritation.



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

H330, Fatal if inhaled.

H332, Harmful if inhaled.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ADG = The Australian Code for the Transport of Dangerous Goods by Road & Rail

AICIS = Australian Industrial Chemicals Introduction Scheme

AIIC = Australian Inventory of Industrial Chemicals

AS = Australian Standard

AS/NZS = Australian New Zealand Standard

ATE = Acute Toxicity Estimate

AUH = Hazard statements specific for Australia

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

EINECS = European Inventory of Existing Commercial chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

Hazchem = Hazardous chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

NICNAS = National Industrial Chemicals Notification and Assessment Scheme (replaced by AICIS since 2020)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

RCM = Regulatory Mark of Conformity

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

SCL = A specific concentration limit

STEL = Short-term exposure limits

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

SUSMP = Standard for the Uniform Scheduling of Medicines and Poisons

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

WHS = Work Health and Safety Regulations

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by the Work Health and Safety Regulations.

Refer to AS 1940-2017: The storage and handling of flammable and combustible liquids.



Conforms to Code of Practice - Preparation of safety data sheets for hazardous chemicals, June 2023.

The safety data sheet is validated by

NL

▼ Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: AU-en