



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SAFETY DATA SHEET

Rislone Diesel Fuel System Treatment

SECTION 1: IDENTIFICATION

1.1. Product identifier

▼ *Trade name:* Rislone Diesel Fuel System Treatment
Product no.: 34740

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Fuel additive

Uses advised against : None known.

1.3. Details of the supplier of the safety data sheet

Company and address: **Rislone**
P.O. Box 187
Holly, MI 48442 USA
(810) 603-1321
www.Rislone.com

E-mail: support@rislone.com

SDS date: 27 March 2026

SDS Version: 4.0

Date of previous version: 20 November 2025 (3.0)

1.4. Emergency telephone number

ChemTel Inc.
(800) 255-3924 (North America)
+1 (813) 248-0585 (International)

SECTION 2: HAZARD(S) IDENTIFICATION

Classified as hazardous according to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272).

2.1. ▼ Classification of the substance or mixture

Flam. Liq. 4; H227, Combustible liquid
Skin Irrit. 2; H315, Causes skin irritation.

2.2. Label elements



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

▼ Hazard pictogram(s):



Signal word:

Warning

▼ Hazard statement(s):

Combustible liquid (H227)
Causes skin irritation. (H315)

Precautionary statement(s):

General:

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

▼ Prevention:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Wash hands and exposed skin thoroughly after handling. (P264)
Wear eye protection/protective gloves/protective clothing. (P280)

▼ Response:

In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)

▼ Storage:

Store in a well-ventilated place. Keep cool. (P403+P235)

Disposal:

Dispose of contents/container in accordance with local regulation. (P501)

▼ Hazardous substances:

Contains no substances that need to be listed on the label.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Chemical name	Common name/synonyms	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated light		CAS No.: 64742-47-8	60-80%	Asp. Tox. 1, H304	[19]
2-butoxyethanol		CAS No.: 111-76-2	5-10%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Solvent naphtha (petroleum), light arom.		CAS No.: 64742-95-6	3-5%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336	[19]
2-ethylhexyl nitrate		CAS No.: 27247-96-7	3-5%	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332	
Solvent naphtha (petroleum), heavy arom.		CAS No.: 64742-94-5	3-5%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336	[19]
1,2,4-trimethylbenzene		CAS No.: 95-63-6	1-3%	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335	
2,6-di-tert-butylphenol		CAS No.: 128-39-2	<1%	Skin Irrit. 2, H315	
naphthalene		CAS No.: 91-20-3	<1%	Acute Tox. 4, H302 Carc. 2, H351	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST-AID MEASURES

4.1. ▼ Description of first aid measures

General information:

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

▼ *Skin contact:*

IF ON SKIN: Wash with plenty of water and soap.



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

	Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.
<i>Eye contact:</i>	If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.
<i>Ingestion:</i>	If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.
<i>Burns:</i>	Not applicable.

4.2. ▼ Most important symptoms and effects, both acute and delayed

Headache, Methaemoglobinaemia (naphthalene)

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Combustible liquid

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health.

Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

extinguishing water to enter the sewage system and nearby surface waters.
If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Nitrogen oxides (NO_x)

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact a poison centre in order to obtain further advice. See section 1 "Emergency telephone number".

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.
Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. ▼ Precautions for safe handling

Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material:

Keep only in original packaging.

Storage conditions:

Dry, cool and well ventilated

Incompatible materials:

Oxidizing agents



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. ▼ Control parameters

ALBERTA

2-butoxyethanol

Long term exposure limit (8 hours) (ppm): 20

Long term exposure limit (8 hours) (mg/m³): 97

Annotations:

3 = Occupational exposure limit is based on irritation effects and its adjustment to compensate for unusual work schedules is not required.

naphthalene

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m³): 52

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m³): 79

Annotations:

1 = Substance may be readily absorbed through intact skin.

p-xylene;m-xylene;xylene;o-xylene

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m³): 434

Short term exposure limit (15 minutes) (ppm): 150

Short term exposure limit (15 minutes) (mg/m³): 651

Trimethylbenzene

Long term exposure limit (8 hours) (ppm): 25

Long term exposure limit (8 hours) (mg/m³): 123

Occupational Health and Safety Code 2009 Order, Alta Reg 87/2009 (revised in 2018)

BRITISH COLUMBIA

2-butoxyethanol

Time-Weighted Average Limit (TWA): 20 ppm

naphthalene

Time-Weighted Average Limit (TWA): 10 ppm

Annotations:

Skin = The substances contributes significantly to the overall exposure by the skin route.

p-xylene;m-xylene;xylene;o-xylene

Time-Weighted Average Limit (TWA): 100 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 150 ppm

Trimethylbenzene



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Time-Weighted Average Limit (TWA): 25 ppm
OHS Regulation Part 5: Chemical Agents and Biological Agents.

ONTARIO

2-butoxyethanol

Time-Weighted Average Limit (TWA): 20 ppm

naphthalene

Time-Weighted Average Limit (TWA): 10 ppm

Annotations:

"Skin" = Danger of cutaneous absorption.

p-xylene;m-xylene;xylene;o-xylene

Time-Weighted Average Limit (TWA): 100 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 150 ppm

Trimethylbenzene

Time-Weighted Average Limit (TWA): 25 ppm

Regulation 833 (Control of Exposure to Biological or Chemical Agents) and Ontario
Regulation 490/09 (Designated Substances)

QUEBEC

2-butoxyethanol

Long term exposure limit (8 hours) (ppm): 20

Annotations:

Note 3 = Where the use of these products is permitted.

naphthalene

Long term exposure limit (8 hours) (ppm): 10

Annotations:

Pc = Potentially significant contribution to the overall exposure by the cutaneous route. The cutaneous route includes mucous membranes and the eyes.

Note 3 = Where the use of these products is permitted.

p-xylene;m-xylene;xylene;o-xylene

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m³): 434

Trimethylbenzene

Long term exposure limit (8 hours) (ppm): 25

Annotations:

S = Sensitizer.

Regulation respecting occupational health and safety (Chapter S-2.1, r. 13)

SASKATCHEWAN

2-butoxyethanol

Long term exposure limit (8 hours) (ppm): 20

Short term exposure limit (15 minutes) (ppm): 30

naphthalene

Long term exposure limit (8 hours) (ppm): 10

Short term exposure limit (15 minutes) (ppm): 15

Annotations:

Skin = Potentially harmful after absorption through the skin or mucous membranes
 p-xylene;m-xylene;xylene;o-xylene
 Long term exposure limit (8 hours) (ppm): 100
 Short term exposure limit (15 minutes) (ppm): 150
 Trimethylbenzene
 Long term exposure limit (8 hours) (ppm): 25
 Short term exposure limit (15 minutes) (ppm): 30
 The Occupational Health and Safety Regulations, 2020, Chapter S15.1 Reg 10.

8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations:

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios:

There are no exposure scenarios implemented for this product.

Exposure limits:

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures:

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

▼ *Hygiene measures:*

Take off contaminated clothing and wash it before reuse.

▼ *Measures to avoid environmental exposure:*

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally:

Use only protective equipment with a recognized certification mark, e.g. the UL mark.

Respiratory Equipment:

Work situation	Type	Class	Colour	Standards	
In case of inadequate ventilation	Combination filter AXP1		Brown/White	EN14387, EN143	

Skin protection:

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection:

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
When there is risk of splash- / intermittent exposure	Cotton/Nitril	-	> 240	EN374-2, EN16523-1, EN388	

Eye protection:

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
▼ <i>Colour:</i>	Green, Yellow
<i>Odour:</i>	Petroleum-like
<i>Odour threshold (ppm):</i>	No data available.
<i>pH:</i>	Not determined
<i>Density (g/cm³):</i>	-
<i>Relative density:</i>	0.80-0.83
<i>Kinematic viscosity:</i>	Not determined
<i>Particle characteristics:</i>	Does not apply to liquids.

Phase changes

<i>Melting point/Freezing point (°C):</i>	Not determined
<i>Softening point/range (°F):</i>	Does not apply to liquids.
<i>Boiling point (°C):</i>	92
<i>Vapour pressure:</i>	Not determined
<i>Relative vapour density:</i>	No data available.
<i>Decomposition temperature (°C):</i>	No data available.

Data on fire and explosion hazards



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

<i>Flash point (°C):</i>	62
<i>Flammability (°C):</i>	Not applicable
<i>Auto-ignition temperature (°C):</i>	215
<i>Explosion limits (% v/v):</i>	Not applicable

Solubility

<i>Solubility in water:</i>	Insoluble
<i>n-octanol/water coefficient (LogKow):</i>	No data available.
<i>Solubility in fat (g/L):</i>	No data available.

9.2. Other information

<i>Evaporation rate (n-butylacetate = 100):</i>	Not determined
<i>Other physical and chemical parameters:</i>	No data available.
<i>Oxidizing properties:</i>	No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.
Heat, flames, and sparks

10.5. Incompatible materials

Oxidizing agents

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

▼ Acute toxicity

Based on available data, the classification criteria are not met.

▼ Skin corrosion/irritation

Causes skin irritation.

▼ Serious eye damage/irritation



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Based on available data, the classification criteria are not met.

▼ **Respiratory sensitisation**

Based on available data, the classification criteria are not met.

▼ **Skin sensitisation**

Based on available data, the classification criteria are not met.

▼ **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

▼ **Carcinogenicity**

Based on available data, the classification criteria are not met.

▼ **Reproductive toxicity**

Based on available data, the classification criteria are not met.

▼ **STOT-single exposure**

Based on available data, the classification criteria are not met.

▼ **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

▼ **Aspiration hazard**

Based on available data, the classification criteria are not met.

▼ **Long term effects**

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Other information

2-butoxyethanol has been classified by IARC as a group 3 carcinogen.

naphthalene has been classified by IARC as a group 2B carcinogen.

p-xylene;m-xylene;xylene;o-xylene has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. ▼ Toxicity

Based on available data, the classification criteria are not met.

12.2. ▼ Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. ▼ Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

▼ Waste treatment methods

naphthalene is listed with EPA Hazardous Waste Number: U165

p-xylene;m-xylene;xylene;o-xylene is listed with EPA Hazardous Waste Number: U239

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
TDG	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Transport hazard class: 9 Label: 9 Classification code: M6 	III	No	Limited quantities: 5 L Tunnel restriction code: (-) See below for additional information.
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

These substances when carried in single or combination packaging's containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of TDG/IMDG/IATA provided the packaging's meet the general provisions of packaging.

-

TDG / See Schedule 1 for any information on special provisions, requirements, or warnings in connection with transport. See part 3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. ▼ Canadian lists

NDSL:

None of the components are listed

▼ *DSL:*

Distillates (petroleum), hydrotreated light
2-butoxyethanol
Solvent naphtha (petroleum), light arom.
2-ethylhexyl nitrate
Solvent naphtha (petroleum), heavy arom.
1,2,4-trimethylbenzene
2,6-di-tert-butylphenol
naphthalene
p-xylene;m-xylene;xylene;o-xylene
Trimethylbenzene

15.4. Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

15.5. Demands for specific education

No specific requirements.

Additional information

Not applicable.

15.7. Chemical safety assessment

No

Sources

Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SECTION 16: OTHER INFORMATION

▼ Full text of H-phrases as mentioned in section 3

H226, Flammable liquid and vapour.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H312, Harmful in contact with skin.
H315, Causes skin irritation.
H319, Causes serious eye irritation.
H332, Harmful if inhaled.
H335, May cause respiratory irritation.
H336, May cause drowsiness or dizziness.
H351, Suspected of causing cancer.

The full text of identified uses as mentioned in section 1

None known.



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Abbreviations and acronyms

ANSI = American National Standards Institute
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
DSL = Domestic Substances List
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
HHNOC = Health Hazards Not Otherwise Classified
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogKow = logarithm of the n-octanol/water coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NDSL = Non-domestic substances list
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PHNOC = Physical Hazards Not Otherwise Classified
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
SCL = A specific concentration limit.
SOR = Statutory Orders and Regulations
STEL = Short-term exposure limits
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TDG = Transportation of Dangerous Goods
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative
WHIMS = Workplace Hazardous Materials Information System

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by WHMIS 2022

The safety data sheet is validated by

NL

SDS date:

2026-03-27

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Country-language: CA-en