



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SAFETY DATA SHEET

Rislone DPF Cleaner

SECTION 1: IDENTIFICATION

1.1. Product identifier

Trade name: Rislone DPF Cleaner
Product no.: 34744

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Fuel additive
Uses advised against : None known.

1.3. Details of the supplier of the safety data sheet

Company and address: **Rislone**
P.O. Box 187
Holly, MI 48442
USA
(810) 603-1321
www.Rislone.com
E-mail: support@rislone.com
SDS date: 07 March 2025
SDS Version: 3.0
Date of previous version: 30 January 2025 (2.0)

1.4. Emergency telephone number

ChemTel Inc.
(800) 255-3924 (North America)
+1 (813) 248-0585 (International)

SECTION 2: HAZARD(S) IDENTIFICATION

Classified as hazardous according to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272).

2.1. ▼ Classification of the substance or mixture

Flam. Liq. 4; H227, Combustible liquid
Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.
Repr. 1B; H360, May damage fertility or the unborn child.
STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

▼ *Hazard pictogram(s):*





Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Signal word:

Danger

▼ *Hazard statement(s):*

Combustible liquid (H227)
May be fatal if swallowed and enters airways. (H304)
May damage fertility or the unborn child. (H360)
May cause damage to organs through prolonged or repeated exposure. (H373)

Precautionary statement(s):

General:

If medical advice is needed, have product container or label at hand. (P101)
Keep out of reach of children. (P102)

▼ *Prevention:*

Obtain special instructions before use. (P201)
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Do not allow contact with air. (P222)
Do not breathe vapour/mist. (P260)
Wear eye protection/protective gloves/protective clothing. (P280)

▼ *Response:*

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)
IF exposed or concerned: Get medical advice/attention. (P308+P313)
Get medical advice/attention if you feel unwell. (P314)
Do NOT induce vomiting. (P331)
In case of fire: Use water mist/carbon dioxide/alcohol-resistant foam to extinguish. (P370+P378)
Leaking gas fire: Do not extinguish, unless leak can be stopped safely. (P377)
In case of leakage, eliminate all ignition sources. (P381)

▼ *Storage:*

Store in a well-ventilated place. (P403)
Store in a well-ventilated place. Keep cool. (P403+P235)
Store locked up. (P405)

Disposal:

Dispose of contents/container in accordance with local regulation (P501)

▼ *Hazardous substances:*

Distillates (petroleum), hydrotreated light paraffinic; Baseoil - unspecified; [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] Solvent naphtha (petroleum), heavy arom. ethylbenzene

Additional labelling:

Not applicable.

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.]	CAS No.: 64742-55-8	25-40%	Asp. Tox. 1, H304	[19]
p-xylene;m-xylene;xylene;o-xylene	CAS No.: 1330-20-7	5-10%	Flam. Liq. 3, H226 Acute Tox. 4, H312 Skin Irrit. 2, H315 Acute Tox. 4, H332	
Solvent naphtha (petroleum), heavy arom.	CAS No.: 64742-94-5	1-5%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336	[19]



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

ethylbenzene	CAS No.: 100-41-4	0-5%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Acute Tox. 4, H332 STOT RE 2, H373	
naphthalene	CAS No.: 91-20-3	<1%	Acute Tox. 4, H302 Carc. 2, H351	
phenol, 2-dodecyl-, branched;phenol, dodecyl-, branched;phenol, 3- dodecyl-, branched;phenol, (tetrapropenyl) derivatives;phenol, 4- dodecyl-, branched	CAS No.: 210555-94-5	<0.25%	Skin Corr. 1C, H314 Eye Dam. 1, H318 Repr. 1B, H360	[19]
ethylenediamine;1,2- diaminoethane	CAS No.: 107-15-3	<0.25%	Flam. Liq. 3, H226 Acute Tox. 4, H302 Acute Tox. 3, H311 Skin Corr. 1B, H314 Skin Sens. 1B, H317 Acute Tox. 4, H332 Resp. Sens. 1B, H334	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: FIRST-AID MEASURES

4.1. Description of first aid measures

General information:

If breathing is irregular, drowsiness, loss of consciousness or cramps: Call 911 and give immediate treatment (first aid).
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation:

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Skin contact:

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.
If skin irritation occurs: Get medical advice/attention.

Eye contact:

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

Ingestion:

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical attention for at least 48 hours.

Burns:

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Headache, Methaemoglobinaemia (naphthalene)

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Combustible liquid

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact a poison centre in order to obtain further advice. See section 1 "Emergency telephone number".

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.
Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Avoid direct contact with the product.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material:

Always store in containers of the same material as the original container.

Storage conditions:

Dry, cool and well ventilated

Incompatible materials:

Combustible materials

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

ALBERTA



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

p-xylene;m-xylene;xylene;o-xylene

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m³): 434

Short term exposure limit (15 minutes) (ppm): 150

Short term exposure limit (15 minutes) (mg/m³): 651

ethylbenzene

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m³): 434

Short term exposure limit (15 minutes) (ppm): 125

Short term exposure limit (15 minutes) (mg/m³): 543

naphthalene

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m³): 52

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m³): 79

Annotations:

1 = Substance may be readily absorbed through intact skin.

ethylenediamine;1,2-diaminoethane

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m³): 25

Annotations:

1 = Substance may be readily absorbed through intact skin.

Occupational Health and Safety Code 2009 Order, Alta Reg 87/2009 (revised in 2018)

BRITISH COLUMBIA

p-xylene;m-xylene;xylene;o-xylene

Time-Weighted Average Limit (TWA): 100 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 150 ppm

ethylbenzene

Time-Weighted Average Limit (TWA): 20 ppm

naphthalene

Time-Weighted Average Limit (TWA): 10 ppm

Annotations:

Skin = The substances contributes significantly to the overall exposure by the skin route.

ethylenediamine;1,2-diaminoethane

Time-Weighted Average Limit (TWA): 10 ppm

Annotations:

Skin = The substances contributes significantly to the overall exposure by the skin route.

OHS Regulation Part 5: Chemical Agents and Biological Agents.

ONTARIO

p-xylene;m-xylene;xylene;o-xylene

Time-Weighted Average Limit (TWA): 100 ppm

Short-Term Exposure Limit (STEL) / Ceiling Limit (C): 150 ppm

ethylbenzene

Time-Weighted Average Limit (TWA): 20 ppm

naphthalene



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Time-Weighted Average Limit (TWA): 10 ppm

Annotations:

"Skin" = Danger of cutaneous absorption.

ethylenediamine;1,2-diaminoethane

Time-Weighted Average Limit (TWA): 10 ppm

Annotations:

"Skin" = Danger of cutaneous absorption.

Regulation 833 (Control of Exposure to Biological or Chemical Agents) and Ontario Regulation 490/09 (Designated Substances)

QUEBEC

p-xylene;m-xylene;xylene;o-xylene

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m³): 434

ethylbenzene

Long term exposure limit (8 hours) (ppm): 20

Annotations:

Note 3 = Where the use of these products is permitted.

naphthalene

Long term exposure limit (8 hours) (ppm): 10

Annotations:

Pc = Potentially significant contribution to the overall exposure by the cutaneous route. The cutaneous route includes mucous membranes and the eyes.

Note 3 = Where the use of these products is permitted.

ethylenediamine;1,2-diaminoethane

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m³): 25

Annotations:

Pc = Potentially significant contribution to the overall exposure by the cutaneous route. The cutaneous route includes mucous membranes and the eyes.

S = Sensitizer.

Regulation respecting occupational health and safety (Chapter S-2.1, r. 13)

SASKATCHEWAN

p-xylene;m-xylene;xylene;o-xylene

Long term exposure limit (8 hours) (ppm): 100

Short term exposure limit (15 minutes) (ppm): 150

ethylbenzene

Long term exposure limit (8 hours) (ppm): 100

Short term exposure limit (15 minutes) (ppm): 125

Annotations:

T20 = Substance is also included in Table 20 of The Occupational Health and Safety Regulations and subject to Sections 306 and 311

naphthalene

Long term exposure limit (8 hours) (ppm): 10

Short term exposure limit (15 minutes) (ppm): 15

Annotations:

Skin = Potentially harmful after absorption through the skin or mucous membranes

ethylenediamine;1,2-diaminoethane

Long term exposure limit (8 hours) (ppm): 10

Short term exposure limit (15 minutes) (ppm): 15

Annotations:



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Skin = Potentially harmful after absorption through the skin or mucous membranes
The Occupational Health and Safety Regulations, 2020, Chapter S15.1 Reg 10.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations:

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios:

There are no exposure scenarios implemented for this product.

Exposure limits:

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures:

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked. Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures:

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure:

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally:

Use only protective equipment with a recognized certification mark, e.g. the UL mark.

Respiratory Equipment:

No specific requirements

Skin protection:

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Gloves	-	-	EN374	



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Eye protection:

Type	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Colour:</i>	Amber
<i>Odour:</i>	Petroleum distillates
<i>Odour threshold (ppm):</i>	No data available
<i>pH:</i>	No data available
▼ <i>Density (g/cm³):</i>	-
▼ <i>Relative density:</i>	0.812
▼ <i>Kinematic viscosity:</i>	No data available.
<i>Particle characteristics:</i>	No data available

Phase changes

<i>Melting point/Freezing point (°C):</i>	No data available
<i>Softening point/range (°F):</i>	Does not apply to liquids.
▼ <i>Boiling point (°C):</i>	>37.7
<i>Vapour pressure:</i>	No data available
<i>Relative vapour density:</i>	No data available
<i>Decomposition temperature (°C):</i>	No data available

Data on fire and explosion hazards

<i>Flash point (°C):</i>	63 Test method: EN ISO 13736
<i>Flammability (°C):</i>	No data available
<i>Auto-ignition temperature (°C):</i>	No data available
<i>Explosion limits (% v/v):</i>	No data available

Solubility

▼ <i>Solubility in water:</i>	Insoluble
▼ <i>n-octanol/water coefficient (LogKow):</i>	No data available.
<i>Solubility in fat (g/L):</i>	No data available

9.2. Other information

<i>Sensitivity to shock:</i>	No
<i>Evaporation rate (n-butylacetate = 100):</i>	No data available
<i>Other physical and chemical parameters:</i>	No data available.



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Oxidizing properties:

No data available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Heat, flames, and sparks
Excessive heat

10.5. Incompatible materials

Strong acids
Strong oxidizing agents
Strong bases

10.6. ▼ Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

▼ Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Long term effects

None known.

Other information

p-xylene;m-xylene;xylene;o-xylene has been classified by IARC as a group 3 carcinogen.

ethylbenzene has been classified by IARC as a group 2B carcinogen.

naphthalene has been classified by IARC as a group 2B carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No data available.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

p-xylene;m-xylene;xylene;o-xylene is listed with EPA Hazardous Waste Number: U239

naphthalene is listed with EPA Hazardous Waste Number: U165

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
TDG	-	-	-	-	-	-
IMDG	-	-	-	-	-	-



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informat ion:
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

▼ **Additional information**

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. ▼ Canadian lists

▼ *NDSL*:

phenol, 2-dodecyl-, branched;phenol, dodecyl-, branched;phenol, 3-dodecyl-, branched;phenol, (tetrapropenyl) derivatives;phenol, 4-dodecyl-, branched

▼ *DSL*:

Distillates (petroleum), hydrotreated light paraffinic;Baseoil - unspecified;[A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] p-xylene;m-xylene;xylene;o-xylene Solvent naphtha (petroleum), heavy arom. ethylbenzene naphthalene ethylenediamine;1,2-diaminoethane

15.4. Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

15.5. Demands for specific education

No specific requirements.

Additional information



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

Not applicable.

15.7. Chemical safety assessment

No

Sources

Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.
H226, Flammable liquid and vapour.
H302, Harmful if swallowed.
H304, May be fatal if swallowed and enters airways.
H311, Toxic in contact with skin.
H312, Harmful in contact with skin.
H314, Causes severe skin burns and eye damage.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H318, Causes serious eye damage.
H332, Harmful if inhaled.
H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336, May cause drowsiness or dizziness.
H351, Suspected of causing cancer.
H360, May damage fertility or the unborn child.
H373, May cause damage to organs through prolonged or repeated exposure.

The full text of identified uses as mentioned in section 1

None known.

Abbreviations and acronyms

ANSI = American National Standards Institute
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
DSL = Domestic Substances List
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
HHNOC = Health Hazards Not Otherwise Classified
IARC = International Agency for Research on Cancer
IATA = International Air Transport Association
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NDSL = Non-domestic substances list
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PHNOC = Physical Hazards Not Otherwise Classified
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
SCL = A specific concentration limit.
SOR = Statutory Orders and Regulations
STEL = Short-term exposure limits



Conforms to Hazardous Products Regulation SOR/2015-17 (as amended by SOR/2022-272)

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TDG = Transportation of Dangerous Goods

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

WHIMS = Workplace Hazardous Materials Information System

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by WHMIS 2022

The safety data sheet is validated by

NL

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product.

Information in this safety data sheet cannot be used as a product specification.

Country-language: CA-en