



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

## SAFETY DATA SHEET

# Rislone CAT Complete

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

*Trade name:* Rislone CAT Complete  
*Product no.:* 44720, 34720  
*Unique formula identifier (UFI):* YEUY-R3U9-U00J-C9PQ

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

*Relevant identified uses of the substance or mixture:* Fuel additive  
For private use  
*Uses advised against :* None known.

#### 1.3. Details of the supplier of the safety data sheet

*Company and address:* **RISLONE Nordic AB**  
Rydståvägen 45  
S-424 91 OLOFSTORP  
Sweden  
+46 (0)31 55 50 88  
<https://www.rislonenordic.com/>

*Contact person:* Support Department  
*E-mail:* [info@rislonenordic.com](mailto:info@rislonenordic.com)  
*Revision:* 07 May 2026  
*SDS Version:* 9.0  
*Date of previous version:* 10 February 2025 (8.0)

#### 1.4. ▼ Emergency telephone number

ChemTel Inc.  
(800) 255-3924 (North America)  
+1 (813) 248-0585 (International)

22 59 13 00 (Poison Information Center)  
112 (Emergency Poison Information Center)

### SECTION 2: HAZARDS IDENTIFICATION

Classified according to Regulation (EC) No. 1272/2008 (CLP).

## 2.1. ▼ Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation.

Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

▼ Hazard pictogram(s):



▼ Signal word:

Warning

▼ Hazard statement(s):

Causes skin irritation. (H315)

Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s):

▼ General:

If medical advice is needed, have product container or label at hand. (P101)  
Keep out of reach of children. (P102)

▼ Prevention:

Wash hands and exposed skin thoroughly after handling. (P264)  
Avoid release to the environment. (P273)  
Wear protective gloves/protective clothing/eye protection/face protection. (P280)

Response:

IF SWALLOWED: Immediately call a POISON CENTER/doctor. (P301+P310)  
Do NOT induce vomiting. (P331)

▼ Storage:

Not applicable.

▼ Disposal:

Dispose of contents/container in accordance with local regulation. (P501)

Hazardous substances:

2-butoxyethanol  
p-xylene;m-xylene;xylene;o-xylene  
Tricarbonyl(methylcyclopentadienyl)manganese

Additional labelling:

UFI: YEUY-R3U9-U00J-C9PQ

## 2.3. Other hazards

Additional warnings:

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substances

Not applicable. This product is a mixture.

#### 3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Distillates (petroleum), hydrotreated light paraffinic	CAS No.: 64742-55-8 EC No.: 265-158-7 REACH: 01-2119487077-29-XXXX Index No.: 649-468-00-3	25-40%	Asp. Tox. 1, H304	[12], [19]
2-butoxyethanol	CAS No.: 111-76-2 EC No.: 203-905-0 REACH: 01-2119475108-36-XXXX Index No.: 603-014-00-0	5-10%	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	[1]
Distillates (petroleum), hydrotreated light	CAS No.: 64742-47-8 EC No.: 265-149-8 REACH: 01-2119474881-29-XXXX Index No.: 649-422-00-2	3-5%	Asp. Tox. 1, H304	[19]
Paraffins (petroleum), normal C5-20	CAS No.: 64771-72-8 EC No.: 265-233-4 REACH: 01-2119930064-48-XXXX Index No.:	3-5%	Asp. Tox. 1, H304	[19]
p-xylene;m-xylene;xylene;o-xylene	CAS No.: 1330-20-7 EC No.: 215-535-7 REACH: 01-2119488216-32-XXXX Index No.: 601-022-00-9	1-3%	Flam. Liq. 3, H226 Acute Tox. 4, H312 Skin Irrit. 2, H315 Acute Tox. 4, H332	[1]
Solvent naphtha (petroleum), light arom.	CAS No.: 64742-95-6 EC No.: 265-199-0 REACH: 01-2119486773-24-XXXX Index No.: 649-356-00-4	1-3%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	[15], [19]
Monoalkylaryl alkoxyate aminated	CAS No.: 2306287-53-4 EC No.: 870-278-3 REACH: Index No.:	1-3%	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 2, H411	



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

ethylbenzene	CAS No.: 100-41-4 EC No.: 202-849-4 REACH: 01-2119489370-35-XXXX Index No.: 601-023-00-4	<1%	Asp. Tox. 1, H304 Acute Tox. 4, H332 STOT RE 2, H373 Aquatic Chronic 3, H412	[1]
Tricarbonyl(methylcyclopentadienyl)manganese	CAS No.: 12108-13-3 EC No.: 235-166-5 REACH: 01-2119495971-23-XXXX Index No.:	<1%	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 1, H330 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
1,2,4-trimethylbenzene	CAS No.: 95-63-6 EC No.: 202-436-9 REACH: 01-2119472135-42-XXXX Index No.: 601-043-00-3	<1%	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
Mesitylene	CAS No.: 108-67-8 EC No.: 203-604-4 REACH: 01-2119463878-19-XXXX Index No.:	<0.25%	Flam. Liq. 3, H226 STOT SE 3, H335 Aquatic Chronic 2, H411	[1]
1,2,3-trimethylbenzene	CAS No.: 526-73-8 EC No.: 208-394-8 REACH: Index No.:	<0.1%	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2, H319	
Cumene;propylbenzene	CAS No.: 98-82-8 EC No.: 202-704-5 REACH: 01-2119473983-24-XXXX Index No.: 601-024-00-X	<0.05%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 Aquatic Chronic 3, H412	
naphthalene	CAS No.: 91-20-3 EC No.: 202-049-5 REACH: 01-2119561346-37-XXXX Index No.: 601-052-00-2	<0.05%	Acute Tox. 4, H302 Carc. 2, H351 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

### Other information

[1] European occupational exposure limit.

[12] The classification as a carcinogen will not be taken into account as the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic



aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method' (CLP, Annex VI, note L).

[15] The classification as a carcinogen / mutagen will not be taken into account as the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7) (CLP, Annex VI, note P).

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

#### *General information:*

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### *Inhalation:*

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### ▼ *Skin contact:*

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

#### *Eye contact:*

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes.

Remove contact lenses. Seek medical assistance and continue flushing during transport.

#### *Ingestion:*

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

*Burns:* Not applicable.

**4.2. ▼ Most important symptoms and effects, both acute and delayed**

Headache, Methaemoglobinaemia (naphthalene)

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**Information to medics**

Bring this safety data sheet or the label from this product.

---

**SECTION 5: FIREFIGHTING MEASURES**

**5.1. Extinguishing media**

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.  
Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

**5.2. Special hazards arising from the substance or mixture**

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters. If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:  
Carbon oxides (CO / CO<sub>2</sub>)

**5.3. ▼ Advice for firefighters**

Firefighters should wear appropriate protective equipment and self-contained breathing apparatus with a full face mask.

---

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1. ▼ Personal precautions, protective equipment and emergency procedures**

Avoid direct contact with spilled substances.  
Ensure adequate ventilation, especially in confined areas.  
Contaminated areas may be slippery.

**6.2. Environmental precautions**

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

**6.3. ▼ Methods and material for containment and cleaning up**

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

*Recommended storage material:*

Properly labeled containers

*Storage conditions:*

Dry, cool and well ventilated  
Tightly closed container

*Incompatible materials:*

heat, sparks, flame, and other sources of ignition  
Combustible materials

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. ▼ Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1 (Oljetåke (mineraloljepartikler))

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 3 (beregnet verdi)

Distillates (petroleum), hydrotreated light paraffinic

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1 (Oljetåke (mineraloljepartikler))

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 3 (beregnet verdi)

2-butoxyethanol

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 50

Long term exposure limit (8 hours) (ppm): 10

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 75 (beregnet verdi)

Short term exposure limit (15 minutes) (ppm): 20 (beregnet verdi)



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

---

Annotations:

E = The EU has set an indicative limit value and/or remark for the substance.

H = Chemicals that can be absorbed through the skin.

p-xylene;m-xylene;xylene;o-xylene

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 108

Long term exposure limit (8 hours) (ppm): 25

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 135 (beregnet verdi)

Short term exposure limit (15 minutes) (ppm): 37,5 (beregnet verdi)

Annotations:

E = The EU has set an indicative limit value and/or remark for the substance.

H = Chemicals that can be absorbed through the skin.

ethylbenzene

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 20

Long term exposure limit (8 hours) (ppm): 5

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 30 (beregnet verdi)

Short term exposure limit (15 minutes) (ppm): 10 (beregnet verdi)

Annotations:

E = The EU has set an indicative limit value and/or remark for the substance.

H = Chemicals that can be absorbed through the skin.

K = Carcinogenic substance.

Tricarbonyl(methylcyclopentadienyl)manganese

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 0,2 (som Mn)

Long term exposure limit (8 hours) (ppm): 0,1 (som Mn)

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 0,6 (beregnet verdi, som Mn)

Short term exposure limit (15 minutes) (ppm): 0,3 (beregnet verdi, som Mn)

Annotations:

E = The EU has set an indicative limit value and/or remark for the substance.

H = Chemicals that can be absorbed through the skin.

1,2,4-trimethylbenzene

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 100

Long term exposure limit (8 hours) (ppm): 20

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 150 (beregnet verdi)

Short term exposure limit (15 minutes) (ppm): 30 (beregnet verdi)

Annotations:

E = The EU has set an indicative limit value and/or remark for the substance.

Mesitylene

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 100

Long term exposure limit (8 hours) (ppm): 20

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 150 (beregnet verdi)

Short term exposure limit (15 minutes) (ppm): 30 (beregnet verdi)

Annotations:



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

E = The EU has set an indicative limit value and/or remark for the substance.

naphthalene

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 50

Long term exposure limit (8 hours) (ppm): 10

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 75 (beregnet verdi)

Short term exposure limit (15 minutes) (ppm): 20 (beregnet verdi)

Annotations:

E = The EU has set an indicative limit value and/or remark for the substance.

H = Chemicals that can be absorbed through the skin.

K = Carcinogenic substance.

Regulations concerning action and limit values for physical and chemical agents in the working environment and classified biological agents (Regulations concerning Action and Limit values) FOR-2011-12-06-1358. Last update: FOR-2026-04-10-580.

#### ▼ DNEL

1,2,4-trimethylbenzene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	9,512 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	16,171 mg/kg bw/day
Long term – Local effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	15 mg/kg bw/day

2-butoxyethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	59 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	98 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	147 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	246 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	426 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	1,091 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	6.3 mg/kg bw/day



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Short term – Systemic effects - General population	Oral	26.7 mg/kg bw/day
--	------	-------------------

Distillates (petroleum), hydrotreated heavy paraffinic

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	0.97 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	5.58 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	2.73 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	0.74 mg/kg bw/day

Distillates (petroleum), hydrotreated light paraffinic

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	0.97 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	5.58 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	2.73 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	0.74 mg/kg bw/day

ethylbenzene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	180 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	442 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	15 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	77 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	293 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	1.6 mg/kg bw/day

Mesitylene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	9,512 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	16,171 mg/kg bw/day
Long term – Local effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	29.4 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	100 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	15 mg/kg bw/day

naphthalene



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	3.57 mg/kg bw/day
Long term – Local effects - Workers	Inhalation	25 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	25 mg/m <sup>3</sup>

p-xylene;m-xylene;xylene;o-xylene

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	125 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	212 mg/kg bw/day
Long term – Local effects - General population	Inhalation	65.3 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	221 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	65.3 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	221 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	260 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	442 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	260 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	442 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	2.5 mg/kg bw/day

Solvent naphtha (petroleum), light arom.

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	178.57 mg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	837.5 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	640 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	1,066.67 mg/m <sup>3</sup>
Short term – Systemic effects - General population	Inhalation	1,152 mg/m <sup>3</sup>
Short term – Systemic effects - Workers	Inhalation	1,286.4 mg/m <sup>3</sup>

Tricarbonyl(methylcyclopentadienyl)manganese

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	0.062 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	0.11 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	0.11 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	0.6 mg/m <sup>3</sup>

#### ▼ PNEC

1,2,4-trimethylbenzene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		36.7 µg/L



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Freshwater sediment		4.16 mg/kg
Intermittent release (freshwater)		20.8 µg/L
Intermittent release (marine water)		2.08 µg/L
Marine water		3.67 µg/L
Marine water sediment		0.416 mg/kg
Sewage treatment plant		3.182 mg/L
Soil		0.81 mg/kg

#### 2-butoxyethanol

Route of exposure:	Duration of Exposure:	PNEC:
Sewage treatment plant		66 mg/L

#### Distillates (petroleum), hydrotreated heavy paraffinic

Route of exposure:	Duration of Exposure:	PNEC:
Predators		9.33 mg/kg

#### Distillates (petroleum), hydrotreated light paraffinic

Route of exposure:	Duration of Exposure:	PNEC:
Predators		9.33 mg/kg

#### ethylbenzene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0.1 mg/L
Freshwater sediment		13.7 mg/kg
Intermittent release (freshwater)		0.1 mg/L
Marine water		0.01 mg/L
Marine water sediment		1.37 mg/kg
Predators		0.02 g/kg
Sewage treatment plant		9.6 mg/L
Soil		2.68 mg/kg

#### Mesitylene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		40 µg/L
Freshwater sediment		3.11 mg/kg
Intermittent release (freshwater)		60 µg/L
Intermittent release (marine water)		6 µg/L
Marine water		4 µg/L
Marine water sediment		0.311 mg/kg
Sewage treatment plant		2.42 mg/L



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Soil		0.599 mg/kg
------	--	-------------

#### naphthalene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		2.4 µg/L
Freshwater sediment		67.2 µg/kg
Intermittent release (freshwater)		20 µg/L
Marine water		2.4 µg/L
Marine water sediment		67.2 µg/kg
Sewage treatment plant		2.9 mg/L
Soil		53.3 µg/kg

#### p-xylene;m-xylene;xylene;o-xylene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0.044 mg/L
Freshwater sediment		2.52 mg/kg
Intermittent release (freshwater)		0.01 mg/L
Intermittent release (marine water)		0.001 mg/L
Marine water		0.004 mg/L
Marine water sediment		0.252 mg/kg
Sewage treatment plant		1.6 mg/L
Soil		0.852 mg/kg

#### Tricarbonyl(methylcyclopentadienyl)manganese

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0.21 µg/L
Intermittent release (freshwater)		2.1 µg/L
Marine water		0.021 µg/L
Soil		16 µg/kg

### 8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

*General recommendations:*

Smoking, drinking and consumption of food is not allowed in the work area.

*Exposure scenarios:*

There are no exposure scenarios implemented for this product.

*Exposure limits:*

Professional users are subjected to the legally set maximum concentrations for

*Appropriate technical measures:*

occupational exposure. See occupational hygiene limit values above.

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

▼ *Hygiene measures:*

Take off contaminated clothing and wash it before reuse.

*Measures to avoid environmental exposure:*

Keep damming materials near the workplace. If possible, collect spillage during work.

**Individual protection measures, such as personal protective equipment**


*Generally:*

Use only CE marked protective equipment.


▼ *Respiratory Equipment:*

No specific requirements.

*Skin protection:*

Recommended	Type/Category	Standards	
Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.	-	-	

*Hand protection:*

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Gloves	-	-	EN374	

*Eye protection:*

Type	Standards	
Tight sealing safety goggles	Tight sealing safety goggles	

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

### 9.1. Information on basic physical and chemical properties

<i>Physical state:</i>	Liquid
<i>Colour:</i>	Brown
<i>Odour / Odour threshold:</i>	Petroleum-like
▼ <i>pH:</i>	No data available.
<i>Density (g/cm<sup>3</sup>):</i>	-
<i>Relative density:</i>	0.81
<i>Kinematic viscosity:</i>	No data available
<i>Particle characteristics:</i>	Does not apply to liquids.

#### Phase changes

<i>Melting point/Freezing point (°C):</i>	No data available
<i>Softening point/range (°C):</i>	Does not apply to liquids.
<i>Boiling point (°C):</i>	No data available
<i>Vapour pressure:</i>	No data available
▼ <i>Relative vapour density:</i>	No data available.
<i>Decomposition temperature (°C):</i>	No data available

#### Data on fire and explosion hazards

<i>Flash point (°C):</i>	67
<i>Flammability (°C):</i>	No data available
<i>Auto-ignition temperature (°C):</i>	No data available
▼ <i>Lower and upper explosion limit (% v/v):</i>	No data available.

#### Solubility

<i>Solubility in water:</i>	Insoluble
▼ <i>n-octanol/water coefficient (LogKow):</i>	No data available.
▼ <i>Solubility in fat (g/L):</i>	No data available.

### 9.2. Other information

<i>Other physical and chemical parameters:</i>	No data available.
▼ <i>Oxidizing properties:</i>	No data available.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

### 10.3. Possibility of hazardous reactions



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

---

None known.

**10.4. Conditions to avoid**

Heat, flames, and sparks

**10.5. Incompatible materials**

heat, sparks, flame, and other sources of ignition

Combustible materials

**10.6. ▼ Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

---

**SECTION 11: TOXICOLOGICAL INFORMATION**

---

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

Based on available data, the classification criteria are not met.

**▼ Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/irritation**

Based on available data, the classification criteria are not met.

**Respiratory sensitization**

Based on available data, the classification criteria are not met.

**Skin sensitisation**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

**Carcinogenicity**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**▼ Symptoms related to the physical, chemical and toxicological characteristics**

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

## 11.2. Information on other hazards

### ▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

### Other information

2-butoxyethanol has been classified by IARC as a group 3.

p-xylene;m-xylene;xylene;o-xylene has been classified by IARC as a group 3.

ethylbenzene has been classified by IARC as a group 2B.

naphthalene has been classified by IARC as a group 2B.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

### 12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

### 12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 6 - Acute toxicity

Dispose of contents/container to an approved waste disposal plant.

Disposal to the sewer is discouraged.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

*EWC code:*

Not applicable.



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

## Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR/ADN/RID	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

### ▼ Additional information

Not dangerous goods according to ADR/ADN/RID, IATA and IMDG.

Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.

-

### 14.6. Special precautions for user

Not applicable.

### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

*Restrictions for application:*

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

*Demands for specific education:*

No specific requirements.

*SEVESO - Categories / dangerous substances:*

Not applicable.

*REACH, Annex XVII:*

p-xylene;m-xylene;xylene;o-xylene is subject to REACH restrictions (entry 40).  
Solvent naphtha (petroleum), light arom. is subject to REACH restrictions (entry 40).  
1,2,4-trimethylbenzene is subject to REACH restrictions (entry 40).  
Mesitylene is subject to REACH restrictions (entry 40).



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

*Declaration of chemicals:*

If the product is imported or produced in more than 100 kg/year it is subject to registration in the Product Register because it is classified as hazardous.

*Additional information:*

Not applicable.

*Sources:*

Act no. 62 of 17th June 2005 relating to working environment, working hours and employment protection, etc. (Working Environment Act).  
Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.  
Regulation of 15 May 2015 no. 541 on declaring chemicals to the product register (Declaration Regulations)  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).  
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

## 15.2. Chemical safety assessment

No

## SECTION 16: OTHER INFORMATION

### ▼ Full text of H-phrases as mentioned in section 3

- H226, Flammable liquid and vapour.
- H301, Toxic if swallowed.
- H302, Harmful if swallowed.
- H304, May be fatal if swallowed and enters airways.
- H310, Fatal in contact with skin.
- H312, Harmful in contact with skin.
- H315, Causes skin irritation.
- H319, Causes serious eye irritation.
- H330, Fatal if inhaled.
- H332, Harmful if inhaled.
- H335, May cause respiratory irritation.
- H336, May cause drowsiness or dizziness.
- H351, Suspected of causing cancer.
- H373, May cause damage to organs through prolonged or repeated exposure.
- H400, Very toxic to aquatic life.



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

---

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

H412, Harmful to aquatic life with long lasting effects.

#### ▼ Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EC = Effective concentration

ED = Effective dose

EINECS = European Inventory of Existing Commercial chemical Substances

EL = Effective Loading

ErC = Concentration associated with x% growth rate response

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

HP = Hazardous Property code

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IC = X maximum inhibitory concentration

IMDG = International Maritime Dangerous Goods

LC = Lethal concentration

LCLo = Value is the lowest concentration of a material in air reported to have caused the death of animals or humans

LD = Lethal dose

LOAEC = Lowest Observed Adverse Effect Concentration

LOAEL = Lowest Observed Adverse Effect Level

LOEC = Lowest Observed Effect Concentration

LogKow = logarithm of the n-octanol/water coefficient

LL = Lethal Loading

M = For multiplication factor

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)



According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

---

NOAEC = No Observed Adverse Effect Concentration  
NOAEL = No Observed Adverse Effect Level  
NOEC = No Observed Effect Concentration  
NOELR = No Observable Effect Loading Rate  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

**▼ Additional information**

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).  
The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

**The safety data sheet is validated by**

NL

**Other**

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.  
The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.  
It is recommended to hand over this safety data sheet to the actual user of the product.  
Information in this safety data sheet cannot be used as a product specification.  
Country-language: NO-en