PRODUCT DATA SHEET

Radiator Stop Leak Tablets

Part #: 31177

50 g

ISO 9001 CERTIFIED COMPANY

Rislone® Radiator Stop Leak Tablets

Rislone® Cooling System Supplement Radiator Stop Leak Tablets inhibit the formation of rust and scale, neutralize pH imbalance, control electrolysis, lubricate and seal internal, external, and coolant-to-oil leaks. Same formula tablets used by many OEM auto and truck manufacturers around the world. Rislone Radiator Stop Leak is designed to enhance the use of antifreeze or can be used in water. When used in water alone, it is also recommended to use a cooling system anti-rust and water pump lube.



- Seals Leaks and Seepage
- Helps Control Electrolysis
- Lubricates Water Pump Seal
- Inhibits Rust & Corrosion
- Harmless to ALL Plastic, Metals, Hoses, & Connections
- Quick Dissolving Seal Tabs

Professional strength formula works with ALL types and colors of antifreeze coolant including conventional, extended life, waterless, and straight water.

INSTRUCTIONS:

Cooling systems that are dirty or partially clogged should be flushed before use.

1. Remove radiator cap when engine is cool.
2. Tablets may be crumbled or pre-dissolved (use warm tap water) for easier application. Install one tablet for each three litres of cooling system capacity. If vehicle does not have a regular radiator cap, remove top hose where it attaches to radiator and install tablets in hose and then reinstall hose.
3. Fill radiator and reservoir to proper level.
4. Reinstall radiator cap.
5. Drive/idle engine for 15 minutes at normal operating temperature.
6. If leak persists, a second application may be necessary.

Litres	Tablets
1.5 to 4.4	1
4.5 to 7.4	2
7.5 to 10.4	3
10.5 to 13.4	4
13.5 to 16.5	5

DOSAGE:

One package treats systems up to 15 litres. For larger systems, use one tablet for each 3 litres of cooling system capacity.

For continued protection of the entire cooling system, repeat Rislone application every 25 000 kilometers or once per year.