ISO 9001 CERTIFIED COMPANY

PRODUCT DATA SHEET

Super Leak Fix™

Part #: 34305

500 mL (16.9 FL OZ)

Rislone® Super Leak Fix™



Rislone® Super Leak Fix is formulated to work in multiple systems including all Engine Oil, Transmission, Power Steering, Hydraulic, and Differential & Gear. Use to stop current leaks, or as a preventative maintenance before leaks start. Premium seal renewing additives are designed to stop seal and gasket leaks caused by normal wear and age. Contains no solids, will not clog filter or harm system.

- **America's Most Trusted Stop Leak Brand Since 1947**
- **Multi-System Formula / 5X Sealer**
  - **Engine**
  - **Transmission**
  - **Power Steering**
  - **Hydraulic**
  - **Gear & Axle**
- **Safe and Easy To Use / Will Not Harm Seals**

Helps with small leaks (if you need to add fluid 1x per month), medium leaks (if you need to add fluid 1x per week), preventative maintenance (to prevent future leaks from happening), with engine oil (gasoline, hybrid, diesel), transmission fluid (automatic, manual, CVT), power steering fluid (pump, gear box, rack & pinion), hydraulic (jack, snow plow, tractor, construction), and gear (differential, axle, gearbox, transfer case).

INSTRUCTIONS:

Add Super Leak Fix to leaking system per dosage chart. Do not overfill.
Leaks usually stop in 300 km, or 2 days of use. If leak continues, second application may be required or mechanical attention is needed.
WARNING: Do not use in brake system or add to antifreeze/coolant.

DOSAGE:

- Engine and Transmission – Use full bottle
- Power Steering – Use ½ bottle
- Hydraulic, Differential, Small Engines – Use 100 mL per Liter of capacity
- Preventative Maintenance – Use ½ Recommended Dosage